Direct particle tracking observation and Brownian dynamics simulations of a single nanoparticle optically trapped by a plasmonic nanoaperture

Zhe Xu,[†] Wuzhou Song,^{†,‡} and Kenneth B. Crozier^{,†,§}*

[†]School of Physics, University of Melbourne, Victoria 3010, Australia

[‡]School of Materials Science and Engineering, Huazhong University of Science and Technology, Wuhan 430074, P. R. China

[§]Department of Electrical and Electronic Engineering, University of Melbourne, Victoria 3010, Australia

KEYWORDS: optical trapping, particle tracking, double nanohole, fluorescence microscopy, Brownian motion

ABSTRACT:

Optical trapping using plasmonic nanoapertures has proven to be an effective means for the contactless manipulation of nanometer-sized particles under low optical intensities. These particles have included polystyrene and silica nanospheres, proteins, coated quantum dots and magnetic nanoparticles. Here we employ fluorescence microscopy to directly observe the optical trapping process, tracking the position of a polystyrene nanosphere (20 nm diameter) trapped in water by a double nanohole (DNH) aperture in a gold film. We show that position distribution in the plane of the film has an elliptical shape. Comprehensive simulations are performed to gain insight into the trapping process, including of the distributions of the electric field, temperature, fluid velocity, optical force and potential energy. These simulations are combined with stochastic Brownian diffusion to directly model the dynamics of the trapping process, i.e. particle trajectories. We anticipate that the combination of direct particle tracking experiments with Brownian motion simulations will be valuable tool for the better understanding of fundamental mechanisms underlying nanostructure-based trapping. It could thus be helpful in the development of the future novel optical trapping devices.

The use of optical forces for the acceleration and trapping of micrometer-sized particles was first demonstrated by Arthur Ashkin in 1970.¹ It was later shown that a single tightly focused laser beam, termed optical tweezers, could be used to trap, transport and manipulate particles, and many applications in the biological and physical sciences have been introduced.²⁻⁵ In conventional optical tweezers, particles are trapped using the gradient forces exerted by laser beams focused with lenses. For the trapping of very small particles (tens of nanometers) however, these face challenges, because the forces are roughly proportional to particle volume⁶. A

consequence is that the field intensity must be increased to maintain trap stability to overcome the strong Brownian motion, but this can result in undesired thermal effects. Furthermore, in conventional optical tweezers, a lower bound on the focal spot size is set by the diffraction limit. This determines the precision with which an object can be trapped.

To circumvent the limitations for trapping smaller objects with conventional optical tweezers, the use of nanotweezers based on plasmonics⁷⁻²⁰ and other approaches, such as waveguides^{21, 22}, ring resonators^{23, 24}, and photonic crystal resonators^{25, 26}, has recently attracted keen interest. Plasmon-based optical nanotweezers can provide nanoscale local field enhancement and strong optical forces, and plasmonic nanoapertures have been of particular interest. Kwak et al demonstrated the trapping of fluorescent nanospheres (200 nm diameter) using a nanoaperture in a gold film.⁷ The trapping process was monitored by recording the transmission through the nanoaperture of the fluorescent emission from the nanosphere as a function of time.⁷ Juan et al demonstrated the trapping of 50 nm polystyrene beads with a nanoaperture.¹⁰ The trapping process was monitored by recording the transmission of the infrared trapping laser through the nanoaperture as a function of time.¹⁰ Other notable nanoaperture works include reports of the trapping of beads with diameters of 12 nm¹⁴, trapping using rectangular nanopore apertures¹⁵, trapping using nanoapertures at the ends of optical fibers¹⁶, the trapping of proteins and other biomolecules¹⁷, and fundamental studies on the trapping process¹⁸, namely on the role played by the nanoparticle being trapped in modifying the cavity resonance and thus the optical forces. We argue, however, that the direct observation of the dynamics of trapped nanoparticles (NPs), i.e. position as a function of time, could greatly assist the understanding and further development of optical nanotweezers. To the best of our knowledge, however, this has not been demonstrated in previous reports of the nanoaperture

trapping (e.g. Ref [7, 10, 14-18]). Rather, the trapping process in these reports was monitored by measuring the optical transmission (of trapping laser or of fluorescence from the trapped object) through the nanoaperture as a function of time. Step-like increases in transmission were observed, with each step interpreted as being due to the trapping of an individual nanoparticle. However, the information on trapping dynamics that experimental data sets comprising transmission vs time can provide is limited compared to what can be obtained with direct imaging.

In this work, we employ fluorescence microscopy to track the position of a polystyrene nanosphere (20 nm diameter) trapped by a double nanohole (DNH) aperture in a gold (Au) film. This allows us to determine the spatial confinement of the trapped particle, i.e. its position distribution, which was not possible with previous reports of nanoaperture trapping, in which transmission vs time was monitored [7, 10, 14-18]. Our results show that the measured position distributions have elliptical shapes and that tighter spatial confinement occurs at the higher laser intensity. We present comprehensive three-dimensional finite-element method (FEM) (COMSOL Multiphysics) simulations of the dynamics of the trapping process that combine optical modeling with Brownian motion, gravity and fluid dynamics (Stokes drag). The simulations emphasize the important role of the morphology of the DNH structure in the trapping process. The simulations furthermore provide information inaccessible with our experiments, predicting nanoparticle trajectories in three dimensions and on sub-nanosecond timescales. Our simulations also indicate that the DNH yields enhanced optical forces and potential energy, but with only modest temperature increases from Joule heating due to the good thermal conductivity provided by the gold film^{19, 20, 27}. We anticipate that the combination of the direct experimental observation of the dynamics of trapped particles with comprehensive multiphysics simulations

will be a powerful means for better understanding optical trapping with plasmonic and photonic nanostructures.

Figure 1a shows a scanning electron micrograph (SEM) top-view image of the DNH. The DNH is milled into a 100 nm thick Au film on a 1 mm thick glass substrate with a 5 nm titanium adhesion layer (EMF Corp., TA134) using a focused ion beam tool (FEI Helios Nanolab 600 Dual Beam FIB-SEM). Each circular hole in the DNH has a diameter of ~ 100 nm. The circular holes are separated by ~ 140 nm (center-to-center). We refer to the pointed features of the narrowest constriction of the DNH as the “tips”. These are separated by ~ 30 nm. The simulated structure is chosen with the goal of matching the geometrical parameters measured from the SEM. The region of the gold film between the holes is open, and is defined by two arcs (also referred to as tips as discussed above) whose closest separation is 30 nm. Further details on the simulations are provided in the Supporting Information. The glass substrate on which the gold film (containing the DNH) is formed is taken as having a refractive index of $n_{\text{glass}}=1.45$. The superstrate is water ($n_{\text{water}}=1.33$). The complex-valued relative permittivity of the gold is taken as $\epsilon_r=-48.45-i3.6$, which is appropriate for the wavelength of the trapping laser²⁸. Plane wave illumination (x -polarized, $\lambda=1064$ nm) is incident from the water side, travelling in $+z$ direction. This results in highly confined electric fields in the DNH through the excitation of surface plasmon polaritons (SPPs). Indeed, as shown in Figure 1b and c, for which no NPs are present, the electric field enhancement ($|E|/|E_0|$) is as large as ~ 16.3 times, which is defined by comparing the electric field amplitude with ($|E|$) and without ($|E_0|$) the gold film (containing the DNH). The field enhancement is largest within the gap between the tips and around the bottom of the DNH (i.e. at the glass side) when the incident field is polarized across the gap (x -axis). In Figure 1d, we plot the power dissipation density (Q_h) in a plane halfway through the DNH at the

illumination intensity we use in experiments ($I_0=6.67 \text{ mW}/\mu\text{m}^2$). Due to the large imaginary part of the relative permittivity of gold, most of the power dissipation is concentrated in the gold near the surface of the DNH, and is small elsewhere. The power dissipation density profile also strongly depends on the DNH geometry and is highly non-uniform. Figure 1e schematically illustrates our experimental set-up, with further details provided in the Supporting Information. The sample is mounted upside-down and aligned using a piezoelectric stage with a sub-nanometer position resolution. The trapping is monitored by observing the NP fluorescence. An *x*-polarized laser beam ($\lambda=1064 \text{ nm}$) is focused by an oil immersion objective (100 $\times$, NA=1.3) into a $\sim 20 \mu\text{m}$ thick perfusion chamber containing distilled water (UltraPure DNase/RNase-Free), polystyrene NPs ($n_{NP}=1.6$, FluoSpheres, 20 nm diameter, carboxylate-modified, Nile Red, Life Technologies) and a trace amount of surfactant (Tween 20, 0.05% v/v). The spot size is $\sim 1.2 \mu\text{m}$. A loosely-focused green laser beam ($\lambda=532 \text{ nm}$) is projected along the same optical path to excite fluorescence, which is imaged onto a sensitive electron multiplying camera (EM-CCD, ProEM-HS: 512 $\times$ 512, Princeton Instruments) operated at a frame rate of 30 frames per second (fps). The input intensity of the green laser is significantly weaker than that of the trapping laser and is therefore expected to produce negligible optical forces. Each pixel on the EM-CCD sensor array is $16 \mu\text{m} \times 16 \mu\text{m}$, which translates to $160 \text{ nm} \times 160 \text{ nm}$ in the sample plane with the 100 $\times$ magnification objective.

Joule heating can have a substantial effect in plasmonic trapping, resulting in often undesired temperature increases of the plasmonic nanostructure, the trapped object (e.g. NP) and the water^{29, 30}. The temperature rise can furthermore result in substantial thermophoresis and thermal-induced fluid convection³¹⁻³³. When a DNH is illuminated by a trapping laser, heat is generated in response to the absorbed power (Figure 1d) and released to the surroundings. Since

thermal processes in metals are fast³³, a steady state is rapidly reached, producing a temperature gradient and buoyancy-driven natural convection in the chamber^{20, 27, 33}. We carry out numerical simulations of the temperature distribution and convection velocity field of the surrounding water for a DNH on glass substrate illuminated at a wavelength of 1064 nm. These simulations combine optics with thermodynamics and hydrodynamics³³, and further details are provided in the Supporting Information. Key results are provided as Figure 2. As shown in Figure 2a, a maximum temperature rise (ΔT) of ~ 6 K is predicted for illumination at the intensity used in experiments ($I_0 = 6.67 \text{ mW}/\mu\text{m}^2$). The temperature distribution is very uniform around the DNH. Near the DNH, the strong heat source density leads to the temperature being high, while far from the DNH, the heat source is weaker, and the Au film is close to its initial temperature (i.e. without illumination, prescribed $T_0 = 293.15 \text{ K}$). Since gold has much higher thermal conductivity than glass and water ($\kappa_{\text{Au}} \sim 317 \text{ WK}^{-1}\text{m}^{-1}$, $\kappa_{\text{glass}} \sim 1 \text{ WK}^{-1}\text{m}^{-1}$, $\kappa_{\text{water}} \sim 0.58 \text{ WK}^{-1}\text{m}^{-1}$)³⁴, the heat generated by optical absorption near the DNH surface is readily conducted into the surrounding gold film, rather than into the water or the substrate. In other words, the gold film acts as a heat-sink^{19, 20} and helps reduce localized heating. This contrasts with isolated nanoantennas, for which strong illumination can result in reshaping and melting^{19, 27, 29, 33}. In Figure 2b-d, the simulated thermal-induced convection flow distributions are plotted on various cross-sections. Both magnitude (color map: nm/s) and direction (white arrows, magnitude proportionally-scaled) are shown. It can be seen that the water circulates upwards and outwards in a radially symmetric pattern and the fluid velocity near DNH surface is zero (see top panels of Figure 2b&c). This buoyancy-driven natural convection pattern is known as Rayleigh-Benard-like fluid convection^{32, 33}. The simulations predict a maximum velocity of $\sim 7 \text{ nm/s}$ in the $20 \mu\text{m}$ thick water-filled chamber, for illumination of the single DNH at an intensity of $I_0 = 6.67 \text{ mW}/\mu\text{m}^2$. This velocity is

very small. We thus conclude that thermal-induced fluid convection is weak and has negligible contribution³³ to the DNH trapping process in these experiments. At the start of a trapping experiment when the trapping laser is turned on, only NPs that are very close to the DNH can be trapped, due to the optical forces being short-range in nature. Before this, the motion of the NPs is mainly driven by stochastic Brownian diffusion. Our simulations predict that the fluid velocities resulting from heating due to optical power absorbed by the DNH structure will be very small. On the other hand, in some applications, high fluid velocities are desired and several recent works have demonstrated methods for increasing it substantially. Specifically, it was shown that by introducing an optically absorptive and thermally-conductive indium-tin-oxide (ITO) substrate³⁵ or a photothermal induced electrothermoplasmonic (ETP) flow^{36, 37}, high fluid velocities of $\sim \mu\text{m/s}$ can be achieved. In Figure 2e, the peak temperature increase and maximum convection velocity are plotted as a function of the trapping laser intensity.

If a NP moves close to an illuminated DNH, for example by Brownian motion, it will experience optical forces and can be trapped. To gain insight into the three-dimensional distribution of these optical trapping produced by a DNH, we perform FEM simulations to find the fields and use the Maxwell stress tensor (MST) method to find the forces³⁸⁻⁴⁰. We introduce a polystyrene NP ($n_{NP}=1.6$) at a certain point (x, y, z) , compute the electric and magnetic fields on its surface, and determine the three components (x , y , and z) of the time-averaged force with the MST⁴¹ (see Supporting Information). This process is repeated over a grid of coordinates for the sphere center position to obtain the force field map. In Figure 3a, we plot vertical force F_z as a function of NP center position along the z -axis, for $(x_{center}, y_{center})=(0, 0)$. It can be seen that the NP is pulled into the DNH (F_z is positive) except when very close to glass surface ($F_z<0$) and that force increases with the NP diameter d . Although the three-dimensional optical force field

on the particle is not necessarily strictly conservative, by constraining the motion of the particle to one dimension, an *effective* trapping potential energy can be introduced^{40, 42}. This quantity U_z is plotted as Figure 3b, and is found from Figure 3a by path integration along the z -axis, from outside of the hole ($z_{center}=-192$ nm, $U_z=0$) to inside of the hole ($z_{center}=-12$ nm). While multiphysics simulations that combine optics with thermodynamics and hydrodynamics are needed for a detailed understanding of the trapping process (and are presented later), the *effective* trapping potential energy calculated in this way provides useful physics insight. Namely, it can be seen from Figure 3b that one should expect the force provided by the DNH trap should be sufficient to trap NPs against Brownian motion at the illumination intensity used ($I_0=6.67$ mW/ μm^2). This conclusion is reached by the observation that the calculated trapping potential energy near substrate surface (i.e. glass/water interface) is larger than thermal energy ($1k_B T=4.1 \times 10^{-21}$ J, where k_B is Boltzmann constant and $T=300$ K is temperature). In Figure 3c, we plot F_x and F_z as functions of NP position along the x -axis, with $y_{center}=0$ nm, and $z_{center}=-50$ or -100 nm. The positive values of F_z confirm that the NP is pulled into the DNH. It can also be seen that F_x is positive (negative) when x_{center} is positive (negative). While $F_x=0$ at $x_{center}=0$ and $z_{center}=-50$ or -100 nm, these positions do not allow stable trapping because displacement of the NP from $x_{center}=0$ does not result in a restoring force to pull the NP back to $x_{center}=0$. This indicates that NP is predominantly pulled to the sides of the DNH gap edge (30 nm wide), to the positions denoted by red dots in Figure 1a. In Figure 3d, we plot F_y and F_z as functions of NP position along the y -axis, with $x_{center}=0$ nm, and $z_{center}=-50$ or -100 nm. The positive values of F_z again confirm that the NP is pulled into the DNH. It can also be seen that F_y is positive (negative) when y_{center} is negative (positive). This indicates that the NP experiences a restoring force for excursions in the y -direction from the DNH center ($y=0$) and a stable equilibrium is produced at

the center in the y -direction. In Figure 3e and f, we plot the transverse forces F_x and F_y as functions of NP center position along the x - and y -axes respectively. The calculations are performed for various vertical cross sections that are away from the DNH surface (i.e. $z=-100$ nm plane). The F_x pulling strength to the side walls (indicated in red dots in Figure 1a) diminishes with distance from DNH surface. This is especially evident from examination of the central part of Figure 3e. Again, the NP experiences a restoring force in the y -direction (Figure 3f) and is pulled into the DNH due to the positive values of F_z (Figure 3e&f). We also note from Figure 3e that the NP experiences a restoring force in the x -direction when it is outside of the hole. More optical forces maps can be found in the Supporting Information.

To study the trapping process experimentally, we employ fluorescence microscopy to visualize optical trapping and track the position of a polystyrene nanosphere with a diameter of 20 nm trapped by a DNH. We add a trace amount of surfactant (Tween 20, 0.05% v/v) to the particle solution to limit adhesion to the surface and use a bath sonicator to further prevent aggregation. The particle solution contains the nanospheres at 0.02% solids. Before the experiments, distilled water with Tween 20 (0.05% v/v) is flowed through the channel to prevent nonspecific binding. After the experiment is initiated, we usually wait for about 10 to 20 mins for a NP to be trapped. Three EM-CCD frames are shown as Figure 4a-c, showing a few steps in the NP trapping and release process (see also Supporting Movie 1). At time t_0 , the NP moves randomly and is ~ 2.8 μm from the DNH. From time t_1 , the NP is stably trapped for ~ 34 seconds. At time t_2 , it is no longer trapped. To illustrate and analyze the optical trapping process, we plot the fluorescence intensity integrated over a 30×30 pixel cross section centered over the illuminated DNH as a function of time. As shown in Figure 4d, at $t \sim 6$ s, the NP enters the DNH vicinity and becomes trapped, resulting in an abrupt jump (step-like) in fluorescence. At $t \sim 49$ s,

the trapping laser is turned off and the NP is released. Turning the laser on at $t \sim 55$ s results in the NP being trapped again. That the NP is trapped when the laser is on and released when it is off confirms the predominant role of optical forces in the trapping process and that the NP is not attached to the surface just by van der Waals force, etc. It can be seen from Figure 4d that blocking the laser (at $t \sim 49$ s) results in quick release of the NP from the trap. We also verify that the NP is less strongly trapped (larger positional fluctuations) when the laser power is reduced or the polarization is rotated. Note that the NP in Figure 4d is not the same NP as that in Figure 4a-c. To assess the trapping more quantitatively, we determine the trapped NP center positions from 1000 EM-CCD frames using a radial-symmetry-based particle localization algorithm⁴³ over an interval of 33 s for two different illumination intensities (Figure 4e). In Figure 4f and g, we plot the measured NP center positions (x_c and y_c) as histograms. The full-widths-at-half maximum (FWHMs) of fitted Gaussian distributions are 59 and 190 nm along the x - and y -directions when the illumination intensity is $6.6 \text{ mW}/\mu\text{m}^2$ (see Supporting Movie 2). When the illumination intensity is $22 \text{ mW}/\mu\text{m}^2$, the FWHMs are 31 and 115 nm along the x - and y -directions, respectively. It can be seen that there is suppression of Brownian motion at the higher laser intensity. Also, at both intensities, DNH results in the NPs being confined in an elliptical region, where the position histograms are narrower along the x -direction than the y -direction. This anisotropy can be ascribed to the near field being more strongly confined along the x -direction than the y -direction (see Figure 1c). In addition, the trapped NP experiences the steric hindrance from DNH edge in x -direction rather than in y -direction. To obtain experimental trapping stiffness for a rough estimate, we determine the “effective” trapping stiffness ($k_{\text{eff}} = k_B T / \text{var}(x)$, $\text{var}(x)$ is the position variance) for the illumination intensity of $6.6 \text{ mW}/\mu\text{m}^2$. This is extracted from the measured variance of position (determined from FWHMs in Figure 4f&g) and

correction function using the method of Ref [44] that accounts for video-image motion blur over a finite integration time. The successive grayscale images for tracking are recorded with an ~ 30 ms exposure time. This yields trapping stiffnesses in the x - and y -directions of $k_x=0.2625$ fN/nm and $k_y=0.0801$ fN/nm, respectively, i.e. k_x is about 3 times larger than k_y .

We next investigate the trapping process further by performing Langevin equation simulations to predict the motion of a NP in the vicinity of a DNH under the influence of Brownian fluctuation (stochastic) and DNH generated optical forces (deterministic)⁴⁵. These simulations combine optical forces with Brownian motion, gravity and fluid dynamics (Stokes drag). While even the early works on plasmonic trapping identified the possible role of heating (as well as other non-optical forces) on the trapping process^{41, 46}, the simulations of Figure 2 predict that the peak value of the fluid velocity is only ~ 7 nm/s. We thus do not include heating-driven convection velocity fields in these simulations. Volpe and Volpe previously simulated the motion of a particle in an optical trap⁴⁷, but this approach would be unsuitable for our DNH, as a constant stiffness value was assumed whereas the DNH provides highly confined field distribution (see Figure 1b&c). Furthermore, steric hindrance (i.e. DNH gap and edge) plays an important role in the trapping¹⁴. We thus write the Langevin equation as given by Eq. 1 below (see also Figure 1e and Supporting Information) where m_p is the mass of the NP. The drag force ($\vec{F}_D$, see e.g. Ref [48] and [49]), gravity force with buoyancy ($\vec{F}_g$), Brownian force ($\vec{F}_B$), and optical gradient force⁴⁰ ($\vec{F}_{Opt}$) are as given in Eqs 2-5. We assume no any other forces included here, such as the thermophoretic force⁵⁰. Eqs 2-5 are described further below.

$$m_p \frac{d^2 \vec{r}}{dt^2} = m_p \frac{d\vec{v}}{dt} = \vec{F}_D + \vec{F}_g + \vec{F}_B + \vec{F}_{Opt} \quad (1)$$

$$\vec{F}_D = \frac{m_p}{\tau_p}(\vec{u} - \vec{v}), \tau_p = \frac{\rho_p d_p^2}{18\mu} \quad (2)$$

$$\vec{F}_g = m_p \vec{g} \frac{(\rho_p - \rho)}{\rho_p} \quad (3)$$

$$\vec{F}_B = \zeta \sqrt{\frac{12\pi k_B \mu T r_p}{\Delta t}} \quad (4)$$

$$\vec{F}_{Opt} = \pi r_p^3 \epsilon_0 n_f^2 \frac{n_p^2 - n_f^2}{n_p^2 + 2n_f^2} \nabla |\vec{E}(\vec{r})|^2 \quad (5)$$

The force $\vec{F}_D$ is known as Stokes drag, and τ_p is the particle velocity response time, $\vec{v}$ is the particle velocity, $\vec{u}$ is the fluid velocity, μ is the fluid viscosity, ρ_p is the material density of the NP, and d_p is the particle diameter. We take the fluid velocity $\vec{u}$ to be zero, as it is predicted by the simulations of Figure 2 to have a very small value near DNH surface. The additional computational expense of including it in this simulation is therefore unjustified. We employ Stokes' drag in its basic form (Eq. 2), and do not modify it via Faxén's law^{48, 49} (see Supporting Information). The force $\vec{F}_g$ is gravity force with buoyancy, with ρ being the water density and $\vec{g}$ being the acceleration due to gravity. The force $\vec{F}_B$ is a stochastic Brownian force modeled as a Gaussian white noise process^{51, 52}. In this equation, Δt is the time step taken by the solver, r_p is the particle radius, T is the fluid temperature, k_B is the Boltzmann constant, and ζ is a normally distributed random number with a mean of zero and unit variance. Eq. 5 provides the expression for the optical trapping force $\vec{F}_{Opt}$. It can be seen that we employ the optical gradient force, with the NP approximated as an electric point dipole. This provides a considerable reduction in computational expense, in comparison to calculating the optical force rigorously using the Maxwell stress tensor (MST). One might expect the gradient force to be a reasonable

approximation, given that the NP is small (20 nm diameter) and its refractive index is close to water ($\Delta n=0.27$) in comparison to what would occur for a metal (e.g. Au) or high index dielectric (e.g. Si) nanoparticle. We furthermore provide a comparison between the gradient force calculated in this way (dipole approximation) with that calculated rigorously by the MST in the Supporting Information. It can be seen that they are in reasonable agreement. The fact that they are in agreement also suggests that in our configuration, the perturbation to the DNH field distribution by the presence of the NP is not important for the trapping process. In other words, this effect (sometimes termed SIBA¹⁰) is not important in the trapping process in this tested geometry. In Eq. 5, ϵ_0 is the vacuum permittivity, n_f is the refractive index of water, and n_p is the refractive index of particle.

By solving Eq. 1 to Eq. 5 numerically with a given initial velocity ($\vec{v}_0 = 0$ at $t=0$) and a given initial position (x_0, y_0, z_0), particle trajectories can be modeled. We begin however by performing modeling that includes only the optical forces. In other words, only $\vec{F}_{Opt}$ is non-zero in Eq. 1. We assume that when the NP encounters the wall (gold or glass surface) it is reflected from it such that the particle momentum is conserved. In Figure 5a, we show the trajectories that result when the NP is released at $(x_0, y_0, z_0) = (5 \text{ nm}, 5 \text{ nm}, -50 \text{ nm})$ for two different illumination intensities and with only optical forces included. In Figure 5b, this is repeated for a release position of $(x_0, y_0, z_0) = (5 \text{ nm}, 5 \text{ nm}, -110 \text{ nm})$. In Figure 5c, we plot the corresponding trajectories in the xy -plane for the illumination intensity of $I_0=6.67 \text{ mW}/\mu\text{m}^2$. The solver time step is set to be 0.1 ns. It can be seen from Figure 5c that, after release, for both cases of starting position, the NP initially moves towards the right hotspot, reaching it at 20 ns or 40 ns. The NP is then reflected from the wall. Throughout the duration of the plotted trajectories (100 ns), the z -component of the optical force (F_z) remains positive, so the NP is continually pulled toward the bottom of the

DNH, bouncing off the walls as it encounters them. We next perform modeling including all forces in Eq. 1-5. As noted by Bui et al, the accurate simulation of optical and Brownian forces requires the time step Δt to be chosen carefully.⁴⁵ We set the solver time step to be $\Delta t=0.5$ ns, which is small enough to ensure that over the distance the NP moves over one time step, the optical (and other) forces do not vary much. We simulate particle trajectories over durations of 100 μ s, i.e. 2×10^5 time steps. We show three trajectories in Figure 5d and e, for all of which the initial release position is $(x_0, y_0, z_0) = (0, 0, -110 \text{ nm})$. We plot the trajectories in the xy -plane in Figure 5d and the corresponding vertical (z) positions as a function of time in Figure 5e. It can be seen that the NP moves around DNH, strongly influenced by the Brownian force. We attribute the asymmetrical confinements in x - and y -axes that we observe experimentally to arise from both the optical forces and the morphology of the DNH. By the latter, we refer to the fact that the DNH morphology represents a constriction that limits particle movement along the x -axis, while it is far less constrained along the y -axis. From Figure 5e, it can be seen that the Brownian forces acting on the NP result in it jittering in and out of the DNH. In Figure 5f, the results of ten simulated NP trajectories (each with duration 100 μ s) are shown as a histogram of vertical position. It can be seen that the NP largely remains within the region of high intensity, i.e. within the DNH aperture or a small distance (~ 50 nm) from it. In our experiments, our camera (EM-CCD) is operated at 30 frames per second, i.e. 33 ms between frames, over tens of seconds. Furthermore, our imaging method is inherently two dimensional, i.e. we track particle positions in x - and y - but not along the z -axis. Our theoretical modeling on the other hand, allows us to predict nanoparticle trajectories in three dimensions and with temporal resolution that is in principle arbitrarily-high. Due to practical considerations, the duration of the modeled trajectory is limited, in our case to 100 μ s. This simulation takes three days to perform on a standard

desktop computer at the time of writing. Nonetheless, the combination of theoretical modeling and particle tracking experiments elucidate the dynamics of nanoparticles trapped by the DNH nanoaperture on timescales ranging from nanoseconds to tens of seconds. In these simulations, we do not include forces such as adhesion, etc. Such forces can be challenging to accurately model⁴⁵. Finally, we note that we do not rule out the possibility that other forces may contribute to the observed localization. These may be the topic of future investigations.

In conclusion, we employ fluorescence microscopy to directly observe the dynamics of a single nanosphere with a diameter of 20 nm optically trapped by a double nanohole in a gold film. We track its position and fluorescent emission as a function of time, demonstrating that the region visited by the trapped nanoparticle has an elliptical shape and that tighter spatial confinement occurs at the higher laser intensity. We perform numerical simulations to further elucidate the DNH trapping process, including predicting trajectories over time intervals too short for the experiments. Our simulations include electric field distribution, heat generation, fluid velocity, optical forces, potential energy, and the dynamics of the trapping process, i.e. nanoparticle trajectories. The theoretical prediction and experimental demonstration in this work will be useful for the better understanding of the fundamental physics of light-nanostructure interactions and could open new avenues for the future optical trapping devices on the nanoscale.

ASSOCIATED CONTENT

Supporting Information. Detailed descriptions of the experimental methods, simulation methods, theoretical formula and additional experimental and numerical figures are provided. Movie 1 illustrates the optical trapping and release of a single 20 nm polystyrene nanoparticle in real time. Movie 2 demonstrates the optical tracking of a 20 nm nanoparticle trapped by a DNH.

AUTHOR INFORMATION

Corresponding Author

* E-mail: kcrozier@unimelb.edu.au.

Author Contributions

Z.X. and K.B.C. conceived and designed the research study. Z.X. performed experiments, simulation and data analysis. All authors discussed the results. Z.X. and K.B.C. wrote the manuscript.

Notes

The authors declare no competing financial interest.

ACKNOWLEDGMENTS

This research was sponsored in part by the Australian Research Council (DP150103736 and FT140100577), by the Victorian Endowment for Science, Knowledge and Innovation (VESKI), and by the Laby Foundation. This work was performed in part at the Melbourne Centre for Nanofabrication (MCN) in the Victorian Node of the Australian National Fabrication Facility (ANFF).

Figures and captions

Figure 1. (a) DNH aperture in Au film: LEFT-top-view image of scanning electron micrograph (SEM), RIGHT-simulated structure, comprising two circular holes (diameter $D=100$ nm) separated by 140 nm (center-to-center) with 30 nm gap. (b)(c) Electric field enhancement

($|E|/|E_0|$) distribution, for plane wave illumination from water side (x -polarized, $\lambda=1064$ nm, traveling in $+z$ direction). Black dot indicates coordinate system origin. (b) $x=0$ cross section; (c) $z=-50$ nm cross section. (d) Heat power dissipation density (Q_h) in the center plane ($z=-50$ nm) for $I_0=6.67$ mW/ μm^2 . Scale bar is 100 nm in (b)-(d). (e) Schematic illustration of 20 nm NPs optically trapped in the near fields of a DNH in water chamber. Fluorescence is recorded by EM-CCD camera. Sketch is not to scale. Definitions of symbols are as follows. v : NP velocity; F_B : Brownian force; F_g : gravity with buoyancy; F_D : drag force; F_{opt} : optical trapping force. Note that the directions of the forces as depicted in this figure are examples for illustration purposes.

Figure 2. (a) FEM simulation of steady-state temperature increase (ΔT) profile around DNH for illumination intensity $I_0 = 6.67 \text{ mW}/\mu\text{m}^2$, plotted in a cross-section through the DNH center ($z = -50 \text{ nm}$). (b)-(d) FEM simulations of water convection velocity field for $I_0 = 6.67 \text{ mW}/\mu\text{m}^2$, plotted in both magnitude (color map: nm/s) and direction (white arrows, magnitude proportionally-scaled). (b) $x=0$ cross section; (c) $y=0$ cross section; (d) $z=-150 \text{ nm}$ cross section (i.e. at distance of 50 nm below gold film surface). (e) Peak temperature increase (ΔT_{max} : K, blue squares) and maximum convection velocity (v_{max} : nm/s, red circles) as a function of trapping laser intensity.

Figure 3. Map of optical forces exerted on a single polystyrene nanoparticle ($n=1.6$) near DNH for $I_0=6.67 \text{ mW}/\mu\text{m}^2$, calculated with Maxwell stress tensor (MST) method. (a) Vertical force F_z and (b) trapping potential energy U_z as functions of particle diameter d and position. ($x_{\text{center}}=y_{\text{center}}=0$) (c)-(f) Force map exerted on $d=20$ nm NP. (c)&(e) $y_{\text{center}}=0$; (d)&(f) $x_{\text{center}}=0$.

Figure 4. (a)-(c) EM-CCD frames showing optical trapping and release of a single 20 nm NP by DNH (approx. position: yellow dot). $I_0=16 \text{ mW}/\mu\text{m}^2$. (d) Optical trapping of a single 20 nm NP seen as sudden discrete jumps in fluorescence intensity. $I_0=22 \text{ mW}/\mu\text{m}^2$. (e) Scatter plots of NP center locations. (f)(g) Position histograms along x - and y -axes, extracted from data of panel e.

Figure 5. (a)-(c) Simulation of NP trajectories (20 nm diameter), with only optical force modeled. DNH is illuminated by x -polarized plane wave at a wavelength of 1064 nm. (a)(b) Particle trajectories as a function of time. Initial release position (a) $(x_0, y_0, z_0) = (5 \text{ nm}, 5 \text{ nm}, -50 \text{ nm})$; (b) $(x_0, y_0, z_0) = (5 \text{ nm}, 5 \text{ nm}, -110 \text{ nm})$. (c) Plot of trajectories (each 100 ns duration) in xy -plane for the two different release positions, from data of panel a&b for $I_0 = 6.67 \text{ mW}/\mu\text{m}^2$. Blue square indicates initial position and pink cross indicates DNH center. (d)-(f) Simulation of NP trajectories (20 nm diameter) influenced by all forces, for $I_0 = 6.67 \text{ mW}/\mu\text{m}^2$. (d) Position (in xy -plane) vs time tracking of three NPs (20 nm diameter). (e) Vertical positions vs time for same

trajectories as panel d. DNH edge (gold film surface) is denoted by orange dashed-dotted line. (f) Histogram of vertical positions of trajectories of ten NPs, for bin width of 5 nm. Each trajectory has a duration of 100 μ s and time step 0.5 ns (2×10^5 time steps).

REFERENCES

- (1) Ashkin, A. Acceleration and trapping of particles by radiation pressure. *Phys. Rev. Lett.* **1970**, 24, 156-159.
- (2) Ashkin, A.; Dziedzic, J. M.; Bjorkholm, J.; Chu, S. Observation of a single-beam gradient force optical trap for dielectric particles. *Opt. Lett.* **1986**, 11, 288-290.
- (3) Ashkin, A.; Dziedzic, J. M.; Yamane, T. Optical trapping and manipulation of single cells using infrared laser beams. *Nature* **1987**, 330, 769-771.
- (4) Grier, D. G. A revolution in optical manipulation. *Nature* **2003**, 424, 810-816.
- (5) Neuman, K. C.; Block, S. M. Optical trapping. *Rev. Sci. Instrum.* **2004**, 75, 2787-2809.
- (6) Spesvytseva, S. E. S.; Dholakia, K. Trapping in a material world. *ACS Photonics* **2016**, 3, 719-736.
- (7) Kwak, E. S.; Onuta, T. D.; Amarie, D.; Potyrailo, R.; Stein, B.; Jacobson, S. C.; Schaich, W.; Dragnea, B. Optical trapping with integrated near-field apertures. *J. Phys. Chem. B* **2004**, 108, 13607-13612.
- (8) Grigorenko, A.; Roberts, N.; Dickinson, M.; Zhang, Y. Nanometric optical tweezers based on nanostructured substrates. *Nat. Photonics* **2008**, 2, 365-370.
- (9) Righini, M.; Ghenuche, P.; Cherukulappurath, S.; Myroshnychenko, V.; García de Abajo, F.; Quidant, R. Nano-optical trapping of Rayleigh particles and Escherichia coli bacteria with resonant optical antennas. *Nano Lett.* **2009**, 9, 3387-3391.
- (10) Juan, M. L.; Gordon, R.; Pang, Y.; Eftekhari, F.; Quidant, R. Self-induced back-action optical trapping of dielectric nanoparticles. *Nat. Phys.* **2009**, 5, 915-919.
- (11) Zhang, W.; Huang, L.; Santschi, C.; Martin, O. J. Trapping and sensing 10 nm metal nanoparticles using plasmonic dipole antennas. *Nano Lett.* **2010**, 10, 1006-1011.
- (12) Juan, M. L.; Righini, M.; Quidant, R. Plasmon nano-optical tweezers. *Nat. Photonics* **2011**, 5, 349-356.
- (13) Tsai, W. Y.; Huang, J. S.; Huang, C. B. Selective trapping or rotation of isotropic dielectric microparticles by optical near field in a plasmonic archimedes spiral. *Nano Lett.* **2014**, 14, 547-552.
- (14) Pang, Y.; Gordon, R. Optical trapping of 12 nm dielectric spheres using double-nanoholes in a gold film. *Nano Lett.* **2011**, 11, 3763-3767.
- (15) Chen, C.; Juan, M. L.; Li, Y.; Maes, G.; Borghs, G.; Van Dorpe, P.; Quidant, R. Enhanced optical trapping and arrangement of nano-objects in a plasmonic nanocavity. *Nano Lett.* **2012**, 12, 125-132.
- (16) Berthelot, J.; Aćimović, S.; Juan, M.; Kreuzer, M.; Renger, J.; Quidant, R. Three-dimensional manipulation with scanning near-field optical nanotweezers. *Nat. Nanotechnol.* **2014**, 9, 295-299.
- (17) Al Balushi, A. A.; Kotnala, A.; Wheaton, S.; Gelfand, R. M.; Rajashekhara, Y.; Gordon, R. Label-free free-solution nanoaperture optical tweezers for single molecule protein studies. *Analyst* **2015**, 140, 4760-4778.
- (18) Mestres, P.; Berthelot, J.; Aćimović, S. S.; Quidant, R. Unraveling the optomechanical nature of plasmonic trapping. *Light: Sci. Appl.* **2016**, 5, 1-14.
- (19) Wang, K.; Schonbrun, E.; Steinvurzel, P.; Crozier, K. B. Trapping and rotating nanoparticles using a plasmonic nano-tweezer with an integrated heat sink. *Nat. Commun.* **2011**, 2, 469.

- (20) Wang, K.; Crozier, K. B. Plasmonic trapping with a gold nanopillar. *ChemPhysChem* **2012**, 13, 2639-2648.
- (21) Yang, A. H.; Moore, S. D.; Schmidt, B. S.; Klug, M.; Lipson, M.; Erickson, D. Optical manipulation of nanoparticles and biomolecules in sub-wavelength slot waveguides. *Nature* **2009**, 457, 71-75.
- (22) Lin, S.; Crozier, K. B. An integrated microparticle sorting system based on near-field optical forces and a structural perturbation. *Opt. Express* **2012**, 20, 3367-3374.
- (23) Lin, S.; Schonbrun, E.; Crozier, K. B. Optical manipulation with planar silicon microring resonators. *Nano Lett.* **2010**, 10, 2408-2411.
- (24) Lin, S.; Crozier, K. B. Planar silicon microrings as wavelength-multiplexed optical traps for storing and sensing particles. *Lab Chip* **2011**, 11, 4047-4051.
- (25) Mandal, S.; Serey, X.; Erickson, D. Nanomanipulation using silicon photonic crystal resonators. *Nano Lett.* **2010**, 10, 99-104.
- (26) Chen, Y. F.; Serey, X.; Sarkar, R.; Chen, P.; Erickson, D. Controlled photonic manipulation of proteins and other nanomaterials. *Nano Lett.* **2012**, 12, 1633-1637.
- (27) Baffou, G.; Quidant, R. Thermo-plasmonics: using metallic nanostructures as nano-sources of heat. *Laser Photonics Rev.* **2013**, 7, 171-187.
- (28) Johnson, P. B.; Christy, R. W. Optical constants of the noble metals. *Phys. Rev. B* **1972**, 6, 4370-4379.
- (29) Baffou, G.; Quidant, R.; García de Abajo, F. J. Nanoscale control of optical heating in complex plasmonic systems. *ACS Nano* **2010**, 4, 709-716.
- (30) Baffou, G.; Berto, P.; Bermúdez Ureña, E.; Quidant, R.; Monneret, S.; Polleux, J.; Rigneault, H. Photoinduced heating of nanoparticle arrays. *ACS Nano* **2013**, 7, 6478-6488.
- (31) Garcés-Chávez, V.; Quidant, R.; Reece, P.; Badenes, G.; Torner, L.; Dholakia, K. Extended organization of colloidal microparticles by surface plasmon polariton excitation. *Phys. Rev. B* **2006**, 73, 085417.
- (32) Landau, L. D.; Lifshitz, E. M. *Fluid Mechanics*. Elsevier Science: **2013**.
- (33) Donner, J. S.; Baffou, G.; McCloskey, D.; Quidant, R. Plasmon-assisted optofluidics. *ACS Nano* **2011**, 5, 5457-5462.
- (34) Haynes, W. M. *CRC Handbook of Chemistry and Physics*. CRC Press: **2014**.
- (35) Roxworthy, B. J.; Bhuiya, A. M.; Vanka, S. P.; Toussaint, K. C., Jr. Understanding and controlling plasmon-induced convection. *Nat. Commun.* **2014**, 5, 3173.
- (36) Ndukaife, J. C.; Mishra, A.; Guler, U.; Nnanna, A. G. A.; Wereley, S. T.; Boltasseva, A. Photothermal heating enabled by plasmonic nanostructures for electrokinetic manipulation and sorting of particles. *ACS Nano* **2014**, 8, 9035-9043.
- (37) Ndukaife, J. C.; Kildishev, A. V.; Nnanna, A. G.; Shalaev, V. M.; Wereley, S. T.; Boltasseva, A. Long-range and rapid transport of individual nano-objects by a hybrid electrothermoplasmonic nanotweezer. *Nat. Nanotechnol.* **2016**, 11, 53-60.
- (38) Wang, X.; Wang, X. B.; Gascoyne, P. R. General expressions for dielectrophoretic force and electrorotational torque derived using the Maxwell stress tensor method. *J. Electrostatics* **1997**, 39, 277-295.
- (39) Jackson, J. D. *Classical Electrodynamics*. John Wiley & Sons: **2007**.
- (40) Novotny, L.; Hecht, B. *Principles of Nano-Optics*. Cambridge University Press: **2012**.
- (41) Ploschner, M.; Mazilu, M.; Krauss, T. F.; Dholakia, K. Optical forces near a nanoantenna. *J. Nanophotonics* **2010**, 4, 041570.

- (42) Lehmuskero, A.; Johansson, P.; Rubinsztein-Dunlop, H.; Tong, L.; Kall, M. Laser trapping of colloidal metal nanoparticles. *ACS Nano* **2015**, 9, 3453-3469.
- (43) Parthasarathy, R. Rapid, accurate particle tracking by calculation of radial symmetry centers. *Nat. Methods* **2012**, 9, 724-726.
- (44) Wong, W. P.; Halvorsen, K. The effect of integration time on fluctuation measurements: calibrating an optical trap in the presence of motion blur. *Opt. Express* **2006**, 14, 12517-12531.
- (45) Bui, A. A.; Stilgoe, A. B.; Lenton, I. C.; Gibson, L. J.; Kashchuk, A. V.; Zhang, S.; Rubinsztein-Dunlop, H.; Nieminen, T. A. Theory and practice of simulation of optical tweezers. *J. Quant. Spectrosc. Radiat. Transfer* **2017**, 195, 66-75.
- (46) Righini, M.; Zelenina, A. S.; Girard, C.; Quidant, R. Parallel and selective trapping in a patterned plasmonic landscape. *Nat. Phys.* **2007**, 3, 477-480.
- (47) Volpe, G.; Volpe, G. Simulation of a Brownian particle in an optical trap. *Am. J. Phys.* **2013**, 81, 224-230.
- (48) Durlofsky, L.; Brady, J. F.; Bossis, G. Dynamic simulation of hydrodynamically interacting particles. *J. Fluid Mech.* **1987**, 180, 21-49.
- (49) Svoboda, K.; Block, S. M. Biological applications of optical forces. *Annu. Rev. Biophys. Biomol. Struct.* **1994**, 23, 247-285.
- (50) Duhr, S.; Braun, D. Why molecules move along a temperature gradient. *Proc. Natl. Acad. Sci. U.S.A.* **2006**, 103, 19678-19682.
- (51) Kim, M.-m.; Zydney, A. L. Effect of electrostatic, hydrodynamic, and Brownian forces on particle trajectories and sieving in normal flow filtration. *J. Colloid Interface Sci.* **2004**, 269, 425-431.
- (52) Heiniger, A. T.; Miller, B. L.; Fauchet, P. M. Numerical study of sensitivity enhancement in a photonic crystal microcavity biosensor due to optical forces. *Opt. Express* **2015**, 23, 25072-25083.

Table of Content (ToC) Graphic

For Table of Contents Use Only

Manuscript ID: ph-2018-00176k

Manuscript Title: Direct particle tracking observation and Brownian dynamics simulations of a single nanoparticle optically trapped by a plasmonic nanoaperture

Manuscript Authors: Zhe Xu, Wuzhou Song, and Kenneth B. Crozier

Brief synopsis: Fluorescence microscopy is used to track the position of the trapped 20 nm nanosphere by a double nanohole aperture. FEM simulation is also used to model the trapped nanosphere trajectories.