Shear Lag Effects in Reinforced Concrete C-shaped Walls

Ryan D. Hoult¹

1. Corresponding Author. Senior Tutor, Department of Infrastructure Engineering,
University of Melbourne, Parkville, 3010, Australia. Email: ryan.hoult@unimelb.edu.au.
Ph: +61401955374

Abstract

Shear lag effects can significantly reduce the moment capacity of non-rectangular reinforced concrete walls. While this phenomenon is recognized as an important component in the analysis and design of buildings, it is generally not well understood by practicing engineers. Furthermore, there is a paucity of experimental studies that have focused on the seismic performance of reinforced concrete C-shaped walls and virtually no studies that have investigated shear lag effects for these types of walls. This research investigates shear lag effects in reinforced concrete C-shaped walls using an extensive number of finite element modelling results. The numerical analyses are conducted using VecTor3, a state-of-the-art finite element modelling program, to estimate the vertical strain distributions across the web and flanges of the wall. The results show that shear lag effects are significant and sometimes prominent in C-shaped walls, particularly for the wall sections perpendicular to the direction of loading. An expression is derived to estimate the effective width of C-shaped walls and for the different directions of loading. Moment-curvature analyses are conducted to illustrate how practicing engineers can implement the effective width method for future analyses and designs.

1. Introduction

Reinforced concrete (RC) buildings typically utilize structural (or shear) walls as their primary lateral load resisting system. There are many different cross-sectional shapes being used for the core walls of these buildings. For example, the C-shaped (or U-shaped) wall is a popular construction choice (Arabzadeh & Galal, 2017; Beyer *et al.*, 2008a) as it can enclose a service core, elevators (lifts), stairs and toilets. The seismic performance of C-shaped walls differ from the behavior of rectangular walls, as the flanged sections increase the walls' lateral strength and stiffness (Paulay & Priestley, 1992). Furthermore, C-shaped sections have three primary modes of bending; compared to rectangular walls

28 with only one primary mode of bending about the strong axis, C-shaped wall can bend about the
29 major (strong) axis and about the minor (weak) axis with web in compression (WiC) and web in
30 tension (WiT). These bending directions are illustrated in Figure 1.

31 In regions of high seismicity, a displacement-based design (Moehle, 1992; Priestley *et al.*, 2007;
32 Wallace & Moehle, 1992) is commonly undertaken to provide, among many things, a sufficient
33 amount of longitudinal and transverse reinforcement within the plastic hinge region of the wall. One
34 of the most important components when designing RC walls using the displacement-based design
35 procedure is the assumption of a linear strain profile along the wall length (Thomsen & Wallace,
36 2004). This assumption stems from the elementary theory of bending, or the Bernoulli-Euler
37 assumption, that plane sections remain plane after bending, which is only approximate and ‘strictly
38 applicable only when there is no shear force or when the structure has infinite shear stiffness’ (Kwan,
39 1996). For non-rectangular sections with flanges, such as C- and T-shaped, this assumption is not
40 necessarily justifiable (Moffatt & Dowling, 1975), and the effects due to shear lag can be substantial
41 (Arabzadeh & Galal, 2017). Therefore, the Bernoulli-Euler assumption is potentially inappropriate
42 when assessing or designing RC C-shaped walls. In reality, a shear flow would develop, where the
43 longitudinal strains in the center of the web and flanges would lag behind the strains at the web-flange
44 intersection of the wall (Kwan, 1996); this phenomenon has been termed “shear lag” and is illustrated
45 in Figure 2 with idealized strain distributions for both a C-shaped wall and two directions of loading.
46 As shown in Figure 2, the distribution of strain is nonlinear, which can complicate the analysis and
47 design of RC C-shaped walls (Hassan & El-Tawil, 2003).

48 While this phenomenon has been recognized as an important component in the analysis and design of
49 buildings, the nonlinear strain distribution profiles have generally not been widely recognized by
50 practicing engineers (Deschappelles & Kwan, 1997). Instead, engineers will usually resort to using an
51 “effective width” method in order to avoid the more complicated nonlinear strain distribution
52 resulting from shear lag (Hassan & El-Tawil, 2003). As described by Zhang and Li (2017b), the
53 method typically involves only activating the longitudinal reinforcement within a calculated effective
54 width of the flange to contribute to resisting the moment of a wall section; only a uniformly stressed

55 effective portion of the flange is considered. Ray (1995) defines the effective width as ‘the width of
 56 wall perpendicular to direction of horizontal loading which is considered as effective as compression
 57 flange, and also vertical reinforcement provided in this width acts in tension and in tension flange’.
 58 The effective width (b_{eff}) can be calculated using the strain distributions using Equation 1.

$$b_{eff} = \frac{\sum_{i=1}^n \varepsilon_i w_i}{\varepsilon_{max}} \quad 1$$

59 where ε_i is the steel tension strain or concrete compression strain in element i , w_i is the width of
 60 element i and ε_{max} is the maximum strain across the length of the wall (web or flange).

61 The effective width method is also a requirement in some design codes. For example, the effective
 62 flange width for RC walls with ‘intersecting rectangular segments’ (e.g. C-shaped) as specified in the
 63 European seismic design code (CEN, 2004) as the minimum of (i) the actual flange width; (ii) one-
 64 half of the distance to an adjacent web of the wall; and (iii) 25% of the total height of the wall above
 65 the level considered. The effective flange width for the design of RC structural walls with flanged
 66 sections was also specified in the 1994 version of the Uniform Building Code [UBC-94] (ICBO,
 67 1994), which specified that the b_{eff} must not exceed 10% of the wall height, though some researchers
 68 suggested that this value for the b_{eff} was relatively low (Paulay, 1986; Sittipunt & Wood, 1993;
 69 Wallace & Wood, 1994). Furthermore, Wallace (1996) believed that the low b_{eff} value prescribed in
 70 UBC-94 was ‘based on the premise that it is conservative to underestimate the effective flange width
 71 since it leads to a low estimate of the wall flexural strength’. Consequently, Wallace (1996) identified
 72 that this premise could also lead to inadequate detailing of the wall web opposite the flange in tension
 73 and inadequate shear reinforced, which violates the rules of capacity design. Therefore, Wallace
 74 (1996) recommends the effective width for the design of RC structural walls with flange section as
 75 one quarter of the height of the wall ($H_n/4$), which was subsequently adopted in the ACI 318-11 (ACI,
 76 2011). However, previous research has found this design method in ACI 318-11 to account for the
 77 influences of shear lag in RC walls to be inaccurate (Aaleti *et al.*, 2013; Hassan & El-Tawil, 2003;
 78 Thomsen & Wallace, 2004; Zhang & Li, 2016). For the analysis and design of reinforced concrete
 79 walls, Ray (1995) recommends using factors (ψ) for calculating the effective width of the flanges

perpendicular to the direction of lateral loading for C-shaped walls. Equations 2 and 3 are used to calculate the effective width of the flanges (b_{e1}) and web (b_{e2}) respectively, corresponding to the direction of loading shown in Figure 3. The factors in Table 1 were adopted by Ray (1995) from BS 5400: Part 5 (British Standard Institution, 1979) for cantilever beams with a uniformly distributed load. As these factors have been originally derived for beam sections, they are not dependent on axial load, which could be an important factor for the effective width of RC walls.

$$b_{e1} = 0.85\psi b_1 \quad 2$$

$$b_{e2} = \psi b_2 \quad 3$$

Some other studies have focused on alternative methods for estimating the shear lag effect in non-rectangular walls without the need for using the effective width method. A parametric study by Kwan (1996) used a number of “boxed” core wall models with the finite element method. Design charts and empirical equations were derived from the study for estimating the amount of shear lag expected in boxed core walls. Empirical expressions have also been proposed from a study by Waugh (2009) using numerical results and existing experimental data for T-shaped RC walls. There has also been some research focusing on shear lag effects on non-rectangular cross-sections of beams and beam-slab systems (Chang, 2004; Pantazopoulou & French, 2001; Pantazopoulou *et al.*, 1988; Song & Scordelis, 1990). However, these studies that have focused on the performance of beams are unlikely to be representative of the performance of flanged walls, which are typically not only subjected to flexural loading but also axial loading. More recently, Zhang and Li (2017b) developed a new method for considering shear lag effects in RC walls with flanged sections. It was found that the proposed method from Zhang and Li (2017b) compared well to experimental and finite element modelling results of L- and T-shaped RC walls, particularly for when the flanges were in tension and where the maximum strains were close to yield (i.e. pre-yield drifts). Yet, the proposed method from Zhang and Li (2017b) is relatively complicated and unlikely to be adopted by practicing engineers; ‘For practical applications, there is still the need for simple methods, which can allow quick estimation of the shear-lag effects without the use of computers, particularly during the preliminary design stage’ (Kwan, 1996).

Some experimental studies focusing on T-shaped wall specimens have shown significant shear lag effects, particularly across the flange of the wall and for bending that causes the flange to be in tension (Brueggen, 2009; Brueggen *et al.*, 2017; Thomsen & Wallace, 2004; Zhang & Li, 2016, 2017a). The experimental research from Brueggen (2009) found that the flange of the T-shaped wall specimens tested became more “effective” (e.g. more of the flange is “activated”) as the top displacement of the wall increased. This observation was also observed in Hassan and El-Tawil (2003) from the numerical analyses conducted on C-shaped walls, where the web of the wall became more effective as the drift level increased. Furthermore, the experimental research from Brueggen (2009) found that the shear lag phenomenon was more apparent for pre-yield drift levels. Therefore, accounting for the effects of shear lag for non-rectangular RC walls is not only important for ultimate limit state (ULS) design but also Serviceability (e.g. pre-yield). Moreover, Brueggen (2009) found from the T-shaped wall specimens tested that the strains in the flange ends, or boundary ends of the wall, were approximately one half of the strains at the flange-web intersection in the center of the flange. This observation was also corroborated by the test results from Brueggen *et al.* (2017), where it was also shown that evenly distributing the longitudinal reinforcement throughout the flange can reduce the effects of shear lag in comparison to concentrating at the boundary ends. The experimental results on T-shaped walls from Zhang and Li (2016) showed that ‘omitting the shear lag effect leads to overestimating the tension force and base moment of the wall’. Similarly, it was observed that the measured force capacity of the wall specimens tested by Brueggen *et al.* (2017) were less than expected (sometimes by up to 30%) because ‘the reinforcement concentrated in the boundary elements of the flanges was less stressed due to shear lag’.

While there has been some experimental research that has focused on the seismic performance of C-shaped walls (Beyer *et al.*, 2008b; Ile & Reynouard, 2005; Lowes *et al.*, 2013), experimental data is still limited and, to the knowledge of the author, no studies have specifically addressed the effects due to shear lag on RC C-shaped walls. However, the C-shaped wall tests from Constantin and Beyer (2016) showed that the vertical strains captured at the base of the wall during testing deviated substantially from that predicted using a plane section analysis. While Constantin and Beyer (2016)

postulate that the significant deviations from the plane section assumption are due to the large shear deformations present in slender core walls under diagonal loading, it is possible that the effects of shear lag have also influenced different strain gradients to that obtained using a section analysis. Section analysis was also found to overestimate the moment capacities determined experimentally, particularly for diagonal loading. Moreover, the flanges of the C-shaped wall specimens from Constantin and Beyer (2016), discussed more in Section 2.1, were detailed with different amounts of longitudinal reinforcement to study the influence of wall behavior. It was found that larger shear deformations are present for the flange with a concentrated reinforcement layout than for the flange with distributed reinforcement. The results from numerical analyses on some C-shaped walls found that the flange under tension becomes less effective as the axial load ratio (ALR) increased (Hassan & El-Tawil, 2003). Furthermore, the study by Hassan and El-Tawil (2003) found that increasing the wall height did not have any significant impact on shear lag effects.

The research discussed henceforth investigates the strain distribution and the effects of shear lag in RC C-shaped walls. A large number of finite element modelling (FEM) analyses are conducted on low-rise C-shaped walls with different web lengths, flange lengths, axial load ratios and reinforcement layouts. The strain distributions across the web and flanges of the walls are examined for different levels of drift. The effective widths of the flanges and web in tension or compression, depending on the direction of loading, are calculated using the strain distributions and Equation 1. Moment-curvature ($M-\phi$) analyses are conducted for a C-shaped wall using the strain distribution results from the FEM results (i.e. $M-\phi$ that includes the effects due to shear lag) and this is compared to the results of sectional analyses with the Bernoulli-Euler assumption (i.e. elementary theory of bending without considering the effects of shear lag). A simple expression with parameters derived from this research is recommended to be used for calculating the effective width of the flange or web of C-shaped walls, which can aid in providing more accurate flexural strength results in analysis and design.

In the next section, a state-of-the-art FEM program, VecTor3 (ElMohandes & Vecchio, 2013), will be discussed and validated using some recent experimental results on C-shaped walls.

2. VecTor3

VecTor3 (ElMohandes & Vecchio, 2013) is a state-of-the-art nonlinear finite element (FE) modelling program used for RC 3-dimensional solids that uses the Disturbed Stress Field Model (DSFM) (Vecchio, 2000), which improves the prediction of the behavior of RC elements (ElMohandes, 2013) in comparison to its predecessor the modified compression field theory (MCFT) (Vecchio & Collins, 1986). The DSFM is a smeared rotating crack model, which explicitly allows for rigid slip along cracked element boundaries in its development of ‘compatibility, equilibrium and constitutive relations’ (Vecchio *et al.*, 2001). More information about the program and some recent improvements of the predictions for the behavior of RC elements can be found in ElMohandes (2013).

A range of material models have been incorporated in VecTor3 to represent modelling of the concrete and steel materials. Some of these models were used for the finite element modelling analyses conducted in Hoult *et al.* (2017) and Hoult *et al.* (2018) for lightly reinforced and unconfined rectangular and C-shaped walls respectively. Furthermore, Constantin (2016) validated these models in VecTor4 for modelling the performance of C-shaped wall specimens detailed for high ductility; a complete description of the VecTor4 software and the shell elements used for the analyses in Constantin (2016) can be found in Hrynyk (2013). Subsequently, they are used here for modelling C-shaped walls with similar detailing in VecTor3. For example, the stress-strain relationship of the concrete under compression is calculated in VecTor3 using a Hognestad relationship for “pre-peak” and using the Kent and Park (1971) relationship for “post-peak”, which has been modified by Park *et al.* (1982) to ‘account for the enhancement of concrete strength and ductility due to confinement’ (Wong *et al.*, 2013). Figure 4 shows the resulting monotonic stress-strain relationship for the concrete in compression using a compression strength of 32 MPa and neglecting the effects due to confinement, which is calculated using the Kupfer/Richart relationship (Kupfer *et al.*, 1969; Kupfer & Gerstle, 1973).

All models are summarized in Table 2, where the reader is directed to Constantin (2016) and ElMohandes and Vecchio (2013) for more information on the selected models.

In the next section, the results from VecTor3 of a model C-shaped wall will be shown to provide good agreement with predictions of the force-displacement and strain distribution results when compared to

recent experimental results. For sake of brevity, the results from only one experimental test specimen have been used here to validate the finite element models given in Table 2. However, it should be noted that the results from other experimental wall specimens were also used in Hoult *et al.* (2018) to validate some of these materials models in VecTor3.

2.1 TUC from Constantin & Beyer (2016)

Constantin and Beyer (2016) investigated the seismic behavior of C-shaped walls using quasi-static cyclic bi-directional loading along the diagonal direction of the wall. One of the wall specimens denoted TUC is shown in Figure 5 and was built at half-scale with detailing for high ductility. The test campaign was a continuation of the campaign conducted by Beyer *et al.* (2008b), thus the overall geometry of the specimens were the same. However, the reinforcement layouts, instrumentation and loading history differed in Constantin and Beyer (2016) with TUC in comparison to the wall specimens tested from Beyer *et al.* (2008b). For example, to investigate the influence of concentrated versus distributed reinforcement on the overall performance of the wall, the longitudinal reinforcement layout was different in the two flanges of specimen TUC. Furthermore, one of the key objectives for the testing by Constantin and Beyer (2016) was to investigate the behavior of the wall under diagonal loading, which differed from the loading profile conducted in Beyer *et al.* (2008b).

Wall specimen TUC was subjected to a constant axial load ratio ($ALR = P/f'_c A_g$) of 0.06 (or 6%), where the concrete compressive strength (f'_c) at the day of testing was 42 MPa, the gross cross-sectional area of the wall (A_g) was 320,000 mm², and thus the axial load (P) was calculated to be 806.4 kN. The mean values for the mechanical properties of the reinforcing steel used in specimen TUC are given Table 3.

Loading was first applied to specimen TUC in the principal directions (i.e. parallel to the web and flanges, or bending about the major and minor axes) to check the strength capacity at small drift levels. The main cycles of loading were applied along the two geometric diagonals of the C-shaped wall (directions E-F and H-G in Figure 6b). More information on the instrumentation used, test setup, and cyclic loading history can be found in Constantin and Beyer (2016).

VecTor3 (ElMohandes & Vecchio, 2013) was used to construct a model of wall specimen TUC, where the force-displacement relationship and strain distributions obtained experimentally both up the height of the wall and across the section of the wall will be used for comparison to the results from the numerical analyses in an attempt to validate the chosen material models.

The VecTor3 3-dimensional model of specimen TUC is shown in Figure 7. It is comprised of a total of 10410 nodes and 6880 elements, with each hexahedral element sized 50 mm x 50 mm horizontally in the x- and y-directions. A refined mesh size in the z-direction was used for the lower region of the wall; the hexahedral elements within 2650 mm from the base were 66.25 mm in height, while the height of the elements above 2650 mm in the z-direction were 100 mm. This mesh setup decreased the computation time while improving the accuracy of cracking and strain distributions at the base of the wall and within the expected yielding region. This approach has been used successfully by other researchers (Bohl & Adebar, 2011; Hoult *et al.*, 2017; Kwan, 1996; Zhang & Li, 2014). It is also important to note that the refined mesh size is within the 3:2 aspect ratio recommended in Wong *et al.* (2013) for VecTor2, which is a limitation which has been extrapolated for 3-dimensional elements here; VecTor2 (Wong *et al.*, 2013) is a FE modelling program for 2-dimensional plane RC sections, whereas VecTor3 can model 3-dimensional solids that are needed for non-rectangular sections. Ten different concrete materials that consisted of different amounts of smeared longitudinal and transverse reinforcement were used to represent specimen TUC, which are shown in Figure 7. A collar at the top of the wall was also modelled using 50 mm x 50 mm x 100 mm elements, enabling application of the loads at same height as the experiment, where the shear span for the East-West and North-South directions of loading were 3350mm and 2950mm respectively. The foundation of the test specimen TUC was not modelled and all nodes were fixed (i.e. all degrees of freedom restrained), which has also been practiced by other researchers using the VecTor software (Bohl, 2003; Constantin, 2016; Hoult *et al.*, 2017).

The corresponding longitudinal (ρ_{wy} , in the z-direction) and transverse ($\rho_{wh,x}$ and $\rho_{wh,y}$, in the x and y-directions) reinforcement ratios, as well as the diameter of the reinforcing bars in the longitudinal (d_{bl}) and transverse ($d_{bt,x}$ and $d_{bt,y}$) directions, used in these different regions are given in Table 4. It should

be noted that the Young's Modulus (E_c) and tensile strength (f'_t) of the concrete used for the materials were taken as the lower characteristic values given in Constantin and Beyer (2016).

The nodes at the base of wall were assigned fixed conditions. The axial load was kept constant during the testing of the wall and was distributed evenly to all of the nodes at the top of the wall section. A 1 mm displacement was applied to all nodes at the top of wall for the lateral loading, which was then controlled incrementally with monotonic loading. The direction of the controlled displacement was such that the wall could be assessed for bending about the major axis (Figure 6, A-B), minor axis (Figure 6, C-D), and in the diagonal directions (Figure 6, E-F and G-H). It should be noted that displacements for bending about the major and minor axes were limited to drifts of approximately 0.1%, corresponding with the loading protocol in Constantin and Beyer (2016). Furthermore, cyclic loading was also conducted in VecTor3 for the diagonal loading directions corresponding to directions E-F and G-H in Figure 6.

Several comparisons are made between the results from VecTor3 and the experimental observations from Constantin and Beyer (2016) to ultimately determine the applicability of the material models and the finite element modelling program for predicting the performance of C-shaped walls. The experimental force-displacement observations are compared to the predictions made by VecTor3 from monotonic and cyclic loading applied in all directions, including bending about the major axis, minor axes and diagonally. The force-displacement results from VecTor3 for all modes of bending and for the analyses with monotonic loading are given in Figure 8. The experimental results from Constantin and Beyer (2016) are also shown in Figure 8. Furthermore, the same force-displacement relationship comparisons are given in Figure 9 for the VecTor3 analyses with reverse cyclic loading. In general, the force-displacement relationship predicted by VecTor3 compares well with the experimental observations for all modes of bending.

The vertical strains on the outside of the flange ends were reported in Constantin and Beyer (2016) for wall specimen TUC using measurements obtained from the Linear Variable Differential Transformer (LVDT) chains that were mounted up the wall height. The strain distributions with height at diagonal loading drifts of 0.4% and 1.0% from Constantin and Beyer (2016) are given in Figure 10 for the both

directions E-F and G-H. The average vertical strain results were extracted from the VecTor3 results for monotonic loading using the elements on the outer face at the boundary-to-flange intersection and are superimposed in Figure 10. There are some slight inconsistencies with the strain comparisons; for example, the strains at approximately 150 mm from the base of the wall at position G (Figure 10d). This low strain value predicted numerically is most likely a result of lower cracking widths, or less cracking in general, for this area of the wall predicted by VecTor3 in comparison to the experimental data. This could be due to a range of things, such as the values assumed or used for the mechanical properties of the concrete (e.g. tensile strength). Moreover, the experimental results may have some inherent randomness related to cracking distributions in comparison to the FE modelling calculations. However, the overall strain distribution results predicted by VecTor3 generally compare well to the experimental observations for the diagonal directions of loading. This observation is particularly true for the strains close to the base of the wall, which is important for the analyses undertaken in this research investigation.

For this study, it is also important that VecTor3 is capable of accurately predicting the vertical strains at the base of the wall and across the section. Figure 11 illustrates the vertical strains from VecTor3 for monotonic loading across the base of the C-shaped wall section of TUC for the different directions of diagonal loading (according to Figure 6b) and for two different levels of average drift ($\delta = \Delta_{SRSS}/H_e$). It should be noted that the square root of the sum of squares (Equation 4) was used in calculating δ to obtain displacements representative of the diagonal direction of loading, consistent with what was practiced in Constantin and Beyer (2016). These estimates are compared in Figure 11 to what was observed experimentally from Constantin and Beyer (2016). In general, the estimates from VecTor3 of the vertical strain for these two average drifts agree with what was observed experimentally.

$$\Delta_{SRSS} = \sqrt{\Delta_x^2 + \Delta_y^2} \quad 4$$

Overall, VecTor3 has been shown to provide well-correlated results to the experimental observations from wall specimen TUC (Constantin & Beyer, 2016). Importantly, the vertical strain distributions at the base of the wall for different directions of loading and average drifts were well correlated.

Therefore, numerical analyses have been conducted on C-shaped walls using VecTor3 with a range of different parameters commonly observed in both low-to-moderate and high seismic regions to assess the effects of shear lag.

2.2 VecTor3 Analyses for Shear Lag Effects

In total, 54 RC C-shaped walls with varying parameters have been analyzed in VecTor3. Three different walls, denoted here as walls CW1, CW2 and CW3, have different web and flange lengths (L_w and L_f respectively) to accommodate elevator cars; CW1 and CW3 enclose one 500kg capacity (6 person) elevator car while CW2 encloses two 500kg capacity cars. The internal dimension of one 500kg capacity car is 1000 mm x 1300 mm (RLB, 2014). Therefore, the resulting lengths of the web (L_w) and flange (L_f) that were required for the three different walls are given in Table 5.

All of the low-rise C-shaped cores are 3-storeys tall with an inter-storey height of 3500 mm, which makes the full height (H_n) and effective height ($H_e \approx 0.7H_n$) of the walls 10.5 m and 7.35 m respectively. This corresponds to aspect ratios ($A_r = H_e/L_w$), or flexure-to-shear strength ratio, for all of the walls and directions of bending greater than two. The flanges and web of all the walls had a thickness (t_w) of 200 mm. A sensitivity study was conducted in Hoult (2017) using different mesh and element sizes in VecTor3 for predicting the behavior of RC C-shaped walls, where two elements across the thickness of the walls was found to produce sufficiently accurate results. As practiced in the previous section, the 3:2 aspect ratio for plane stress elements as recommended in Wong and Vecchio (2002) and Palermo and Vecchio (2007) was adhered to, but further extrapolated to hexahedral elements for VecTor3. The element size in the x, y and z-directions for all models were 100 mm, 100 mm and 150 mm respectively. This resulted in a total number of hexahedral elements for CW1, CW2 and CW3 of 4704, 5684 and 5684 respectively. As an example, the elevated and cross-sectional views of the VecTor3 model of CW3 are shown in Figure 12.

The material and constitutive models that were summarized in Table 2 will be used in VecTor3 to conduct these analyses. A transverse reinforcement ratio of 1.00% was assumed for the confined regions of the walls in the x and y directions, while 0.25% was used in the unconfined regions of the

wall to correspond with the minimum for design of RC walls in many codes [e.g. AS 3600:2009 (Standards Australia, 2009)]. For this study, a mean insitu compressive strength (f_{cmi}) of 32 MPa was used for all walls, which is a popular strength used in design for buildings less than 13 storeys (Menegon *et al.*, 2015). The f'_t of the concrete was calculated to be 3.3 MPa using the expressions from fib (2012).

The reconnaissance study by Albidah *et al.* (2013) found that the axial load ratio (ALR) was generally low for RC walls, with 75% of the surveyed walls having an ALR lower than 0.05 (5%) while the highest ALR did not exceed 0.10 (10%). However, during seismic excitations the net axial force that acts on an RC wall can increase, or decrease, depending on the direction of motion (Hassan & El-Tawil, 2003). Therefore, three different $ALRs$ were chosen to assess the RC walls: 0%, 10%, and 20%. The axial load was distributed to all nodes at the top of the wall and was held constant throughout the analyses.

Both distributed and concentrated longitudinal reinforcement were used for the walls to observe any difference in longitudinal strain and shear lag effects due to the type of reinforcement detailing. Adebar and Lorzadeh (2012) note that it is rare for RC walls to have a vertical reinforcement ratio (ρ_{vv}) greater than 1.00%, thus an average ρ_{vv} of 1.00% was chosen for all walls. This results in the walls with concentrated longitudinal reinforcement to have vertical ratios of 1.13% in the boundary ends and 0.45% in between using D12 and D8 bars respectively, whereas the walls with distributed reinforcement had 1.00% using D8 bars. The reinforcement ratio values used for the different material types in VecTor3 (shown in Figure 12) are given in Table 6. Smeared reinforcement was used to model the steel embedded in the concrete in VecTor3, which has successfully been used in other research investigations (Beyer, 2007; Bohl & Adebar, 2011; Ghorbani-Renani *et al.*, 2009; Hoult *et al.*, 2017; Luu *et al.*, 2013; Palermo & Vecchio, 2007; Sritharan *et al.*, 2014). Mean values of the material properties for the reinforcing steel were taken from Constantin and Beyer (2016) for D6, D8 and D12 bars, which were given in Table 3.

The nodes at the base of wall were assigned fixed conditions, while the nodes around the outer faces of the wall had constraints such that the wall would not move out of plane. A 1 mm lateral

displacement was applied to all nodes at the top of the model at the effective height, and these displacements were monotonically increased until a 2.0% average drift was achieved; the 2.0% drift limit was used to represent the “ultimate limit state” (ULS) for all analyses as it is widely considered in the earthquake engineering community to be representative of the demand imposed by an extreme seismic event (Pantazopoulou & French, 2001). It should be noted that the definition of drift used here corresponds to the displacement at roof level relative to the height of the modelled wall. The three different directions in which the displacements were applied at the top of the wall corresponded to the wall bending about the major axis and minor axis (with WiC and WiT). Due to time constraints, it was not possible to conduct analyses which involved cyclically varying displacements. While the author acknowledges that C-shaped walls can be subject to diagonal loading, this research is limited to focusing on two primary modes of flexure: bending parallel to the web and flanges. Furthermore, analyses that included “twisting” of the wall were not conducted; in a “real world” situation, a C-shaped wall in a building is likely to twist due to seismic loading being applied offset from the shear center of the wall, particularly for bending about the major axis. However, the primary focus of this investigation is to observe the effects due to shear lag of C-shaped walls with in-plane loading using three modes of bending.

3. Shear Lag in C-shaped Walls with VecTor3

Using the results from VecTor3, the vertical strain distributions across the web and flanges of the C-shaped walls were analyzed for the effects of shear lag. These average strains were extracted from the center of the elements on the outside of the wall at the base and for drift (δ) levels that correspond to (i) first yield and (ii) 2.0%. It should be noted that none of the walls were deemed to have failed at an average drift of 2.0% using material strain limitations; the ϵ_{su} (Table 3) was used for the steel strain limit while a conservative limiting strain value of 0.01 was used for the confined concrete areas. A strain value of 0.01 is lower than the design confined concrete strain value for these walls calculated using the expression given in Priestley *et al.* (2007).

The resulting vertical strain distributions were different for each mode of bending. Therefore, the next sections are separated into the three different modes of bending that were used in this study to

discuss the effects of shear lag. Interestingly, the strain distributions across the section of the wall *parallel* to the direction of the imposed loading (e.g. web in the case of a C-shaped wall bending about the major axis) were close to linear; a linear strain distribution, as assumed in the elementary theory of bending (Bernoulli-Euler assumption), appeared to be appropriate for the sections of a C-shaped wall with length parallel to the direction of bending. However, for the sections of the C-shaped wall that were perpendicular to the imposed load (e.g. flanges in the case of a C-shaped wall bending about the major axis), shear lag effects were present and sometimes significant. This appears to be consistent with the design recommendations for C-shaped walls proposed by Ray (1995), adopted from BS 5400 (British Standard Institution, 1979), as discussed in Section 1. Therefore, the following sections only discuss the shear lag effects in the sections of the wall that are perpendicular to the imposed loading.

3.1 Bending about the Major Axis

The longitudinal strains across the flange in compression (FiC) and tension (FiT) at *yield* for the C-shaped walls with bending about the major axis are given in Figure 13. Importantly, the strain values have been normalized to the maximum absolute value (i.e. the tension strains across the FiT have been normalized to the yield strain value of approximately 0.0027). Similarly, the distance along the section has been normalized to the length of the flange (L_f), as this length can differ depending on the wall (Table 5). As shown in Figure 13b, the yield strain is first reached at the intersection of the web and FiT. Due to the effects of shear lag, the strain decreases along the FiT towards the free-end (boundary end) of the flange. As the *ALR* increases, the FiT becomes less effective, substantiated with the results from the numerical studies on C-shaped walls from Hassan and El-Tawil (2003). Furthermore, the strain distributions are similar for the FiC, where the largest compression strain occurs in the intersection of the web and flange. The compression strains then decrease out to the free-end of the flange. For the strains in the FiC, the *ALR* increases the effectiveness of the flange. For the same direction of loading, the normalized longitudinal strains across the FiC and FiT at the *ULS* ($\delta = 2.0\%$) from VecTor3 are given in Figure 14. The longitudinal strains across the FiT in Figure 14b at the ULS are similar to those illustrated in Figure 13b at yield. However, there is a

noticeable increase in strain at the boundary end of the FiT for some of the wall results relative to the strain values in the middle of the flange; this is discussed in more detail in the next paragraph. The longitudinal strains across the FiC at ULS in Figure 14a are considerably different from that observed at yield (Figure 13a), where increasing the *ALR* on the wall can significantly decrease the effectiveness of the flange. The longitudinal strain distribution across the FiT and FiC at ULS had little dependence if any on the type of longitudinal reinforcement detailing used, whether that be concentrated in the boundary ends or evenly distributed throughout the flange.

For the analyses with FiT, the increased effectiveness of the flange boundary end relative to the middle of the flange is dependent on the section geometry, or the ratio of length of the flange to the length of the web (L_f / L_w). This is illustrated in Figure 15a, which gives the normalized strain distributions across the normalized flange length for the three different walls (CW1, CW2 and CW3 with L_f / L_w of 0.80, 0.53 and 1.05 respectively). It should be noted that for the purposes of illustrating the different strain distribution results in Figure 15a, only the walls with concentrated reinforcement and an *ALR* of 0% were used. When the L_f / L_w is much less than 1.0 (e.g. wall CW2, with a L_f / L_w of 0.53), the strains across the flange decrease out from the web-flange intersection. In contrast, when L_f / L_w is close to unity (e.g. wall CW3, with a L_f / L_w of 1.05), the strains along the flange start to decrease out from the web-flange intersection, but increase close to the maximum (absolute) strain value at flange boundary end. While the strain distributions across the flange are different depending on the section geometry of the wall, the effective widths (using Equation 1) are fairly consistent for all of the analyses with FiT at ULS. This consistency is reflected in Figure 15b, which gives the normalized b_{eff} (to the actual width, b) for all of the analyses with FiT at ULS.

Similar to the research findings from Coull and Bose (1975), Coull and El Magd (1980) and Kwan (1994) on RC boxed core walls, second-order-polynomial functions could be derived to predict the strain distribution across the flange(s) for a C-shaped wall and for bending about the major (strong) axis. However, an emphasis for this research output is for simplicity, such that the recommendations that are given could readily be used by practicing engineers or implemented in design codes. Therefore, a simple equation to estimate the effective width (b_{eff}), which can then be used in a

sectional (or moment-curvature) analysis, will instead be investigated in Section 4 and for all in-plane directions of loading.

3.2 Bending about the Minor Axis (Web in Tension)

Figure 16 gives the normalized longitudinal strain distribution across the web at *yield* for the C-shaped walls with bending about the minor axis (WiT). In contrast to the findings in Section 3.1, the type of detailing of the longitudinal reinforcement resulted in vastly different vertical strain distributions for this direction of loading. When the longitudinal reinforcement is concentrated at the boundary ends (Figure 16a), the yield strain is first reached in the center of the web for the large majority of the walls analyzed. These strain distributions are potentially due to the resulting cracking distributions; for example, it was found in Sritharan *et al.* (2014) that larger crack widths are expected in the lightly reinforced web region in comparison to the boundary regions with large reinforcement ratios, where crack widths are much smaller. This type of cracking distribution would result in high tensile strains in the middle of the web in comparison to the web-flange intersection, consistent with what is being observed in Figure 14a, and particularly for the walls in pure flexure where the *ALR* is zero. If the web of the C-shaped wall has uniformly distributed longitudinal reinforcement (Figure 16b), the strain distribution appears to be parabolic in shape across the web with the yield strain being reached first in the corners (intersection of the web and flange). This distribution is more consistent with the expected effects due to shear lag. Depending on the *ALR*, detailing the wall such that the reinforcement is uniformly distributed rather than concentrated at boundary ends can reduce the effects due to shear lag for this direction of loading, which corroborates with the experimental findings on T-shaped wall specimens from Brueggen *et al.* (2017), as discussed briefly in Section 1. The results from VecTor3 for bending about the minor axis (WiT) indicate that the *ALR* can increase the effectiveness of the web for C-shaped walls at yield when the reinforcement is concentrated (Figure 16a), whereas the *ALR* can decrease the effectiveness of the web at yield for walls with an evenly distributed amount of longitudinal reinforcement (Figure 16b).

As the drift level increases, VecTor3 estimates that the web of the walls in tension become more effective, which is illustrated in Figure 17 with the normalized longitudinal strain distributions across

the web of the wall at a drift of 2.0% for all walls of either concentrated or distributed reinforcement. This corroborates with the findings from Brueggen (2009) and Hassan and El-Tawil (2003), as discussed briefly in Section 1, where the shear lag phenomenon is more apparent for pre-yield drift levels, and the flange (or web, in this case) of the wall can become more effective as the drift level increases.

3.3 Bending about the Minor Axis (Web in Compression)

The longitudinal strains across the web *at yield* for the C-shaped walls and for bending about the minor axis (WiC) are given in Figure 18. The strains are distributed in a parabolic fashion across the web of the wall for this direction of loading, independent of the longitudinal reinforcement detailing. As the *ALR* increases, the web of the wall becomes less effective, corroborating with that observed by Hassan and El-Tawil (2003) for C-shaped RC walls, as discussed briefly in Section 1.

Interestingly, at the ULS ($\delta = 2.0\%$), the web of the walls becomes more effective, but only by a marginal amount. Thus, the strain distributions for ULS in correspondence with a drift of 2.0% are not presented for sake of brevity.

4. Effective Width (b_{eff}) results

Using Equation 1, the effective width (b_{eff}) can be calculated using the strain distribution results from VecTor3 given in Section 3. For each mode of bending, a Pearson's correlation matrix aids in determining if the *ALR* is a dependent variable for estimating the b_{eff} (see Appendix). If it is found that the *ALR* provides a low Pearson's correlation coefficient (i.e. the b_{eff} has little to no dependence on the *ALR*), the b_{eff} is simply a certain fraction of the width of the section (b), which corresponds to either the length of the web or flange dependent on the direction of loading. It should be noted that in some cases it was observed that the *ALR* only affected the b_{eff} for walls with concentrated longitudinal reinforcement and not the walls with distributed reinforcement and vice-versa. For example, Figure 24 (see Appendix) gives the normalized b_{eff} for the range of *ALR* used in the VecTor3 analyses. In Figure 24a, the b_{eff} / b is observed to decrease with increasing *ALR* for the flange in tension (FiT) with distributed reinforcement, whereas the b_{eff} / b is more consistent for the range of *ALR* used and for

concentrated reinforcement. In contrast, the ALR increases the b_{eff} / b in Figure 24b for the web in compression (WiC) with concentrated reinforcement. A multiple linear regression analysis is conducted for each mode of bending to find the values of α and β in Equation 5 to provide the closest correlating value of b_{eff} compared to that calculated using the strain distribution results from VecTor3.

$$b_{eff} = \alpha b(1 + \beta ALR) \quad 5$$

Table 7 gives the resulting values of α and β for all modes of bending, sections of the wall (e.g. FiT or FiC) and for two performance levels (yield and ULS). Figure 19 illustrates the close correlation ($r^2 = 0.94$) of the calculated b_{eff} using Equation 5 and the values in Table 7 compared to the b_{eff} calculated from VecTor3 for the 54 C-shaped walls analyzed.

The values for α in Table 7 range from 0.64 to 0.88, which is equivalent to the b_{eff} / b for C-shaped walls with no applied axial load. These values can be compared to the effective width parameter values adopted from BS 5400 (British Standard Institution, 1979), as seen in Table 1 and recommended by Ray (1995) to be used for the design and analysis of RC C-shaped walls. Using b / H_n values of 0.08 and 0.13 for bending about the major axis (where b is 1600 mm and 2100 mm), corresponding effective width parameter (ψ) values of 0.74 and 0.63 are extrapolated from Table 1. These values appear to be similar to those derived using the VecTor3 results in Table 7, which range from 0.64 to 0.81 for this direction of loading. Furthermore, using b / H_n values of 0.14 and 0.19 for bending about the minor axis (where b is 2000 mm and 3000 mm), corresponding values of ψ of 0.60 and 0.52 are extrapolated from Table 1. These values recommended by Ray (1995) are conservative in comparison to the values in Table 7, which range from 0.73 to 0.88 for this direction of loading.

The next section illustrates how the b_{eff} calculated with Equation 5 can be applied to a moment-curvature analysis to predict the bending strength of a C-shaped wall. Importantly, it will be shown that the effective width method gives similar bending strength values in comparison to a moment-curvature analysis that includes the more complicated nonlinear strain profiles resulting from shear lag.

5. Moment-curvature Analyses

A moment-curvature ($M-\phi$) analysis (or sectional analysis) program was written in Microsoft Excel specifically for RC C-shaped walls using the guide provided in Lam *et al.* (2011). Importantly, the $M-\phi$ program can conduct the analyses for the three different bending directions: about the major axis, about the minor axis with web in compression (WiC), and about the minor axis with web in tension (WiT). The stress-strain relationship for the confined concrete was calculated using the model from Mander *et al.* (1988), which compared well to the model used in VecTor3 (Table 2) with the Kupfer-Richter confinement model applied. The stress-strain curves for the reinforcing steel were adopted from Wong *et al.* (2013) and represents the back-bone curve of the Seckin (1981) stress-strain relationship used in the VecTor3. The same material properties for the concrete and steel were adopted from Section 2.2. The concrete section is divided into a number of layers for the fibre-element model, creating horizontal slices of the section. Sixty slices were deemed to be sufficient for the purposes of moment-curvature analysis for the C-shaped sections (Hoult, 2017). The $M-\phi$ program written in Excel is then verified by comparing the results produced by third-party software RESPONSE-2000 (Bentz, 2000). The $M-\phi$ program in Excel, which initially assumes that plane sections remain plane (Bernoulli-Euler assumption), can then be modified to include shear lag effects by using the strain profiles obtained from the VecTor3 analyses. Furthermore, the program can be modified again by plane sections remain plane principals but with the effective width (b_{eff}) used for the flanges or web using Equation 5. These three scenarios and idealized strain distributions are shown in Figure 20 for a C-shaped wall bending about the major axis. For this example, wall CW2 (Section 2.1, with L_w and L_f of 3000 mm and 1600 mm respectively) is used to illustrate how the effective width method can be included for $M-\phi$ analyses, where the ALR is assumed to be 10% and distributed reinforcement is used (ρ_{wy} of 1.00%).

For bending about the major (strong) axis, the $M-\phi$ results from the program written in Excel and RESPONSE-2000 (Bentz, 2000), which both assume that sections remain plane after bending, are given in Figure 21a. Both of these curves compare well, validating the Excel $M-\phi$ program for this wall and for this mode of bending. The minor difference observed between the RESPONSE-2000 and Excel (No Shear Lag) curves is most likely due to the different material models used to model the

concrete; the model from Popovics (1973) is used to calculate the stress-strain relationship for the concrete in RESPONSE-2000, while the Mander *et al.* (1988) model is used in the Excel program developed here, as state previously. Furthermore, the models from Vecchio and Collins (1986) and Bentz (1999) are used in RESPONSE-2000 to model concrete compression softening and concrete tension stiffening effects respectively, which are not included in the Excel calculations.

Superimposed in Figure 21a are the results from the Excel program with nonlinear strain distributions obtained from VecTor3 (Section 2.3) and for modified flange widths using the b_{eff} calculated from Equation 5. It should be noted that the b_{eff} was calculated to be approximately 1166 mm for the FiT (for both yield and ULS), while the b_{eff} for the FiC was estimated to be 1106 mm pre-yield and 819 mm post-yield (ULS). Figure 21a shows that the two different methods, either by using the actual strain distribution from VecTor3 or providing the effective width of the flanges, results in reduced moment capacities in comparison to the analyses with no consideration of shear lag effects. Figure 21b gives the normalized $M-\phi$ plots, where the moments have been normalized to the maximum moment obtained from the Excel analysis with no shear lag. A bending strength reduction of approximately 10% is shown when using the effective width method in the moment-curvature analysis in comparison to the $M-\phi$ curves using the full flange width. This appears to be conservative in comparison to the method using the actual strain distribution results (from VecTor3) for this wall and direction of loading.

This same $M-\phi$ procedure was conducted for wall CW2 but for bending about the minor axis (WiC). All of the $M-\phi$ results are shown in Figure 22. It should be noted that the b_{eff} of the web was calculated to be 2610 mm using Equation 5. The $M-\phi$ from RESPONSE-2000 and Excel (No Shear Lag) provide reasonable comparisons. The $M-\phi$ curves that include shear lag effects (nonlinear strain distribution and effective width method) produce similar results with a bending strength reduction ranging from 2% to 6%.

All of the $M-\phi$ results for wall CW2 and for bending about the minor axis (WiT) are shown in Figure 23. Note for this wall that the b_{eff} of the web was calculated using Equation 5 to be 2520 mm and 2640 mm for pre-yield and post-yield (ULS) respectively. Not surprisingly, the two $M-\phi$ curves that

have the Bernoulli-Euler assumption (with no shear lag) result in similar values. The $M-\phi$ curves that include shear lag effects are similar with the curves based on the b_{eff} providing more conservative values. The bending strength is reduced by approximately 7% using the $M-\phi$ analysis based on the b_{eff} method to include the effects of shear lag.

6. Conclusions

A numerical investigation was undertaken to explore the effects of shear lag for RC C-shaped walls using VecTor3. It was found that shear lag effects are prominent in the wall section perpendicular to the direction of loading. Furthermore, depending on the direction of loading and ALR , shear lag effects were typically more significant for pre-yield drifts, which corroborates with previous experimental observations on RC T-shaped walls. As there is still a paucity of experimental research on RC C-shaped walls, it is recommended experimental studies be undertaken with one of the primary focuses of investigating the strain/stress distribution and effects due to shear lag.

A simple expression was derived to estimate the effective width of the web or flange(s) of RC C-shaped walls. Importantly, the equation derived from this study is dependent on the web or flange width and, for some directions of loading, the ALR and longitudinal reinforcement layout, whether concentrated or uniformly distributed. This research investigation was limited to analyzing two dependent variables for shear lag effects: the ALR and the detailing of the longitudinal reinforcement. Thus, the expression derived in this study (Equation 5) and subsequent parameters in Table 7 should be limited to the range of values used in the study (i.e. $ALRs$ within a range of 0% to 20%). More research on shear lag effects in non-rectangular RC walls is warranted, with an emphasis on experimental research. Moreover, more research is required to justify that shear lag effects in RC walls had no significant dependence on the height of the walls.

It is recommended that practicing engineers adopt a simple method for including shear lag effects within analysis and design for RC walls with flanges, such as the effective width method. This research has offered such an approach specifically for the in-plane bending of RC C-shaped walls.

7. Appendix

582 See Table 8, Table 9, Table 10, Table 11, Table 12, Table 13 and Figure 24.

583 **8. References**

- 584 Aaleti, S., Brueggen, B. L., Johnson, B., French, C. E., & Sritharan, S. (2013). Cyclic Response of
585 Reinforced Concrete Walls with Different Anchorage Details: Experimental Investigation.
586 *Journal of Structural Engineering*, 139(7), 1181-1191. doi:10.1061/(ASCE)ST.1943-
587 541X.0000732
- 588 ACI. (2011). *Building code requirements for structural concrete: (ACI 318-11) ; and Commentary:*
589 American Concrete Institute.
- 590 Adebar, P., & Lorzadeh, A. (2012). *Compression Failure of Thin Concrete Walls*. Paper presented at
591 the 15 th World Conference on Earthquake Engineering.
- 592 Albidah, A., Altheeb, A., Lam, N., & Wilson, J. (2013). *A Reconnaissance Survey on Shear Wall*
593 *Characteristics in Regions of Low-to-Moderate Seismicity*. Paper presented at the Paper
594 presented at the Australian Earthquake Engineering Society 2013 Conference, Hobart, VIC.
- 595 Arabzadeh, H., & Galal, K. (2017). Seismic Collapse Risk Assessment and FRP Retrofitting of RC
596 Coupled C-Shaped Core Walls Using the FEMA P695 Methodology. *Journal of Structural*
597 *Engineering*, 143(9), 04017096. doi:doi:10.1061/(ASCE)ST.1943-541X.0001820
- 598 Bentz, E. C. (1999). *Sectional Analysis of Reinforced Concrete Structures*. (PhD), University of
599 Toronto, Toronto, Ontario.
- 600 Bentz, E. C. (2000). RESPONSE-2000: Sectional Analysis of Reinforced Concrete Members (Version
601 1.0.5). University of Toronto. Retrieved from <http://www.ecf.utoronto.ca/~bentz/r2k.htm>
- 602 Beyer, K. (2007). *Seismic design of torsionally eccentric buildings with U-shaped RC Walls*. (PhD),
603 ROSE School. (ROSE-2008/0X)
- 604 Beyer, K., Dazio, A., & Priestley, M. J. N. (2008a). Inelastic Wide-Column Models for U-Shaped
605 Reinforced Concrete Walls. *Journal of Earthquake Engineering*, 12(sup1), 1-33.
606 doi:10.1080/13632460801922571

607 Beyer, K., Dazio, A., & Priestley, M. J. N. (2008b). Quasi-Static Cyclic Tests of Two U-Shaped
608 Reinforced Concrete Walls. *Journal of Earthquake Engineering*, 12(7), 1023-1053.
609 doi:10.1080/13632460802003272

610 Bohl, A. (2003). *Plastic Hinge Length in High-Rise Concrete Shear Walls*. (Masters of Applied
611 Science), The University of British Columbia.

612 Bohl, A., & Adebar, P. (2011). Plastic Hinge Lengths in High-Rise Concrete Shear Walls. *ACI*
613 *Structural Journal*, 108(2), 148-157.

614 British Standard Institution. (1979). BS5400 Steel, concrete and composite bridges, Part 5, Code of
615 practice for the design of composite bridges. *British Standard Institution*.

616 Brueggen, B. L. (2009). *Performance of T-shaped Reinforced Concrete Structural Walls Under Multi-*
617 *Directional Loading*. (Ph.D. Thesis), University of Minnesota, Twin Cities, MN.

618 Brueggen, B. L., French, C. E., & Sritharan, S. (2017). T-Shaped RC Structural Walls Subjected to
619 Multidirectional Loading: Test Results and Design Recommendations. *Journal of Structural*
620 *Engineering*, 143(7), 04017040.

621 CEN. (2004). Eurocode 8: Design of structures for earthquake resistance. Part 1: general rules,
622 seismic actions and rules for buildings. In E. S. E. 1998-1:2004 (Ed.). Brussels, Belgium,
623 2004: Comité Européen de Normalisation.

624 Chang, S. T. (2004). Shear Lag Effect in Simply Supported Prestressed Concrete Box Girder. *Journal*
625 *of Bridge Engineering*, 9(2), 178-184. doi:10.1061/(ASCE)1084-0702(2004)9:2(178)

626 Constantin, R. (2016). *Seismic behaviour and analysis of U-shaped RC walls*. École polytechnique
627 fédérale de Lausanne, Lausanne, Switzerland.

628 Constantin, R., & Beyer, K. (2016). Behaviour of U-shaped RC walls under quasi-static cyclic
629 diagonal loading. *Engineering Structures*, 106, 36-52.
630 doi:http://dx.doi.org/10.1016/j.engstruct.2015.10.018

631 Coull, A., & Bose, B. (1975). Simplified analysis of framed-tube structures. *Journal of the Structural*
632 *Division*, 101(11), 2223-2240.

633 Coull, A., & El Magd, S. A. (1980). Analysis of wide-flanged shearwall structures. *American*
634 *Concrete Institute (ACI) Special Publication*, 63, 575-608.

635 Deschappelles, B., & Kwan, A. K. H. (1997). Shear lag in shear/core walls. *Journal of Structural*
636 *Engineering*, 123(11), 1552.

637 ElMohandes, F. (2013). *Advanced Three-Dimensional Nonlinear Analysis of Reinforced Concrete*
638 *Structures Subjected to Fire and Extreme Loads*. (Doctor of Philosophy), University of
639 Toronto, Toronto, Canada.

640 ElMohandes, F., & Vecchio, F. (2013). Vector3 and FormWorks Plus User Manual. Department of
641 Civil Engineering, University of Toronto. Retrieved from
642 http://www.civ.utoronto.ca/vector/user_manuals/manual6.pdf

643 fib, F. I. d. B. (2012). *Model Code 2010 - Final draft, Volume 2. fib Bulletin No. 66*. Lausanne,
644 Switzerland.

645 Ghorbani-Renani, I., Velev, N., Tremblay, R., Palermo, D., Massicotte, B., & Léger, P. (2009).
646 Modeling and Testing Influence of Scaling Effects on Inelastic Response of Shear Walls.
647 *Structural Journal*, 106(3). doi:10.14359/56500

648 Hassan, M., & El-Tawil, S. (2003). Tension Flange Effective Width in Reinforced Concrete Shear
649 Walls. *Structural Journal*, 100(3). doi:10.14359/12610

650 Hoult, R. (2017). *Seismic assessment of reinforced concrete walls in Australia*. (PhD), University of
651 Melbourne. Retrieved from <http://hdl.handle.net/11343/192443>

652 Hoult, R., Goldsworthy, H., & Lumantarna, E. (2017). Plastic Hinge Length for Lightly Reinforced
653 Rectangular Concrete Walls. *Journal of Earthquake Engineering*.
654 doi:10.1080/13632469.2017.1286619

655 Hoult, R., Goldsworthy, H., & Lumantarna, E. (2018). Plastic Hinge Length for Lightly Reinforced C-
656 shaped Concrete Walls. *Journal of Earthquake Engineering*, 1-32.
657 doi:10.1080/13632469.2018.1453419

658 Hrynyk, T. (2013). *Behaviour and modelling of reinforced concrete slabs and shells under static and*
659 *dynamic loads*. (Doctor of Philosophy), University of Toronto, Toronto, Canada.

660 ICBO. (1994). International Council of Building Officials, Uniform Building Code 1994. Whittier,
661 CA.

662 Ile, N., & Reynouard, J. M. (2005). Behaviour of U-shaped Walls Subjected to Uniaxial and Biaxial
663 Cyclic Lateral Loading. *Journal of Earthquake Engineering*, 09(01), 67-94.

664 Kent, D. C., & Park, R. (1971). Flexural members with confined concrete. *Journal of the Structural*
665 *Division*, 97.

666 Kupfer, H., Hilsdorf, H. K., & Rusch, H. (1969). Behavior of Concrete Under Biaxial Stresses.
667 *Journal Proceedings*, 66(8). doi:10.14359/7388

668 Kupfer, H. B., & Gerstle, K. H. (1973). Behavior of Concrete under Biaxial Stresses. *Journal of the*
669 *Engineering Mechanics Division*, 99(4), 13.

670 Kwan, A. K. H. (1994). Simple method for approximate analysis of framed tube structures. *Journal of*
671 *Structural Engineering*, 120(4), 1221-1239.

672 Kwan, A. K. H. (1996). Shear Lag in Shear/Core Walls. *Journal of Structural Engineering*, 122(9),
673 1097-1104. doi:doi:10.1061/(ASCE)0733-9445(1996)122:9(1097)

674 Lam, N., Wilson, J., & Lumantarna, E. (2011). Force-deformation behaviour modelling of cracked
675 reinforced concrete by EXCEL spreadsheets. *Computers and Concrete*, 8(1), 43-57.

676 Lowes, L., Lehman, D., Kuchma, D., Mock, A., & Behrouzi, A. (2013). Large-Scale Tests of C-
677 shaped Reinforced Concrete Walls. from NEES Project Warehouse
678 <http://nees.org/warehouse/project/104>

679 Luu, H., Ghorbanirenani, I., Léger, P., & Tremblay, R. (2013). Numerical Modeling of Slender
680 Reinforced Concrete Shear Wall Shaking Table Tests Under High-Frequency Ground
681 Motions. *Journal of Earthquake Engineering*, 17(4), 517-542.
682 doi:10.1080/13632469.2013.767759

683 Mander, J., Priestley, M., & Park, R. (1988). Theoretical Stress- Strain Model for Confined Concrete.
684 *Journal of Structural Engineering*, 114(8), 1804-1826. doi:doi:10.1061/(ASCE)0733-
685 9445(1988)114:8(1804)

686 Menegon, S. J., Tsang, H. H., & Wilson, J. L. (2015). *Overstrength and ductility of limited ductile RC*
687 *walls: from the design engineers perspective*. Paper presented at the Proceedings of the Tenth
688 Pacific Conference on Earthquake Engineering, Sydney, Australia.

689 Moehle, J. P. (1992). Displacement- Based Design of RC Structures Subjected to Earthquakes.
690 *Earthquake Spectra*, 8(3), 403-428. doi:doi:10.1193/1.1585688

691 Moffatt, K., & Dowling, P. J. (1975). Shear lag in steel box girder bridges. *The Structural Engineer*,
692 53(10).

693 Palermo, D., & Vecchio, F. J. (2007). Simulation of Cyclically Loaded Concrete Structures Based on
694 the Finite-Element Method. *Journal of Structural Engineering*, 133(5), 728-738.
695 doi:10.1061/(ASCE)0733-9445(2007)133:5(728)

696 Pantazopoulou, S. J., & French, C. W. (2001). Slab Participation in Practical Earthquake Design of
697 Reinforced Concrete Frames. *Structural Journal*, 98(4). doi:10.14359/10291

698 Pantazopoulou, S. J., Moehle, J. P., & Shahrooz, B. M. (1988). Simple Analytical Model for T-Beams
699 in Flexure. *Journal of Structural Engineering*, 114(7), 1507-1523. doi:10.1061/(ASCE)0733-
700 9445(1988)114:7(1507)

701 Park, R., Priestley, M. J. N., & Gill, W. (1982). Ductility of Square-Confined Concrete Columns.
702 *Journal of the Structural Division*, 108(4), 21.

703 Paulay, T. (1986). *The Design of reinforced concrete ductile shear walls for earthquake resistance*:
704 University of canterbury, Department of Civil Engineering.

705 Paulay, T., & Priestley, M. J. N. (1992). *Seismic design of reinforced concrete and masonry buildings*
706 / T. Paulay, M.J.N. Priestley: New York : Wiley, c1992.

707 Popovics, S. (1973). A numerical approach to the complete stress-strain curve of concrete. *Cement*
708 *and Concrete Research*, 3(5), 583-599.

709 Priestley, M. J. N., Calvi, G. M., & Kowalsky, M. J. (2007). *Displacement-based seismic design of*
710 *structures* / M. J. N. Priestley, Gian Michele Calvi, Mervyn J. Kowalsky: Pavia : IUSS Press :
711 Fondazione Eucentre, 2007.

712 Ray, S. (1995). *Reinforced Concrete: Analysis and Design*: Blackwell Science.

713 Richart, F. E., Brandtzaeg, A., & Brown, R. L. (1928). A study of the failure of concrete under
714 combined compressive stresses. *University of Illinois Bulletin*; v. 26, no. 12.

715 RLB. (2014). Riders Digest 2014 Adelaide, Australia Edition: Rider Levett Bucknall.

716 Seckin, M. (1981). *Hysteretic Behaviour of Cast-in-Place Exterior Beam-Column-Slab*
717 *Subassemblies*. (Ph.D. Thesis), University of Toronto, Toronto, Canada.

718 Sittipunt, C., & Wood, S. L. (1993). *Finite element analysis of reinforced concrete shear walls*.
719 Retrieved from <http://hdl.handle.net/2142/14203>

720 Song, Q. g., & Scordelis, A. C. (1990). Shear Lag Analysis of T-, I-, and Box Beams. *Journal of*
721 *Structural Engineering*, 116(5), 1290-1305. doi:10.1061/(ASCE)0733-
722 9445(1990)116:5(1290)

723 Sritharan, S., Beyer, K., Henry, R. S., Chai, Y. H., Kowalsky, M., & Bull, D. (2014). Understanding
724 Poor Seismic Performance of Concrete Walls and Design Implications. *Earthquake Spectra*,
725 30(1), 307-334. doi:10.1193/021713EQS036M

726 Standards Australia. (2009). AS 3600-2009: Concrete Structures.

727 Thomsen, J., & Wallace, J. (2004). Displacement-Based Design of Slender Reinforced Concrete
728 Structural Walls—Experimental Verification. *Journal of Structural Engineering*, 130(4), 618-
729 630. doi:doi:10.1061/(ASCE)0733-9445(2004)130:4(618)

730 Vecchio, F. (2000). Disturbed Stress Field Model for Reinforced Concrete: Formulation. *Journal of*
731 *Structural Engineering*, 126(9), 1070-1077.

732 Vecchio, F., & Collins, M. (1986). The Modified Compression-Field Theory for Reinforced Concrete
733 Elements Subjected to Shear. *Journal of the American Concrete Institute*, 83(2), 219.

734 Vecchio, F., Lai, D., Shim, W., & Ng, J. (2001). Disturbed Stress Field Model for Reinforced
735 Concrete: Validation. *Journal of Structural Engineering*, 127(4), 350-358.

736 Wallace, J. W. (1996). Evaluation of UBC- 94 Provisions for Seismic Design of RC Structural Walls.
737 *Earthquake Spectra*, 12(2), 327-348. doi:10.1193/1.1585883

738 Wallace, J. W., & Moehle, J. P. (1992). Ductility and Detailing Requirements of Bearing Wall
739 Buildings. *Journal of Structural Engineering*, 118(6), 1625-1644.

740 Wallace, J. W., & Wood, S. L. (1994, April 25-27). *Seismic Design of RC Shear Walls with*
741 *Unsymmetrical Cross-Sections*. Paper presented at the ASCE Structures Conference, Atlanta,
742 Georgia.

743 Waugh, J. D. (2009). *Nonlinear analysis of T-shaped concrete walls subjected to multi-directional*
744 *displacements*. (Doctor of Philosophy), Iowa State University, Ames, Iowa, United States.
745 Retrieved from <http://lib.dr.iastate.edu/etd/10525> (10525)

746 Wong, P., & Vecchio, F. (2002). Vector2 and FormWorks User Manual. Department of Civil
747 Engineering, University of Toronto.

748 Wong, P., Vecchio, F., & Trommels, H. (2013). Vector2 and FormWorks User Manual. Department
749 of Civil Engineering, University of Toronto.

750 Zhang, Z., & Li, B. (2016). Seismic Performance Assessment of Slender T-Shaped Reinforced
751 Concrete Walls. *Journal of Earthquake Engineering*, 20(8), 1342-1369.
752 doi:10.1080/13632469.2016.1140097

753 Zhang, Z., & Li, B. (2017a). Seismic behaviour of non-rectangular structural RC wall in the weak
754 axis. *Magazine of Concrete Research*, 69(12), 606-617.

755 Zhang, Z., & Li, B. (2017b). Shear lag effect in tension flange of RC walls with flanged sections.
756 *Engineering Structures*, 143(Supplement C), 64-76.
757 doi:<https://doi.org/10.1016/j.engstruct.2017.04.017>

758 Zhang, Z. W., & Li, B. (2014). *Evaluation of seismic performance of slender L-shaped and T-shaped*
759 *RC structural walls*. Paper presented at the Proceedings of the 2nd European conference on
760 earthquake engineering and seismology. Paper.

Table 1 Effective width factors (ψ) from BS 5400: Part 5 (British Standard Institution, 1979)

b/H_n	ψ
0	1
0.05	0.82
0.1	0.68
0.2	0.52
0.4	0.35

Table 2 Material models to be used in the VecTor3 analyses

Constitutive Behaviour	Model
Compression Pre-Peak	Parabola – Hognestad
Compression Post-Peak	Modified Kent & Park (Kent & Park, 1971; Park <i>et al.</i> , 1982)
Compression Softening	Vecchio 1992-A [e1/e2-Form]
Tension Stiffening	Modified Bentz 2003
Tension Softening	Linear
FRC Tension	Not Considered
Confined Strength	Kupfer/Richart (Kupfer <i>et al.</i> , 1969; Kupfer & Gerstle, 1973; Richart <i>et al.</i> , 1928)
Dilation	Constant Poisson's Ratio
Cracking Criterion	Mohr-Coulomb [Stress]
Crack Stress Calc	Basic [DSFM/MCFT]
Crack Width Check	Aggregate 2.5mm Max Crack Width [Default]
Crack Slip Calc	Walraven [Monotonic] (Vecchio & Collins, 1986)
Creep and Relaxation	Not Available
Hysteretic Response	Nonlinear with Plastic Offsets

Table 3 Mechanical properties of the reinforcing steel for TUC from Constantin and Beyer (2016)

	f_y (MPa)	f_u (MPa)	f_u/f_y	ϵ_{sh} (%)	ϵ_{su} (%)
D6	492	623	1.26	-	6.8
D8	563	663	1.18	-	7.9
D12	529	633	1.19	2.4	9.6

Table 4 Concrete materials used to model TUC in VecTor3

Material	f'_c (MPa)	f'_t (MPa)	E_c (GPa)	ρ_{wy} (%)	d_{bl} (mm)	$\rho_{wh,x}$ (%)	$d_{bl,x}$ (mm)	$\rho_{wh,y}$ (%)	$d_{bl,y}$ (mm)
1	42	3	27.7	0.91	8	1.00	6	1.00	6
2	42	3	27.7	0.91	8	-	-	0.23	6
3	42	3	27.7	1.00	8	1.00	6	1.00	6
4	42	3	27.7	1.00	8	1.00	6	1.00	6
5	42	3	27.7	1.00	8	0.23	6	-	-
6	42	3	27.7	0.31	6	1.00	6	1.00	6

7	42	3	27.7	0.31	6	-	-	0.23	6
8	42	3	27.7	0.31	6	1.00	6	1.00	6
9	42	3	27.7	2.45	12	1.00	6	1.00	6
10	42	10	27.7	-	-	-	-	-	-

Table 5 Dimensions of the C-shaped walls

Wall	L_w (mm)	L_f (mm)
CW1	2000	1600
CW2	3000	1600
CW3	2000	2100

Table 6 Concrete materials used to model the C-shaped walls in VecTor3

Reo. Type	Material	ρ_{wv} (%)	d_{bl} (mm)	$\rho_{wh,x}$ (%)	$d_{bl,x}$ (mm)	$\rho_{wh,y}$ (%)	$d_{bl,y}$ (mm)
concentrated	1	1.13	12	1.00	6	1.00	6
concentrated	2	0.45	8	-	-	0.25	6
concentrated	3	0.45	8	0.25	6	-	-
distributed	1	1.00	8	1.00	6	1.00	6
distributed	2	1.00	8	-	-	0.25	6
distributed	3	1.00	8	0.25	6	-	-

Table 7 Parameters and values for b_{eff} of C-shaped walls

Mode of Bending	LS	Reinforcement	α	β
Major (FiT)	Yield/ULS	concentrated	0.72	0.0
		distributed	0.81	-1.0
Major (FiC)	Yield	concentrated/distributed	0.64	0.8
	ULS	concentrated/distributed	0.80	-3.6
Minor (WiC)	Yield/ULS	concentrated/distributed	0.87	0.0
Minor (WiT)	Yield	concentrated	0.73	1.0
		distributed	0.84	0.0
	ULS	concentrated/distributed	0.88	0.0

Table 8 Pearson's correlation matrix for effective width (flange in tension)

Variables	b	ALR	L_f / L_w	Reinforcement Type	b_{eff}
b	1.000	0.000	0.857	0.000	0.655
ALR	0.000	1.000	0.000	0.000	-0.514
L_f / L_w	0.857	0.000	1.000	0.000	0.615
Reinforcement Type	0.000	0.000	0.000	1.000	0.032
b_{eff}	0.655	-0.514	0.615	0.032	1.000

Table 9 Pearson's correlation matrix for effective width (flange in compression, yield)

Variables	b	ALR	L_f / L_w	Reinforcement Type	b_{eff}
b	1.000	0.000	0.857	0.000	0.810
ALR	0.000	1.000	0.000	0.000	0.550
L_f / L_w	0.857	0.000	1.000	0.000	0.757
Reinforcement Type	0.000	0.000	0.000	1.000	-0.044
b_{eff}	0.810	0.550	0.757	-0.044	1.000

Table 10 Pearson's correlation matrix for effective width (flange in compression, ULS)

Variables	b	ALR	L_f / L_w	Reinforcement Type	b_{eff}
b	1.000	0.000	0.857	0.000	0.213
ALR	0.000	1.000	0.000	0.000	-0.870
L_f / L_w	0.857	0.000	1.000	0.000	0.344
Reinforcement Type	0.000	0.000	0.000	1.000	-0.065
b_{eff}	0.213	-0.870	0.344	-0.065	1.000

Table 11 Pearson's correlation matrix for effective width (web in compression)

Variables	b	ALR	L_f / L_w	Reinforcement Type	b_{eff}
b	1.000	0.000	-0.875	0.000	0.993
ALR	0.000	1.000	0.000	0.000	-0.034
L_f / L_w	-0.875	0.000	1.000	0.000	-0.894
Reinforcement Type	0.000	0.000	0.000	1.000	-0.048
b_{eff}	0.993	-0.034	-0.894	-0.048	1.000

Table 12 Pearson's correlation matrix for effective width (web in tension, yield)

Variables	b	ALR	L_f / L_w	Reinforcement Type	b_{eff}
b	1.000	0.000	-0.875	0.000	0.768
ALR	0.000	1.000	0.000	0.000	0.124
L_f / L_w	-0.875	0.000	1.000	0.000	-0.590
Reinforcement Type	0.000	0.000	0.000	1.000	0.165
b_{eff}	0.768	0.124	-0.590	0.165	1.000

Table 13 Pearson's correlation matrix for effective width (web in tension, ULS)

Variables	b	ALR	L_f / L_w	Reinforcement Type	b_{eff}
b	1.000	0.000	-0.875	0.000	0.983
ALR	0.000	1.000	0.000	0.000	0.048
L_f / L_w	-0.875	0.000	1.000	0.000	-0.839
Reinforcement Type	0.000	0.000	0.000	1.000	-0.095
b_{eff}	0.983	0.048	-0.839	-0.095	1.000

Figure 1 Modes of bending for (a) rectangular walls and (b-d) C-shaped wall

Figure 2 C-shaped wall with expected strain distributions for bending about (a) major axis and (b) minor axis (with web in tension)

Figure 3 Effective width (b_{e1} and b_{e2}) for a C-shaped wall as proposed by Ray (1995)

Figure 4 Monotonic stress-strain relationship used in VecTor3

Figure 5 (a) cross-section and reinforcement layout and (b) elevation view of specimen TUC (Constantin & Beyer, 2016)

Figure 6 (a) cardinal points and sign convention for forces/displacements and (b) loading positions (Constantin & Beyer, 2016)

Figure 7 VecTor3 model of wall specimen TUC (a) elevation and (b) cross-section

Figure 8 Force-displacement relationship for TUC for bending (a) about the major axis (b) about the minor axis (c) diagonal direction (E-F) and (d) diagonal direction (G-H)

Figure 9 Force-displacement relationship for TUC for bending (a) diagonal direction (E-F) and (b) diagonal direction (G-H)

Figure 10 Vertical strain distribution (up the height of the wall) for position (a) E (b) F (c) H and (d) G

Figure 11 Comparisons of the vertical strain distributions at the base of the wall of specimen TUC

Figure 12 VecTor3 model of wall CW3 (a) elevation and (b) cross-section

Figure 13 Normalized strain distribution at yield for bending about the major axis (a) Flange in Compression and (b) Flange in Tension

Figure 14 Normalized strain distribution at ULS for bending about the major axis (a) Flange in Compression and (b) Flange in Tension

Figure 15 (a) normalized strain distribution at ULS for FiT and (b) normalized effective width for all C-shaped walls with FiT (ULS)

Figure 16 Normalized strain distribution at yield for bending about the minor axis (Web in Tension) with longitudinal reinforcement (a) concentrated and (b) distributed

Figure 17 Normalized strain distribution at ULS for bending about the minor axis (Web in Tension)

Figure 18 Normalized strain distribution at Yield for bending about the minor axis (Web in Compression)

Figure 19 Effective width estimates (Equation Error! Reference source not found.) compared to VecTor3 results

Figure 20 Idealized strain distribution with (a) Bernoulli-Euler assumption (no shear lag) (b) Nonlinear distribution due to shear lag and (c) Bernoulli-Euler with effective width method

Figure 21 (a) $M-\phi$ analysis for CW2 (major axis) and (b) normalized $M-\phi$

Figure 22 (a) $M-\phi$ analysis for CW2 (minor axis, WiC) and (b) normalized $M-\phi$

Figure 23 (a) $M-\phi$ analysis for CW2 (minor axis, WiT) and (b) normalized $M-\phi$

Figure 24 Normalized b_{eff} dependent on the ALR for (a) FiT (yield and ULS) and (b) WiC (yield)