**Towards a simple and reliable method for calculating the uplift
capacity of plate anchors in sand**

A. Roy¹, S.H Chow², C.D. O’Loughlin³, M.F. Randolph⁴

^{1,3,4} **Centre for Offshore Foundation Systems, University of Western Australia, Australia**

² **Department of Infrastructure Engineering, the University of Melbourne, Australia**

Article manuscript submitted to Canadian Geotechnical Journal

First submission: May, 2020

¹Corresponding Author
PhD student, Centre for Offshore Foundation Systems (BEng, MEng)
The University of Western Australia
35 Stirling Highway, Crawley WA 6009, Perth, Australia
E-mail: anamitra.roy@research.uwa.edu.au
Orcid: (0000-0002-3093-1848)

²Senior Lecturer, Department of Infrastructure Engineering (BEng, MEng, PhD)
Engineering Block B, Grattan Street, Parkville
The University of Melbourne, Victoria 3010, Australia
Phone: +61 3 9035 7504
E-mail: shiaohuey.chow@unimelb.edu.au
Orcid: (0000-0002-5442-0014)

³Associate Professor, Centre for Offshore Foundation Systems (BEng, PhD)
The University of Western Australia
35 Stirling Highway, Crawley WA 6009, Perth, Australia
Phone: +61 8 6488 6488,
E-mail: conleth.oloughlin@uwa.edu.au
Orcid: (0000-0002-5823-6265)

⁴Professor, Centre for Offshore Foundation Systems (MA, PhD, FAA, FEng, FRS, FTSE, FIEAust, CPEng)
The University of Western Australia
35 Stirling Highway, Crawley WA 6009, Perth, Australia
Phone: +61 8 6488 3075,
E-mail: mark.randolph@uwa.edu.au
Orcid : (0000-0003-3136-6454)

8	Number of words	6731 (excluding abstract, references and captions)
9	Number of figures	17
10	Number of tables	07

Abstract

This paper investigates the uplift capacity of horizontal plate anchors in sand through finite element analyses and centrifuge experiments. Finite element simulations adopt a sophisticated bounding surface plasticity model that accounts for stress and density dependent behaviour, as well as loading and fabric related anisotropic effects in sands. Failure mechanisms at peak anchor capacity show that failure occurs progressively, with a marked decrease in mobilised friction angle within the shear bands close to the anchor edge. Numerical simulations of a large set of centrifuge experiments on rectangular, strip and circular plates at different relative densities and stress levels are in good agreement for dense conditions, but perform poorer for loose conditions due mainly to the open cone yield surface in the bounding surface model. Equivalent comparisons with current limit equilibrium methods highlight the challenges in direct application of element level strength equations. Finally, the paper proposes a modified limit equilibrium solution based on a 'rigid-block' failure mechanism extending to soil surface, but with anchor factors that encompass the results from the finite element simulations. The modified solution provides a higher level of agreement with results from a large database of plate and pipeline test data than existing limit equilibrium methods.

Keywords

Plate anchor capacity; bounding surface plasticity; centrifuge tests; sands; stress level dependence

Introduction

Plate anchors are used onshore as foundation elements for structures subjected to high uplift or lateral loads. They could also be an economical alternative to pile foundations for mooring offshore floating renewable energy devices, as relative to piles, they provide much higher capacity relative to their weight (O'Loughlin and Barron 2012, Al Hakeem and Aubeny 2019). Much of their use offshore (e.g. drag embedment anchors or suction embedded plate anchors) has been in the soft clay deposits typically encountered in deep water (Murff et al. 2005, O'Loughlin et al. 2018), whereas offshore floating renewable energy devices are likely to be sited in much shallower water where coarser-grained seabed deposits are to be expected. Consequently, much less attention has been given to studying the performance of plate anchors in sand than in clay. This will require rectification if plate anchor technology is to find application in the offshore renewable energy industry.

Early experimental studies into plate anchor capacity in sand were mainly at single gravity (1 *g*) and hence at very low stress levels (Murray and Geddes 1987, Rowe and Davis 1982) with a limited number of centrifuge testing programmes at higher and more realistic stress levels (Dickin 1988, 1994). The main contribution from these experimental investigations was to identify soil friction (ϕ) and dilation (ψ_d) angles as the key governing parameters. The earliest analytical methods were mainly based on a 'vertical slip surface' mechanism (Fig. 1 (b)), in which soil failure is assumed to occur along vertical planes extending from the extremities of the buried object to the soil surface (Trautmann et al. 1985), although uniform gradient planar or conical surfaces have also been considered (Vermeer and Sutjiadi 1985). Success of such methods depended on accurate estimation of the lateral stress coefficient to compute shear stress (τ_f in Fig. 1) on the slip surface. More recently (Cheuk et al. 2008), pipe uplift experiments in sand involving sophisticated imaging techniques that revealed the progressive failure nature of the uplift problem concluded that the failure mechanism for a shallowly buried pipe (or plate) was better described using 'inclined slip surfaces' with a tendency for the slip surfaces to curve outwards as they approach the ground surface. Similar evidence revealing inclined deforming soil bands, but with intense shear banding concentrated close to the anchor, can be seen in the image analysis data presented in Liu et al. (2012). In light of this evidence, it is logical to assume that the zone of observed deformation does not necessarily coincide with the zone of intense shearing, such that methods that assume peak shear resistance mobilisation along the entire length of the slip plane would tend to overestimate anchor capacity.

Modern LE methods (White et al. 2008, Giampa et al. 2017) have aimed to strike a balance for this apparent mismatch on shear resistance through certain approximation of the shear stresses on the slip plane, which depend

on inputs of ϕ and ψ_d . Acknowledging that selecting appropriate inputs of ϕ and ψ_d is complicated by their dependence on mean stress level (p'), loading path direction and relative density (R_D), it is of interest to consider more advanced soil models (e.g. bounding surface models) that are able to accurately capture stress dilatancy in sands under progressively evolving stress and strain conditions without explicit inputs of ϕ and ψ_d .

Another aspect of plate anchor capacity that deserves attention is the response at field scale stress levels. Most of the experimental investigations have been reduced scale model testing at very low stress levels (Rowe 1978, Rowe and Davis 1982, Frydman and Shaham 1989, Ilamparuthi et al. 2002, Chow et al. 2018, Giampa et al. 2018) which raises questions about the appropriateness of the resulting analytical methods for field scale applications. Although centrifuge test data (e.g. Tagaya et al. 1988) show that for a given anchor embedment depth, the anchor (capacity) factor reduces as the anchor dimension (and hence stress level) increases, such stress-level dependencies have not been incorporated in design equations used in engineering practice. It would be challenging to quantify this stress-level dependence using element level strength degradation equations as attempted through lumped inputs in White et al. (2008), particularly as the plate anchor boundary value problem involves a multitude of different stress paths and varying stress levels in the domain.

This paper provides a comparative assessment of uplift capacity of shallowly embedded horizontal anchors through finite element (FE) analyses and centrifuge experiments, drawing on the numerical and experimental data to articulate limitations of calculating anchor capacity using simplified methods based solely on specified friction and dilation angles. The FE analyses utilised a sophisticated bounding surface plasticity model that takes into account the variation of dilation with relative density, mean stress, direction of loading and progressive failure (elaborated in Dafalias et al. 2004, Dafalias and Manzari 2004, Papadimitriou et al. 2005) with some modifications that allow for fabric anisotropy. As described in Roy et al. (2020), these simple and practical modifications avoid the more complex variations to the model described in Li and Dafalias (2012) and Petalas et al. (2019), which would be required to account for cyclic loading reversals and stress rotations over multiple cycles, but are unnecessary for the monotonic loading conditions considered in this paper. Results from the FE analyses are validated against centrifuge model tests in loose and dense sand that consider plate anchors of different geometries, and at different embedment depths and gravitational acceleration levels. The numerical results shed light on the mobilised friction angles within the failure mechanisms and identify potential demerits of predictive capabilities of existing methods when used across different stress levels. Finally, results from the FE analyses are represented algebraically, allowing for routine use by practitioners.

Methodology

Details of the numerical analysis

Soil constitutive model details

The finite element simulations adopted a bounding surface plasticity model as elaborated in Table 1, with a governing platform identical to the parent models developed by Dafalias and Manzari (2004) and Dafalias et al. (2004). The model controls sand behaviour with the simultaneous interaction of the yield surface (Eq. (7)) with three other surfaces, namely the critical state surface (Eq. (9)), the bounding surface (Eq. (11)) and the dilatancy surface (Eq. (12)). Lode angle (θ) and state parameter (ψ) dependences for these surfaces, as per Eq. (8 - 12), allow realistic predictions of stresses and strains to be obtained over a wide range of densities and mean stress levels. A unique CSL in $e - p'$ space is assumed (Eq. (1)), consistent with the latest developments in constitutive modelling in sands elaborated in Li and Dafalias (2012). It is widely accepted that mobilised stresses and dilation (Eq. (20)) in sands varies with respect to different loading paths and inherent fabric anisotropy (Vaid et al. 1990, Arthur and Menzies 1972). In order to capture these effects with a unique CSL, the model is implemented by adopting a variable rate of interaction of ψ for different loading directions with regards to sand fabric (encapsulated through A_{ratio} in Eqn. (23)). Scaling parameters (f and f_h in Eq. (24) and Eq. (25)) are used to adjust the influence of ψ (to ψ_f in Eq. (26)), thus altering the contractive/dilative tendencies of the soil in the model's governing equations (Eq. (15), Eq. (16) and Eq. (20)). The implementation adopted here is detailed in Roy et al. (2020) and summarised in Table 1 for completeness. Model parameters for the UWA silica sand (with index properties listed in Table 2) used in the centrifuge experiments were calibrated using an optimisation technique on triaxial compression and extension responses (Fig. 2) at various densities and stress levels ranging from 25 kPa to 667 kPa (see Table 3).

Model details and FE methodology

The problem was modelled numerically in Abaqus (Dassault Systemes, 2012) using a series of plane strain and axisymmetric analyses, with an unstructured mesh (Fig. 3) composed of linear quadrilateral elements (CPE4 and CAX4 respectively). The analyses were conducted for different anchor plate dimensions – width (B) or diameter (D) at shallow embedment ratios (H/B or H/D) between 1.05 and 4 in sand with relative density (R_D) varying between 30% and 85%. The anchor corners were filleted with a radius of $0.02B$ or $0.02D$ to avoid numerical convergence issues. The anchor was weightless and fully rigid, with its centre on the upper surface taken as the reference point for the application of displacements. Minimum element sizes in regions within $0.5B$

(or $0.5D$) around the anchor were maintained at approximately $0.03B$ (or $0.03D$) to capture strain localisation. As shown by Fig. 3, the bottom and lateral boundaries of the domain were $3B$ ($3D$) and $5B$ ($5D$) respectively from the centre of the plate, established from a number of preliminary analyses. All nodes on the bottom boundary were fully restrained, whereas lateral restraint only was imposed for nodes on the side boundaries.

The plate-soil interface was taken as fully rough as previous numerical studies indicate that the interface condition of a plate anchor has minimal influence on capacity (Merifield and Sloan 2006, Merifield et al. 2006, Dickin and Laman 2007, Hao et al. 2014). The unit weight of the soil (γ) was assumed as 15 kN/m^3 in the numerical analysis and the anchor capacities are reported (later in the paper) using the dimensionless anchor factor, $N_\gamma = q_u/\sigma'_{vo}$, where q_u is the peak anchor capacity (expressed as a stress). The coefficient of earth pressure (K_0) for the soil was taken as 0.5. As expected in field conditions, a horizontally layered sand has been defined for the soil by appropriate definition of the fabric tensor ($\mathbf{F}$ in Eqn. (21) in Table 1). An explicit integration scheme based on the formulation described in Sloan et al. (2001) was used to obtain the updated stresses for a given increment of strain.

Details of the experimental program

Model plate anchors

Multiple circular, strip (aspect ratio = 8:1) and rectangular (aspect ratio = 2:1) plate anchor models, fabricated from either steel or aluminium were used in the experiments, with dimensions (width B , length L , diameter D and thickness t) and masses given in Table 4. A higher plate thickness (t) was chosen for the strip anchor models to limit bending. The slight variation in t/D and t/B is not considered to have a meaningful effect on anchor capacity for these experiments, where capacity is derived from mobilisation of a soil mass above the plate. The plates were sand-blasted, with surface roughness measurements (normalised roughness coefficient in the range 0.1 to 0.13) indicating that the surface could be considered fully rough (Paikowsky et al. 1995), although surface roughness is not expected to influence vertical capacity (Merifield and Sloan 2006). As shown in Fig. 4, loading of the anchors was achieved using a smooth rod, 4.7 mm in diameter, screwed to the centre of the plate. The rod extended to above the sand surface, allowing connection to an electrical actuator to load the plate anchor (see Fig. 4).

Sample details

The uplift tests were conducted in a fine sub-angular silica sand (UWA silica sand), with properties as summarised in Table 2. 13 samples were prepared in rectangular centrifuge sample containers (or 'strongboxes') with internal dimensions of $650 \text{ mm} \times 390 \text{ mm} \times 325 \text{ mm}$ (length $\times$ width $\times$ height) by air pluviation using an

151 automated sand rainer. To maintain consistency with the numerical modelling where the anchors were ‘wished-
152 in-place’, the anchors were pre-embedded in the samples. This was achieved by pausing pluviation when the sand
153 reached the required anchor embedment depth, vacuum levelling the sand surface and carefully placing the
154 anchors, with a spatial separation distance such that the uplift mechanisms from adjacent tests would not overlap
155 (calculated assuming an inverted trapezoid (or conical frustum) using a maximum slip surface inclination (to the
156 vertical) of 30° (Liu et al. 2012, Ilamparuthi et al. 2002). Pluviation was then resumed and the sample surface was
157 vacuum-levelled to achieve a desirable final sample height, typically ranging between 160 mm and 240 mm
158 (depending on the targeted embedment ratio). As drained behaviour is of interest, there was no requirement to
159 saturate the samples, noting that this also led to quicker turnaround times between samples.

160 Cone penetrometer tests (CPTs) were conducted in each sample (using a 10 mm diameter cone
161 penetrometer) before the anchor tests. Depth profiles of cone tip resistance, q_c , with depth, z , are provided in Fig.
162 5 which show the expected increase in cone resistance with depth, reflecting the dependence of q_c on vertical
163 effective stress level. Determination of relative density from global measurements of sample mass and volume
164 was hindered by the inclusion of the plate anchors in the sample. For this reason, relative density (and subsequently
165 unit weight) was determined using the empirical relationship between cone tip resistance (q_c) and R_D proposed
166 by Roy et al. (2019) for UWA silica sand. These profiles (also shown in Fig. 5) indicate that relative density was
167 typically in the range $R_D = 41\%$ to 51% and $R_D = 69\%$ to 76% in the loose and dense samples respectively (relative
168 to the targeted $R_D = 45\%$ and $R_D = 70\%$).

169 *Testing program*

170 The plate anchor uplift experiments were conducted at The National Geotechnical Centrifuge Facility in
171 the University of Western Australia using the 3.6 m diameter UWA beam centrifuge. The anchors were tested at
172 shallow embedment ratios (H/B or H/D) ranging between 2 and 4 at acceleration levels between 20 and 100g.
173 These embedment ratios and acceleration levels were selected to cover (field scale) stress levels associated with
174 plate embedment depths in the range 1.2 to 8 m. The test program (outlined in Table 5 and Table 6) involved 60
175 uplift tests across 13 sand samples; 6 loose and 7 dense. The samples are identified as C_j , where ‘C’ is either ‘L’
176 or ‘D’ for a loose or dense sample and ‘j’ denotes the order of testing of the sample. Among the 13 samples, 6
177 (D5 - D7, L4 - L6) were dedicated towards a parallel study on inclined loading and only the vertical uplift tests
178 from these samples are reported here. As detailed in Table 5 and Table 6, the tests were performed at different g -
179 levels to simulate different anchor embedment depths (at fixed embedment ratios) and enable quantification of

potential stress level effects. Also included in Table 5 and Table 6 are values of peak mobilised anchor capacity (q_u) and corresponding anchor factors ($N_\gamma = q_u/H\gamma'$) from each test, obtained by reducing the measured peak uplift load by the sum of the anchor and rod weight (friction along the soil-rod interface was not considered as it was estimated to be less than 5% of the total capacity).

Results and Discussion

Comparison of the present dataset with relevant data from literature and FE simulations

Before introducing the FE simulations, Fig. 6 compares N_γ values from the circular plate centrifuge tests with equivalent experimental values in the literature (at approximately similar relative densities), where the (prototype) diameter is larger than 0.15 m. Overall the data are fairly consistent and exhibit the expected increase in N_γ with depth (and hence stress level) and with relative density. There is some scatter in the data (particularly in the Giampa et al. (2017) results in dense sand) and the Tagaya et al. (1988) data N_γ values are slightly lower, which is considered to be due to the lower $\phi = 35.1^\circ$ for this sand (Ottawa sand) as reported in Tagaya et al. (1988).

Comparison between the experimental and numerical results

The measured and simulated results from strip and circular anchors in UWA silica sand are summarised as N_γ values in Fig. 7 (dense sand) and Fig. 8 (loose sand). Simulated results for B (or D) = 1 m only are included in these figures to enable direct comparison with the experimental results. Data from tests on rectangular plates are also included, with the measured N_γ adjusted by a shape factor (S_f) as per the expression developed by Dickin (1988) and expressed as:

$$S_f = 1 - \frac{jB}{3LH}(6B - 7H) \quad (27a)$$

where j was found by Dickin (1988) to be 1.0 for $R_D = 76\%$ and 0.4 for $R_D = 33\%$ in Erith sand. To account for the slightly different R_D values in the experiments reported here, the value of j in Eq. (27a) was calculated by linearly interpolating between the limits 0.4 and 1.0 for $R_D = 33\%$ and 76% respectively, as per the following expression:

$$j = 0.0132 R_D(\%) - 0.013 \quad (27b)$$

The numerical results show that the dependence of N_γ on H/B is quasi-linear for strip anchors and non-linear for circular anchors. For strip anchors in dense sand ($R_D = 70\%$, Fig. 7(a)), the simulated and experimental results agree within an average margin of 8.9% for $H/B \leq 3$, increasing to an average under-prediction of 12.5% at H/B

= 4. The under prediction is partly because the simulations were for $R_D = 70\%$, whereas the sample at $H/B = 4$ was at $R_D = 76\%$, such that the dilation potential would have been lower in the numerical simulations than in the centrifuge tests. An additional numerical simulation adopting $R_D = 76\%$ reduced the under prediction slightly to 9.1%. Agreement between the numerical simulations and the experiments is higher for the circular plates at $R_D = 70\%$ (Fig. 7(b)), with a maximum difference in N_γ of 14%. Additional comparisons are provided in Fig. 7(c) for a circular plate ($D = 0.4$ m, $t = 0.04$ m), where the experiments (reported in Hao et al. 2018) considered both circular and helical plates¹ in the same sand but at $R_D = 85 - 90\%$ and at a centrifuge acceleration of 20g. Similar to the comparison on Fig. 7(b), the numerical and experiment N_γ values are within 7%.

Corresponding comparisons for loose sand with $D = 1$ m are shown in Fig. 8, where the agreement is slightly poorer, with the numerical simulations over predicting the experimental N_γ values by up to 66% and 44% for circular and strip anchors respectively, with an average disparity of 46% (circular anchors) and 17% (strip anchors). Extending the comparisons to all the centrifuge test data on loose sand (at different stress levels), the average over prediction is about 51% for circular anchors and 23% for strip anchors. This discrepancy could be partly attributed to the open cone yield surface in the FE soil model that is unable to simulate plastic strains with increase in mean stress levels under constant deviatoric stress ratios (i.e. in compression dominated loading) and partly to the uncertainty in the choice of K_0 for the numerical analyses. A few simulations were repeated using a reduced K_0 of 0.4, as obtained using the original Jaky formulae reported in Mesri and Hayat (1993), instead of $K_0 = 0.5$ (i.e. as was adopted initially). The lower K_0 produces a twofold effect: firstly, it reduces p' in the domain and secondly, it affects the initial distance between the yield surface axis and the bounding surface, causing a change in the hardening modulus. A few numerical simulations for $R_D = 30\%$ and 70% and adopting both $K_0 = 0.4$ and 0.5 are provided in Fig. 9(a) and Fig. 9(b) for strip anchors and circular anchors respectively. The lower K_0 results in a lower anchor capacity by a margin that lies between 2% and 5%, reducing slightly the disparity in the numerically and experimentally determined N_γ values.

Analytically determined N_γ values calculated using the limit equilibrium solutions of White et al. (2008) for strip anchors and Giampa et al. (2017) for circular anchors are shown on Fig. 7 and Fig. 8, selected as they provide a simplified, hand-calculable method to account for stress level dependent ϕ , ψ_d and non-associated flow. Although the two methods differ slightly in the treatment of the mobilised shear resistance (White et al. (2008) assumes constancy of normal stress on slip planes whereas Giampa et al. (2017) assumes a ϕ and ψ_d dependent

¹ Hao et al. (2018) concluded that there was no discernible difference in the uplift capacity of helical and circular plates

shear stress on slip planes), they account for effects of density and stress in uplift capacity problems through the use of element-level correlations of friction and dilation angles with relative density and stress level (Bolton 1986, Chakraborty and Salgado 2010). The LE solutions produce higher N_y values than the finite element simulations in dense sand, and are in slightly poorer agreement with the experimental data. At a relative density, $R_D = 70\%$, the LE solution and FE simulations are in good agreement for circular anchors, whereas for strip anchors the LE solution results in higher N_y values than the finite element simulations. This indicates that the treatment of normal stresses on slip plane is handled more appropriately by Giampa et al. (2017) than by White et al. (2008), consistent with arguments by Smith (2012). When relative density increases to $R_D = 85\%$ (circular anchors, Fig. 7(c)) the FE simulations and the LE solution diverge, with the LE solution resulting in higher N_y values that are in slightly poorer agreement with the measurements than the FE simulations. This suggests that, for potential use in progressive failure problems, there are shortcomings associated with direct use of Bolton's correlations (Bolton 1986, 1987), as they may prescribe a stronger increase in ϕ and ψ_d with R_D than is appropriate. At low relative densities ($R_D = 30\%$, Fig. 8) the LE solution and the FE simulations are in close agreement, presumably as ψ_d would be close to zero in both approaches.

Deformation and shear strain contours at peak capacity for strip and circular anchors

Fig. 10 shows contours of normalised incremental octahedral plastic shear strain ($\Delta\gamma_{oct}^p/\Delta\gamma_{oct_max}^p$) together with normalised soil displacement (δ_{soil}/δ , where δ and δ_{soil} are anchor and soil displacement respectively) at peak capacity for a strip anchor with $B = 2$ m at $H/B = 2$ and 4, and at relative densities of $R_D = 30\%$ and 85%. The failure mechanism observed from the displacement contours (in red dashed lines) resembles those observed in model tests on shallowly buried pipes in sand (Cheuk et al. 2008), involving an inverted trapezoidal block bounded by distributed shear zones curving outwards and widening towards the soil surface, with no observable movements beneath the plate. The displacement field becomes wider as the relative density increases and as the stress level reduces (i.e. at shallower depths), consistent with the higher dilation angle that would apply to such conditions. Fig. 10 also shows for a strip anchor at $H/B = 2$, vertical displacement of the soil from the plate level to the soil surface is similar to the anchor displacement ($\delta_{soil}/\delta > 0.9$), whereas for a circular plate at the same embedment depth (Fig. 11) vertical displacement reduces with height above the plate, reaching $\delta_{soil}/\delta = 0.5$ and 0.8 at the soil surface for $R_D = 30\%$ and 85% respectively. The lower magnitude of soil displacement at shallow depths observed for the circular anchor is indicative of the lower kinematic constraint associated with the three-dimensional failure mechanism for this axisymmetric problem. Hence, the 'rigid block' mechanism appears less

applicable to circular anchors than to strip anchors, although as the strip anchor embedment depth increases to $H/B = 4$, the magnitude of soil displacement also reduces close to the soil surface (to $\delta_{soil}/\delta = 0.43$ and 0.75 for $R_D = 30\%$ and 85% respectively; Fig. 10(c) and Fig. 10 (d)).

The inclination of the intense plastic shear strain bands (measured to the vertical) for strip anchors indicates the mobilised peak dilation angle, which is approximately $\psi_d = 6^\circ$ and 17° for $R_D = 30\%$ and 85% respectively at $H/B = 2$, reducing to $\psi_d = 5^\circ$ and 15° at $H/B = 4$. The lower kinematic restraint for circular anchors results in shear strain band inclinations that are slightly lower at around 2° and 15° respectively for $R_D = 30\%$ and 85% at $H/D = 2$, and serve as an indication, rather than a measure, of the mobilised dilation angle. However, both mechanisms portray that the shear bands do not extend fully to the soil surface, particularly at deeper depths (see Fig. 10(c,d)), which implies that shear resistance may not be fully mobilised along the entire length of the slip plane. Fig. 10 and Fig 11 also show that the orientation of the zone of intense shearing is remarkably different from the deforming curved soil bands (shown by the dashed lines), and more so as plate embedment depth increases.

Variation of friction angle (ϕ) in the domain

Fig. 12(a) shows contours of friction angle ($\phi = \sin^{-1}(\frac{\sigma_1 - \sigma_3}{\sigma_1 + \sigma_3})$) at peak capacity for a strip anchor with $B = 2$ m at $H/B = 4$ and in sand of relative density, $R_D = 30\%$ and 85% . The numerical simulations show that the value of ϕ mobilised in a rectangular block of soil extending a distance $2B$ above the strip anchor is relatively constant and is in the range $\phi = 29^\circ$ to 36° for $R_D = 30\%$ and $\phi = 34^\circ$ and 41° for $R_D = 85\%$. Compared with Fig. 10, this rectangular block corresponds to the zone of soil moving at approximately the same velocity as the anchor (i.e. attaining the same total displacement). Concentrations of contour lines at higher ϕ values occur in shear zones adjacent to this rectangular block, at approximately $\phi = 38^\circ$ for $R_D = 30\%$ and $\phi = 47^\circ$ for $R_D = 85\%$. The higher ϕ in the shear bands is due to a combination of change in Lode angle (θ) of the loading direction (creating a stress anisotropy) and non-normal loading with respect to the fabric (creating a fabric anisotropy) captured in the FE model. Therefore, this observation of distinct banding is markedly different from limit analysis studies by Khatri and Kumar (2011), which did not explicitly account for loading and fabric anisotropy. There is also a higher ϕ mobilised at shallow depths on account of the lower stresses.

It is also instructive to examine the mobilised ϕ along the slip planes inclined at an angle of dilation as predicted using the White et al. (2008) LE solution. As previously shown in Fig. 10, the FE simulations result in $\psi_d = 15^\circ$ and 5° for $R_D = 85\%$ and $R_D = 30\%$ respectively, whereas Bolton's (1986) correlations result in $\psi_d = 21.4^\circ$ and 3.5° for $R_D = 85\%$ and $R_D = 30\%$ respectively (assuming $p' = \sigma'_{vo}$ as suggested in White et al. 2008).

ψ_d values from the numerical simulations (determined at the centroid of each element) along a slip plane inclined at the LE ψ_d values (as indicated by the dashed lines in Fig. 12(a)) are plotted in Fig. 12(b) with increasing distance (z_l/B along the slip plane) from the anchor. The FE results indicate that, even in the intense shearing zone close to the anchor (say $z_l/B < 2$), ϕ varies from 40° to 48° for the dense case ($R_D = 85\%$) and from 36° to 39° for the loose case ($R_D = 30\%$) on account of a greater degree of progressive failure in the domain. Also shown in Fig. 12(b) are the LE peak friction angles determined using Bolton's correlations, that would result in $\phi = 35^\circ$ for $R_D = 30\%$ and 49° for $R_D = 85\%$. Evidently, there appears to be a higher average variation in mobilised ϕ between the LE approach and the current FE simulations for the dense sand by a margin of $\sim 6^\circ$, but by only about 1.5° for the loose sand. This highlights clearly why a LE method relying on a single lumped value of ϕ is ill-suited for calculating uplift capacity in dense sand.

Behaviour of plate anchors at different stress levels

The centrifuge tests were conducted using different anchor geometries at different stress levels (Table 5 and Table 6), with the resulting N_γ values summarised in Fig. 13. At the anchor embedment depth, a variation in σ'_{v0} from 18 and 130 kPa was obtained by varying the acceleration level in the centrifuge, such that the anchor dimension (at prototype scale) varied by a factor of 3.5 (from B or $D = 0.6$ to 2 m). The data at low relative density ($R_D \sim 40\%$) show less than 5% variation in N_γ across the different stress levels and anchor geometries considered, presumably because the mobilised dilation angles would be low in loose sand, such that the variation in ϕ across different regions in the influence zone under progressive shearing is not significant. In dense sand ($R_D \sim 75\%$), the stress level effect appears to be slightly higher if anchor tests at similar embedment levels are compared, with variations in N_γ of up to approximately 10% and 12% for circular and rectangular anchors respectively. Also included in Fig. 13 are data from single gravity tests on circular and rectangular plates in the same sand (Hao et al. 2015 and Chow et al. 2018), where $\sigma'_{v0} (< 1.5 \text{ kPa})$ at the plate embedment depth is two orders of magnitude lower than in the centrifuge tests. In loose sand N_γ values from these single gravity tests are higher than those measured in the centrifuge tests, by a margin of 32% (rectangular plates) and 37% (circular plates), due to the well-known higher dilation potential at low stress levels. The margin of difference between the 1g and centrifuge tests reduces to $\sim 11\%$ for circular plates in dense sand. This is lower than average differences reported in Tagaya et al. (1988) from a combination of 1g and centrifuge tests, where the average N_γ reduction was 30% and 28% at $H/D = 2.37$ and 4 respectively. However, taken together, the experimental data indicate that N_γ measured in 1g tests (at very low stress levels) is higher than those measured in centrifuge experiments (at more realistic stress

levels). This apparent scatter in N_y at the same embedment depth can be reduced by simultaneously considering stress level and relative density using a relative dilatancy term $I_R (= \frac{R_D(\%)}{100} (10 - \ln p') - 1)$ (discussed later in the paper).

Results from numerical simulations at different stress levels (covering B (or D) = 0.6 m to 5 m) are provided in Fig. 14. As with the centrifuge data, the numerically determined N_y values reduce with increasing stress level, by an amount that increases with increasing relative density, and that is higher for circular anchors than strip anchors. For strip anchors N_y reduces by about 6.1% at $R_D = 85\%$ and at $H/B = 4$ as B increases from 0.6 to 5 m compared to a reduction that is within 1.5% at $R_D = 30\%$, broadly consistent with the reduction in N_y observed in the centrifuge tests on strip anchors. Stress level effects are higher in the numerical simulations of circular anchors in dense sand ($R_D = 85\%$), with a reduction in N_y of 24% at $H/D = 3$ as D increases from 0.6 to 5 m, compared to a reduction of only 6.2% for $R_D = 30\%$.

Fig. 14 also shows corresponding results from analytical LE solutions from White et al. (2008) for strip anchors ($B = 1$ and 5 m) and Giampa et al. (2017) for circular anchors ($D = 1$ and 5 m), which rely on element level correlations for ϕ and ψ_d . The evidence in Fig. 14 suggests that the LE methods would be in good agreement with the FE simulations at lower embedment ratios, where the extent of the failing soil mass remains relatively small and the degree of progressive failure is low. However, the point of contrast is that the LE approaches predict a much higher capacity reduction with increasing stress level than both the FE simulations and the experiments. For example, the maximum change in the LE determined N_y values for strip anchors is 22.6% at $R_D = 85\%$ at $H/B = 4$ (Fig. 14(d)), increasing to 28% for circular anchors at $H/D = 3$. This higher reduction in N_y in the LE methods is due to the over-simplistic assumption that the same mobilised ϕ applies along the shear surfaces at the point of peak anchor capacity, whereas the FE approach allows the mechanism to develop progressively.

Modified limit equilibrium method for anchor uplift capacity in sand

Having demonstrated the performance of the FE model, this final section synthesises the FE results within a modified limit equilibrium method that can be used to compute plate anchor capacity as an alternative to running additional, and computationally intensive, FE simulations.

Assuming an inverted trapezoidal block mechanism for strip anchors and pipelines and separately accounting for the resistance due to soil weight and shearing along the inclined slip planes (White et al. 2008), the

numerical results from the plane strain FE simulations can be summarised and fitted by an expression for strip anchor vertical capacity in sand (e.g. White et al. 2008), as:

$$N_\gamma = 1 + \frac{H}{B} F_{u,ps} \quad (28a)$$

where $F_{u,ps}$ is a uplift factor in plane strain depending on stress level and relative density. Such an approach inherently considers the entire trapezoidal soil block above the plate to be in a state of failure. In order to implement such an approach, $F_{u,ps}$ was back analysed from the numerical simulations. Although the numerical simulations (e.g. Fig.10) show that the shear zones do not always extend to the soil surface (i.e. as plate embedment increases and R_D decreases), so that not all locations along the shear zone are at peak failure as the plate anchor capacity maximises, the back analysis accommodates these simplifications without a compromise on accuracy by incorporating lower $F_{u,ps}$ values than prescribed using LE solutions. The FE simulations show that the mean stress at peak capacity (p'_f) in the influence zone for strip anchors can be approximated as:

$$p'_f = \sigma'_{v0} (0.25 H/B + 0.5) \quad (28b)$$

where σ'_{v0} is the initial vertical effective stress. The resulting I_R values corresponding to each simulation can then be obtained using the p'_f values as per Eqn. (28b). $F_{u,ps}$ values from the FE simulations are plotted against the corresponding I_R in Fig. 15. The relationship is evidently linear, and can be fitted by:

$$F_{u,ps} = 0.43 + 0.052 I_R \quad (28c)$$

The relative merit of Eqn. 28 (a-c) is examined in Fig. 16, which shows the ratio of calculated to measured N_γ values for a database of 105 uplift tests on strip anchors and pipelines at different embedment depths (although all considered 'shallow') in sands of varying densities (see Table 7). It is worth noting that the limits of $0 \leq I_R \leq 4$ proposed in Bolton (1986) were not imposed in Eqn. (28), based on evidence reported in Fannin et al. (2005). In addition, the measured N_γ values for pipelines were reduced by $\pi D/8H$ (White et al. 2008), to account for the difference in the pipeline and anchor geometries, thus allowing the entire database to be compared with results from Eqn. (28) without any further adjustments. The data, which have been separated into loose ($R_D < 40\%$) and dense ($R_D > 40\%$) groups, are predicted well by Eqn. (28), with a mean bias (ratio of predicted to measured N_γ) for strip anchors/pipelines of 0.93 and a COV of 0.13, lower than the COV = 0.16 using the White et al. (2008) LE method. No particular bias is evident between predictions for pipelines and anchors, although the predictions for the Dickin (1988) dataset of strip anchors in Erith sand are poorer (e.g. see Fig. 16(c) where the Erith sand

data plot at $R_D = 76\%$, or Fig. 16(d), where the Erith sand data are under predicted and plot between $\sigma'_{v0} = 33$ and 128 kPa), which is considered to be due to the high friction angles and dilating potential of this sand, rather than an inherent difference in the response of a pipeline and strip anchor under uplift.

The limit of $0 \leq I_R \leq 4$ applies in the White et al. (2008) LE method, such that dense sand data at low p' levels (having $I_R > 4$) in the database are capped at $I_R = 4$ in the LE solution. An immediate consequence of this is that the LE method would result in the same N_γ values for highly dilative conditions associated with $I_R > 4$. Fig. 16 shows that the simplified approach, which reflect the results from sophisticated FE simulations, lead to comparable predictions as the LE solution for $I_R < 3$ and slightly conservative estimates of capacities for $I_R > 3$.

Taking the same assumption of a rigid block failure mechanism for a circular anchor (see Giampa et al. 2017) leads to:

$$N_\gamma = 1 + \frac{H}{D} F_{u_{as1}} + \left(\frac{H}{D}\right)^2 F_{u_{as2}} \quad (29a)$$

where $F_{u_{as1}}$ and $F_{u_{as2}}$ are uplift factors that are dependent on I_R . $F_{u_{as1}}$ and $F_{u_{as2}}$ were back analysed from the FE simulations of circular anchors, with p'_f taken as:

$$p'_f = 1.1 \sigma'_{v0} \left(\frac{H}{D}\right) \quad (29b)$$

leading to the following expressions:

$$F_{u_{as1}} = 1.32 + 0.03 I_R \quad (29c)$$

$$F_{u_{as2}} = 0.32 I_R^{0.3} \quad (29d)$$

The performance of Eqn. (29) is examined in Fig. 17, which summarises the ratio of calculated to measured N_γ for a database of 56 tests (from four studies) on circular plate (or helix) anchors in different sands of varying densities and at embedment depths up to $H/D < 6$ (see Table 7). The mean of the ratio of predicted to measured N_γ values is 0.91 with a COV of 0.19, significantly lower than the COV of 0.29 obtained using the Giampa et al (2017) LE method. Although the Giampa et al. (2017) LE method for circular anchors appears to perform less well than the White et al. (2008) LE method for strip anchors (or pipelines), the treatment of shear stresses on the slip planes differs in the two approaches, so that the former should not be viewed as an axisymmetric equivalent of the latter and insights regarding the appropriateness of each approach cannot be drawn from the comparisons with predictions obtained using Eqns. 28 and 29. Fig. 17 indicates that Eqn. (29) does not lead to any evident bias

with relative density, embedment depth or stress level, unlike the LE method, which significantly overpredicts capacities at higher relative densities associated with $I_R > 3.5$ or at higher stress levels.

In summary, adopting the simplified assumption of a rigid block mechanism for shallowly embedded plate anchors, together with uplift factors that reflect progressive failure along slip planes leads to better overall estimates of anchor capacity than existing LE methods.

Conclusions

The capacity of vertically loaded horizontal plate anchors at shallow embedment in sand has been studied both numerically, using a bounding surface plasticity model, and experimentally, through a series of centrifuge tests. Both the numerical and experimental investigations considered the effects of plate geometry (circular, rectangular and strip), sand densities (in the range $R_D = 30\% - 85\%$), embedment depths (up to H/B and $H/D = 4$) under initial overburden stress levels varying from 18 to 130 kPa. The key findings from this study are as follows:

- The experimental data indicates that N_T for strip and circular anchors increases with embedment ratio, and that the rate of increase is stronger for circular anchors than for strip anchors. Corresponding FE simulations were able to reproduce peak capacity for plates in dense sand within an average margin of $\sim 10\%$, whereas the agreement in loose sand was over-predicted by an average margin of 23%, due mainly to the open cone yield surface in the bounding surface model.
- The numerical displacement contours at peak anchor capacity resembled an inverted trapezoidal block bounded by distributed shear zones curving outwards towards the soil surface, the extent of which was influenced by relative density, embedment ratio and anchor shape.
- The corresponding normalised octahedral plastic shear strain contours mobilised at peak capacity showed inclinations of the shear bands in the range $5^\circ - 6^\circ$ and $15^\circ - 17^\circ$ for $R_D = 30\%$ and 85% respectively. The shear bands do not extend fully to the soil surface, particularly as anchor embedment increases, implying that shear resistance may not be fully mobilised along the entire length of the slip plane.
- The FE simulations show that the mobilised friction angles along the slip planes vary by around 8° in dense sand, but only by about 1.5° in loose sand. This is considered to arise from progressive failure, which implies that methods that assume a fully mobilised friction and dilation angle along slip planes would produce non-conservative estimates of anchor capacity in dense sand, unless the methods are calibrated to account for this.

- Both the experiments and the FE simulations indicate a small reduction in anchor factor with increasing stress level, with a higher stress level dependence observed for circular anchors than for strip anchors. Existing LE methods result in a much higher and unrealistic effect of stress level, owing to the over-simplistic assumption of a uniform mobilised friction angle along the slip planes.
- An analytical solution, based on the same rigid block mechanism assumed in LE methods but encompassing the results from the FE simulations, provides better agreement with a large database of anchor and pipeline tests than existing LE methods, particularly for circular plate anchors. The agreement level could be improved further by treating soil compressibility and the initial stress field in the bounding surface plasticity model more appropriately for loose sand states.

Acknowledgements

This work forms part of the activities of the Centre for Offshore Foundation Systems (COFS), currently supported by the Lloyd's Register Foundation. The Lloyd's Register Foundation invests in science, engineering and technology for public benefit, worldwide. The first author would like to acknowledge the financial support provided through an Australian Government Research Training Program Scholarship. The first author would also like to thank Dong-Xue Hao from Northeast Dianli University of China for making available the anchor test results in UWA silica sand.

List of notation

δ	Anchor displacement
δ_{soil}	Soil displacement
$\Delta\gamma_{oct}^p$	Incremental octahedral plastic shear strain
$\sigma_1, \sigma_2, \sigma_3$	Three major principal stresses
γ'	Effective unit weight of soil
σ'_{vo}	Initial effective overburden stress at anchor level
ϕ_c	Critical state friction angle
ϕ	Soil friction angle
ψ_d	Soil dilation angle
τ_f	Shear stress
θ	Lode angle
ψ	State parameter
A	Area of the plate anchor
B	Plate width (strip and rectangular anchors)

D	Plate diameter (circular anchors)
d_{50}	Median particle size
e	Void ratio
F_{u_ps}	Uplift factor in plane strain conditions
F_{u_as1}, F_{u_as2}	Uplift factor in axisymmetric condition
g	Centrifuge acceleration level
H	Embedment depth of the anchor plate
I_R	Relative dilatancy index
j	Fitting constant
K_0	Coefficient of earth pressure
L	Plate length (strip and rectangular anchors)
N_γ	Anchor factor
p'	Mean effective stress
q_u	Peak anchor capacity
q_c	Cone tip resistance
R_D	Relative density
S_f	Shape factor
t	Thickness of plate anchor
z	Depth
z_l	Distance of soil element from the anchor edge

446

References

- Ansari, Y., Kouretzis, G. and Sloan, S.W. 2018. Development of a prototype for modelling soil–pipe interaction and its application for predicting uplift resistance to buried pipe movements in sand. *Canadian Geotechnical Journal*, 55(10), pp.1451–1474.
- Arthur, J.R.F. and Menzies, B.K. 1972. Inherent Anisotropy in a sand. *Géotechnique*, 22(1), pp.115–128.
- Bolton, M.D. 1986. The strength and dilatancy of sands. *Géotechnique*, 36(1), pp.65–78.
- Chakraborty, T. and Salgado, R. 2010. Dilatancy and Shear Strength of Sand at Low Confining Pressures. *Journal of Geotechnical and Geoenvironmental Engineering*, 136(1), pp.527–532.
- Cheuk, C.Y., White, D.J. and Bolton, M.D. 2008. Uplift Mechanisms of Pipes Buried in Sand. *Journal of Geotechnical and Geoenvironmental Engineering*, 134(2), pp.154–163.
- Chow, S.H. , Le, J., Forsyth, M. and O' Loughlin, C.D. 2018. Capacity of vertical and horizontal plate anchors in

- sand under normal and shear loading. In *International Conference on Physical Modelling in Geotechnics*, pp. 559–564.
- Dafalias, Y.F. and Manzari, M.T. 2004. Simple Plasticity Sand Model Accounting for Fabric Change Effects. *Journal of Engineering Mechanics*, 130(6), pp.622–634.
- Dafalias, Y.F., Papadimitriou, A.G. and Li, X.S. 2004. Sand plasticity model accounting for inherent fabric anisotropy. *Journal of Engineering Mechanics*, 130(11), pp.1319–1333.
- Dickin, E.A. 1994. Uplift resistance of buried pipes in sand. Pdf. *Soils and Foundations*, 34(2), pp.41–48.
- Dickin, E.A. and Laman, M. 2007. Uplift response of strip anchors in cohesionless soil. *Advances in Engineering Software*, 38(8–9), pp.618–625.
- Fannin, R.J., Eliadorani, A. and Wilkinson, J.M.T. 2005. Shear strength of cohesionless soils at low stress. *Géotechnique*, 55(6), pp.467–478.
- Frydman, S. and Shaham, I. 1989. Pullout capacity of slab anchors in sand. *Canadian Geotechnical Journal*, 26(3), pp.385–400.
- Giampa, J., Bradshaw, A. and Schneider, J. 2017. Influence of Dilation Angle on Drained Shallow Circular Anchor Uplift Capacity. *International Journal of Geomechanics*, 17(2), p.4016056.
- Giampa, J.R., Bradshaw, A.S., Gerkus, G., Gilbert, R.B., Gavin, K.G. and Sivakumar, V. 2018. The effect of shape on the pullout capacity of shallow plate anchors in sand. *Géotechnique*, pp.1–9.
- Al Hakeem, N. and Aubeny, C. 2019. Numerical Investigation of Uplift Behavior of Circular Plate Anchors in Uniform Sand. *Journal of Geotechnical and Geoenvironmental Engineering*, 145(9), p.04019039.
- Hao, D., Wang, D., O’Loughlin, C.D. and Gaudin, C. 2018. Tensile monotonic capacity of helical anchors in sand: interaction between helices. *Canadian Geotechnical Journal*, 3483, pp.1–33.
- Hao, D., Fu, S. and Rong, C. 2014. Numerical Analysis of Uplift Capacity of Circular Plate Anchor in Sand. *Journal of geotechnical engineering*, 19, pp.18947–18961.
- Hao, D.X., Fu, S., Chen, R., Zhang, Y. and Hou, L. 2015. Experimental investigation of uplift behavior of anchors and estimation of uplift capacity in sands. *Chinese Journal of Geotechnical Engineering*, 37(11), pp.2101–2106.

- Ilamparuthi, K., Dickin, E.A. and Muthukrisnaiah, K. 2002. Experimental investigation of the uplift behaviour of circular plate anchors embedded in sand. *Canadian Geotechnical Journal*, 39, pp.648–664.
- Khatri, V.N. and Kumar, J. 2011. Effect of anchor width on pullout capacity of strip anchors in sand. *Canadian Geotechnical Journal*, 48(3), pp.511–517.
- Li, X.S. and Dafalias, Y.F. 2012. Anisotropic Critical State Theory: Role of Fabric. *Journal of Engineering Mechanics*, 138(3), pp.263–275.
- Li, X.S. and Wang, Y. 1998. Linear Representation of Steady-State Line for Sand. *Journal of Geotechnical and Geoenvironmental Engineering*, 124(12), pp.1215–1217.
- Liu, J.Y., Liu, M.L. and Zhu, Z.D. 2012. Sand Deformation around an Uplift Plate Anchor. *Journal of Geotechnical and Geoenvironmental Engineering*, 138(6), pp.728–737.
- Loukidis, D. and Salgado, R. 2009. Modeling sand response using two-surface plasticity. *Computers and Geotechnics*, 36(1–2), pp.166–186.
- Merifield, R.S. and Sloan, S.W. 2006. The ultimate pullout capacity of anchors in frictional soils. *Canadian Geotechnical Journal*, 43(8), pp.852–868.
- Merifield, R.S., Lyamin, A.V. and Sloan, S.W. 2006. Three-dimensional lower bound solutions for stability of plate anchors in sand. *Geotechnique*, 56(2), pp.123–132.
- Mesri, G. and Hayat, T.M. 1993. The coefficient of earth pressure at rest: Discussion. *Canadian Geotechnical Journal*, 30(5), pp.647–666.
- Murff, J. D., Randolph, M., Elkhatab, S., Kolk, H.J., Ruinen, R., Storm, P.J. and Thorne, C. 2005. Vertically loaded plate anchors for deepwater applications. In *International symposium on Frontiers of Offshors Geotechnics, Perth*. pp. 31–48.
- Murray, E.J. and Geddes, J.D. 1987. Uplift of anchor plates in sand. *ASCE Journal of geotechnical engineering*, 113(3), pp.202–215.
- O’Loughlin, C.D. and Barron, B. 2012. Capacity and keying response of plate anchors in sand. *7th International Conference Offshore Site Investigation and Geotechnics*, pp.649–655.
- O’Loughlin, C.D., Neubecker, S.R. and Gaudin, C. 2018. Anchoring Systems: Anchor Types, Installation and

- Design. In *Encyclopaedia of Marine and Offshore Engineering*, Wiley.
- Paikowsky, S.G., Player, C.M. and Connors, P.J. 1995. A dual interface apparatus for testing unrestricted friction of a soil along solid surfaces. *Geotechnical Testing Journal*, 18(2), pp.168–193.
- Papadimitriou, A.G., Dafalias, Y.F. and Yoshimine, M. 2005. Plasticity modelling of the effect of sample preparation method on sand response. *Soils and Foundations*, 45(2), pp.109–123.
- Petalas, A.L., Dafalias, Y.F. and Papadimitriou, A.G. 2019. SANISAND-FN: An evolving fabric-based sand model accounting for stress principal axes rotation. *International Journal for Numerical and Analytical Methods in Geomechanics*, 43(1), pp.97–123.
- Rasulo, M.P., Schneider, J.A., Newgard, J.T. and Aubeny, C.P. 2017. Transition depths for deep circular anchors in saturated sand. *Proceedings of the 8th International conference of Offshore Site Investigation Geotechnics*. pp. 987–994.
- Rowe, R.K. 1978. *Soil structure interaction analysis and its application to the prediction of anchor plate behaviour.*, PhD thesis, University of Sydney, Sydney, NSW, Australia
- Rowe, R.K. and Davis, E.H. 1982. The behaviour of plate anchors in sand. *Geotechnique*, 32(1), pp.25–41.
- Roy, A., Chow, S.H., O’Loughlin, C.D. and Randolph, M.F. 2019. Effect of stress history and shallow embedment on centrifuge cone penetration tests in sands, *Proceedings of the 38th International Conference on Offshore Mechanics and Arctic Engineering*, Glasgow
- Roy, A., Chow, S.H., O’Loughlin, C.D., Randolph, M.F. and Whyte, S. 2020. Use of a bounding surface model in predicting element tests and capacity in simple boundary value problems. *Canadian Geotechnical Journal*, doi.org/10.1139/cgj-2019-0841
- Sheng, D., Sloan, S.W. and Yu, H.S. 2000. Aspects of finite element implementation of critical state models. *Computational Mechanics*, 26(2), pp.185–196.
- Sloan, S.W., Abbo, A.J. and Sheng, D. 2001. Refined explicit integration of elastoplastic models with automatic error control. *Engineering Computations*, 18(1/2), pp.121–194.
- Smith, C.C. 2012. Limit loads for a shallow anchor/ trapdoor embedded in a non-associative Coulomb soil. *Geotechnique*, 62 (7), 563-571.

- Tagaya, K., Scott, R.F. and Aboshi, H. 1988. Scale effects in anchor pullout test by centrifugal technique. *Soils and Foundations*, 28(3).
- Trautmann, C.H., O'Rourke, T.D. and Kulhawy, F.H. 1985. Uplift force-Displacement response of Buried pipe. *Journal of Geo- technical and Geoenvironmental Engineering*, 111(9), pp.1061–1076.
- Vaid, Y.P., Chung, E.K.F. and Kuerbis, R.H. 1990. Stress path and steady state. *Canadian Geotechnical Journal*, 27(1), pp.1–7.
- Vermeer, P.A. and Sutjiadi, W. 1985. The uplift resistance of shallow embedded anchors. In *Proc., of 11th Int. Conf. of Soil Mechanics and Foundation Engineering, Balkema, Rotterdam, Netherlands*. pp. 1635–1638.
- White, D.J., Teh, K.L., Leung, C.F. and Chow, Y.K. 2008. A comparison of the bearing capacity of flat and conical circular foundations on sand. *Géotechnique*, 58(10), pp.781–792.
- White, D.J., Cheuk, C.Y. and Bolton, M.D. 2008. The uplift resistance of pipes and plate anchors buried in sand. *Géotechnique*, 58(10), pp.771–779.

Table captions

Table 1: Governing equations for the bounding surface model

Table 2: Physical properties of UWA silica sand

Table 3 : Model parameters for UWA silica sand

Table 4: Details of the plate anchor models used in the experiments

Table 5: Test program and results in dense sand

Table 6: Test program and results in loose sand

Table 7 : Database of anchor and pipeline experiments

Figure captions

Fig. 1: (a) problem definition, (b) failure mechanism with vertical slip surface and (c) failure mechanism with an inclined slip surface

Fig. 2 : Comparison of measured and simulated responses in UWA sand: (a) drained triaxial compression tests (b) undrained triaxial extension tests

Fig. 3 : Mesh details along with boundary conditions used in the strip anchor simulations

Fig. 4 : Experimental details: (a) testing arrangement, (b) plate anchor dimensions, and (c) model plates used in the tests

Fig. 5: Measured cone tip resistance profiles before anchor testing in: (a) loose samples and (b) dense samples

Fig. 6: Comparison of N_γ values measured in the current experiments on circular anchors with previously reported experimental values in: (a) dense sand (b) loose sand

Fig. 7 : Comparison of measured and simulated anchor capacities in dense sand for: (a) strip anchors at $R_D \sim 70\%$, (b) circular anchors at $R_D \sim 70\%$ and (c) circular anchors at $R_D \sim 85\%$

Fig. 8 : Comparison of measured and simulated anchor capacities in loose sand for: (a) strip anchors at $R_D = 30\%$ and (b) circular anchors at $R_D = 30\%$

Fig. 9 : Influence of different K_0 values in the simulated FE responses in: (a) strip anchors and (b) circular anchors

Fig. 10 : Normalised shear strain contours ($\Delta\gamma_{oct}^p / \Delta\gamma_{oct_max}^p$) contrasted against normalised deformation contours (δ / δ_{soil}) at peak anchor capacity for strip anchors ($B = 2$ m): (a) $H/B = 2$, $R_D = 30\%$ (b) $H/B = 2$, $R_D = 85\%$ (c) $H/B = 4$, $R_D = 30\%$ (d) $H/B = 4$, $R_D = 85\%$

Fig. 11 : Normalised shear strain contours ($\Delta\gamma_{oct}^p / \Delta\gamma_{oct_max}^p$) contrasted against normalised deformation contours (δ / δ_{soil}) at peak anchor capacity for circular anchors ($H/D = 2$, $D = 2$ m): (a) $R_D = 30\%$ and (b) $R_D = 85\%$

Fig. 12 : Variation in mobilised friction angle at peak anchor capacity for strip anchors ($B = 2$ m, $H/B = 4$): (a) entire domain for $R_D = 85\%$ and $R_D = 30\%$, (b) along slip planes inclined at the angle of dilation from the White et al. (2008) LE method

Fig. 13 : Measured N_γ values from anchor tests in UWA silica sand with different plate dimensions: (a) circular anchors, (b) rectangular anchors and (c) strip anchors

Fig. 14: Anchor capacity factors from FE and LE at different relative densities and initial stress levels

Fig. 15 : Fitting of F_{u-ps} from the FE simulations in strip anchors

Fig. 16 : Comparison between predicted and measured N_γ for plane strain uplift for (a) variation in I_R (b) variation in H/B (c) variation in R_D (d) variation in initial vertical stress

Fig. 17 : Comparison between predicted and measured N_γ for circular anchors for (a) variation in I_R (b) variation in H/D (c) variation in R_D (d) variation in initial vertical stress

Draft

Table 1: Governing equations for the bounding surface model

Parameters	Description	Governing equations (Eqn. No)	Notes/Reference
e_o	Controls the intercept of the CSL at very low mean stress levels in $e - (p'/P_a)^\xi$ space	$e_c = e_o - \lambda_c \left(p' / P_a \right)^\xi \quad (1)$ $\psi = (e - e_c) \quad (2)$	Li and Wang (1998), Dafalias and Manzari (2004)
λ_c	Controls the slope of the CSL in $e - (p'/P_a)^\xi$ space		
ξ	Influences the linearisation of the CSL with p'		
M	Controls critical state stress ratios in triaxial compression		
c_l	Controls critical state stress ratio in triaxial extension		
G_o	Elastic shear modulus	$G = G_o p_{at} \frac{(2.97 - e)^2}{(1 + e)} \left(\frac{p'}{P_a} \right)^{1/2} \quad (3)$	Dafalias and Manzari (2004)
ν	Poisson's ratio	$K = G \frac{2(1 + \nu)}{3(1 - 2\nu)} \quad (4)$	
		$d\varepsilon_e^e = ds/2G \quad (5)$	
		$d\varepsilon_v^e = dp/K \quad (6)$	
m	Controls the size of the yield surface	$f = [(\mathbf{r} - \boldsymbol{\alpha}) : (\mathbf{r} - \boldsymbol{\alpha})]^{1/2} - \sqrt{2/3} m = 0 \quad (7)$	Dafalias and Manzari (2004)
n^d, n^b	Influences the mobilised stress ratio at peak friction angle and at phase transformation	$\boldsymbol{\alpha}_\theta^a = \sqrt{\frac{2}{3}} (M_\theta^a - m) \mathbf{n} \quad (a = b, d, c) \quad (8)$ $M_\theta^c = g_1(\theta, c_1) M \quad (9)$ $g_1(\theta, c_1) = \left(\frac{2c_1^4}{((1 + c_1^4) - (1 - c_1^4) \cos 3\theta)} \right)^{1/4} \quad (10)$ $M_\theta^b = [M_\theta^c \exp(-n^b \psi_f)] \quad (11)^*$ $M_\theta^d = [M_\theta^c \exp(n^d \psi_f)] \quad (12)^*$	Dafalias and Manzari (2004), Sheng et al. (2000)
c_h, h_{in}	Plastic modulus constants	$K_p = \frac{2}{3} p' h(\boldsymbol{\alpha}_\theta^b - \boldsymbol{\alpha}) : \mathbf{n} \quad (13)$ $h = \frac{b_o}{(\boldsymbol{\alpha} - \boldsymbol{\alpha}_{in}) : \mathbf{n}} \quad (14)$ $b_o = h_o G_o (1 - c_h e) \left(\frac{p'}{P_a} \right)^{-1/2} \quad (15)$ $h_o = h_{in} f_h \quad (16)^*$	Dafalias et al. (2004)

A_0	Parameter affecting the rate of dilatancy	$d\varepsilon^p = \langle L \rangle \mathbf{R} \quad (17)$ $\frac{dg}{d\sigma} = \mathbf{R} = \mathbf{R}' + \frac{1}{3} D \mathbf{I} = B \mathbf{n} - C \left(\mathbf{n}^2 - \frac{1}{3} \mathbf{I} \right) + \frac{1}{3} D \mathbf{I} \quad (18)$ $B = 1 + \frac{3(1-c_2)}{2c_2} g_2(\theta, c_2) \cos 3\theta,$ $C = 3 \sqrt{\frac{3}{2}} \frac{(1-c_2)}{c_2} g_2(\theta, c_2)$	Dafalias et al.(2004), Loukidis and Salgado (2009)
c_2	Parameter affecting the slope of the plastic potential	$g_2(\theta, c_2) = \frac{2c_2}{(1+c_2)-(1-c_2) \cos 3\theta} \quad (19)$ $D = A_0 (\alpha_0^d - \alpha) : \mathbf{n} \quad (20)$	
a	Parameter controlling the initial fabric	$F_{11} = 0.5(1-a) \quad F_{22} = 0.5(1-a) \quad F_{33} = a \quad (21)$ $F_{ij} = 0 \quad (\text{when } i \neq j)$ $A = g_1(\theta, c_1) \mathbf{F} : \mathbf{n}, \quad (22)$ $A_c = - \left(\frac{1}{c_1} \right) A_e = \sqrt{\frac{3}{2}} \left(a - \frac{1}{3} \right)$ $A_{ratio} = 2 * \frac{A_e - A}{A_e - A_c} \quad (23)$	Dafalias et al.(2004)
b_1, b_2, k	Factors to scale the state parameter and plastic modulus for loading conditions other than triaxial compression	$f = \frac{1}{b_1 + b_2 (A_{ratio})^{b_3}} \quad (24)^*$ $b_3 = \frac{\log(\frac{1-b_1}{b_2})}{\log 2}$ $f_h = f^k \quad (25)^*$ $\psi_f = f \psi \quad (26)^*$	

* Introduced for state parameter scaling approach

Table 2: Physical properties of UWA silica sand

Soil properties	UWA Silica sand
Angularity	Sub-rounded to sub-angular
Maximum void ratio ^a	0.789
Minimum void ratio ^a	0.512
Specific gravity ^b	2.67
Uniformity coefficient (U)	1.73
Mean particle size (d_{50})	0.2 mm

^a Maximum and minimum void ratios calculated as per AS 1289.5.5.1

^b Specific gravity calculated as per AS 1289.3.5.1

Table 3 : Model parameters for UWA silica sand

Parameters	Symbol	Value
Elastic properties	G_0	135
	ν	0.14*
Critical state properties	e_o	0.812
	λ	0.0189
	ζ	0.7
	M	1.296
	c_1	0.7
Yield surface	m	0.05*
Parameter for plastic potential gradient	c_2	0.78*
Parameters influencing plastic modulus	h_0	7.5
	c_h	1.01
	n^b	2.0
Parameters influencing dilatancy	A_0	0.84
	n^d	3.4
Anisotropy and state parameter scaling parameters	a	0.27
	b_1	2.5
	b_2	-0.833*
	k	1.5

*Assumed

Table 4: Details of the plate anchor models used in the experiments

Anchor code	Anchor geometry	Material	Width, B or diameter, D (mm)	Plate length, L (mm)	Anchor thickness, t (mm)	Plate mass (g)
ST_1	Strip	Steel	20	160	5	152.26
ST_2	Strip	Steel	20	160	5	152.79
ST_3	Strip	Steel	20	160	5	151.72
R_1	Rectangular	Aluminium	20	40	4	39.13
R_2	Rectangular	Aluminium	20	40	4	38.86
R_3	Rectangular	Aluminium	20	40	4	38.88
R_4	Rectangular	Steel	30	60	5	98.07
R_5	Rectangular	Steel	30	60	5	99.76
C_1	Circular	Steel	30		3	47.27
C_2	Circular	Steel	30		3	47.1
C_3	Circular	Steel	30		3	44.82

Table 5: Test program and results in dense sand

Sample no.	Relative density, R_D (%)	Unit weight, γ' (kN/m ³)	Anchor code	g -level	Embedment ratio, H/B	Peak mobilised anchor capacity, q_u (kPa)	Anchor factor, $N_\gamma = q_u/\gamma'H$
D1	76.72	16.61	ST_3	30	1.95	43.73	2.28
			ST_2	30	1.95	41.01	2.14
			ST_1	50	1.95	69.39	2.18
			R_2	30	2.00	67.42	3.49
			R_3	50	2.00	108.10	3.37
			R_1	100	2.05	222.24	3.38
D2	73.5	16.52	ST_2	30	2.70	65.93	2.51
			ST_3	50	2.70	100.57	2.30
			R_2	30	2.70	96.62	3.73
			R_3	50	2.95	179.19	3.82
			R_1	100	2.68	275.53	3.25
			C_1	33.3	1.80	119.94	4.18
D3	75.28	16.58	C_2	66.6	1.80	195.02	3.43
			ST_1	30	3.95	159.61	4.17
			ST_2	50	3.95	253.20	3.99
			R_3	30	4.00	270.98	7.11
			R_1	50	4.00	401.73	6.34
			R_2	100	4.00	776.96	6.15
D4	75.14	16.57	C_1	33.3	2.70	313.55	7.32
			C_2	66.6	2.70	566.40	6.68
			ST_1	30	3.85	149.96	4.01
			ST_2	50	3.96	230.16	3.60
			R_1	30	3.81	217.58	5.98
			R_3	50	3.95	369.20	5.89
D5*	69.53	16.41	R_2	100	3.85	680.84	5.59
			C_1	33.3	2.53	253.95	6.31
			C_2	66.6	2.57	494.68	6.12
			R_4	20	1.80	50.77	2.96
			C_3	20	1.93	78.28	4.33
			R_5	20	3.03	123.29	4.29
D6*	71.1	16.45	C_3	20	2.90	223.65	8.28
			R_4	20	3.77	232.50	6.55

* Samples prepared for inclined loading tests; only vertical uplift tests from these boxes are reported here

Table 6: Test program and results in loose sand

Sample no.	Relative density, R_D (%)	Unit weight, γ' (kN/m ³)	Anchor code	g -level	Embedment ratio, H/B	Peak mobilised anchor capacity, q_u (kPa)	Anchor factor, $N_\gamma = q_u/\gamma'H$
L1	42.8	15.68	ST_2	30	1.75	21.24	1.31
			ST_3	50	1.75	35.80	1.33
			ST_1	100	1.75	67.52	1.26
			R_3	30	1.80	33.05	2.01
			R_2	50	1.80	51.87	1.90
			R_1	100	1.85	105.80	1.90
L2	48.9	15.84	ST_2	30	2.75	40.07	1.56
			ST_1	50	2.75	68.09	1.60
			ST_3	100	2.75	133.29	1.56
			R_1	30	2.8	52.01	1.98
			R_2	50	2.75	118.37	2.82
			R_5	20	1.90	40.03	2.29
			R_4	33.3	1.83	49.40	1.72
			C_1	33.3	1.90	77.25	2.61
L3	45.7	15.76	ST_2	30	3.60	79.26	2.38
			ST_3	50	3.85	138.38	2.35
			ST_1	75	3.70	190.41	2.25
			R_3	30	3.80	135.60	3.93
			R_2	50	3.80	220.65	3.86
			R_1	100	3.73	420.67	3.75
			C_1	33.3	2.53	179.87	4.70
			C_2	66.6	2.53	356.09	4.70
L4*	47.35	15.8	R_4	20	1.83	35.81	2.13
			C_3	20	1.90	40.91	2.39
L5*	47.37	15.79	R_4	20	2.87	86.78	3.33
			C_3	20	2.77	103.88	4.19
L6*	48.67	15.83	R_4	20	4.07	165.28	4.51
			C_3	20	3.90	209.38	6.04

* Samples prepared for inclined loading tests; only vertical uplift tests from these boxes are reported here

Table 7 : Database of anchor and pipeline experiments

Source	Test type	<i>g</i> - level	Plate or pipe dimension, <i>B</i> or <i>D</i> * (mm)	Unit weight, γ' (kN/m ³)	Relative density, <i>R_D</i> (%)	Embedment ratio, <i>H/B</i> or <i>H/D</i>	Relative dilatancy index, <i>I_R</i>
Rowe (1978)	Anchor	1 <i>g</i>	51	14.75 - 15.3	18 – 38	1.0 – 6.0	0.6 – 2.7
Murray and Geddes (1987)	Anchor	1 <i>g</i>	50.8	15.3	42	1.0 – 6.0	2.8 – 3.6
Rowe and Davis (1982)	Anchor	1 <i>g</i>	51	14.75 - 15.3	18 – 38	1.0 – 6.0	1.0 – 2.7
Dickin (1988)	Anchor	40 <i>g</i>	1000	14.24 - 16	33, 76	1.0 – 8.0	0.5 – 4.7
Dickin (1994)	Pipe	40 <i>g</i>	1000	14.24 - 16	33, 76	1.6 – 5.6	0.9 – 4.4
Dickin (1994)	Pipe	1 <i>g</i>	25 – 1000	14.24 - 16	33, 76	3.5	2.8 – 6.1
Trautmann et al. (1985)	Pipe	1 <i>g</i>	102	16.4 - 17.7	36, 81	1.5 – 8.0	0.0 – 5.2
Ansari et al. (2018)	Pipe	1 <i>g</i>	75	15.03 - 16.1	22, 63	1.5 – 4.0	1.2 – 4.1
White et al. (2001)	Pipe	10 <i>g</i>	220	8.25	16 – 70	3.14	0.5 – 5.2
Hao et al. (2018)	Helix, plate	20 <i>g</i>	400	16.87	86	3-6	3.4 – 5.6
Giampa et al.(2017)	Helix	1 <i>g</i>	152	15.2 - 15.6	32 – 45	1.8-5	1.2 – 2.3
Ilamparuthi et al.(2002)	Plate	1 <i>g</i>	100 – 400	15.5 - 17	39 – 74	0.85-5	1.3 – 6.0
Rasulo et al. (2017)	Helix	1 <i>g</i>	50 – 254	15.2- 16.1	32 – 60	1.8-5	1.2 – 3.0

* at prototype scale. Note that all tests except for White et al. (2001) were conducted in dry sands

Fig. 1: (a) problem definition, (b) failure mechanism with vertical slip surface and (c) failure mechanism with an inclined slip surface

Fig. 2 : Comparison of measured and simulated responses in UWA sand: (a) drained triaxial compression tests (b) undrained triaxial extension tests

Fig. 3 : Mesh details along with boundary conditions used in the strip anchor simulations

Fig. 4 : Experimental details: (a) testing arrangement, (b) plate anchor dimensions, and (c) model plates used in the tests

Fig. 5: Measured cone tip resistance profiles before anchor testing in: (a) loose samples and (b) dense samples

(a)

(b)

Fig. 6: Comparison of N_γ values measured in the current experiments on circular anchors with previously reported experimental values in: (a) dense sand (b) loose sand

(a)

(b)

(c)

Fig. 7 : Comparison of measured and simulated anchor capacities in dense sand for: (a) strip anchors at $R_D \sim 70\%$, (b) circular anchors at $R_D \sim 70\%$ and (c) circular anchors at $R_D \sim 85\%$

Fig. 8 : Comparison of measured and simulated anchor capacities in loose sand for: (a) strip anchors at $R_D = 30\%$ and (b) circular anchors at $R_D = 30\%$

Fig. 9 : Influence of different K_0 values in the simulated FE responses in: (a) strip anchors and (b) circular anchors

Fig. 10 : Normalised shear strain contours ($\Delta\gamma_{oct}^p/\Delta\gamma_{oct_max}^p$) contrasted against normalised deformation contours (δ_{soil}/δ) at peak anchor capacity for strip anchors ($B = 2$ m): (a) $H/B = 2, R_D = 30\%$ (b) $H/B = 2, R_D = 85\%$ (c) $H/B = 4, R_D = 30\%$ (d) $H/B = 4, R_D = 85\%$

Fig. 11 : Normalised shear strain contours ($\Delta\gamma^p_{oct}/\Delta\gamma^p_{oct,max}$) contrasted against normalised deformation contours (δ_{soil}/δ) at peak anchor capacity for circular anchors ($H/D = 2$, $D = 2$ m): (a) $R_D = 30\%$ and (b) $R_D = 85\%$

Fig. 12 : Variation in mobilised friction angle at peak anchor capacity for strip anchors ($B = 2$ m, $H/B = 4$): (a) entire domain for $R_D = 85\%$ and $R_D = 30\%$, (b) along slip planes inclined at the angle of dilation from the White et al. (2008) LE method

Fig. 13 : Measured N_γ values from anchor tests in UWA silica sand with different plate dimensions: (a) circular anchors, (b) rectangular anchors and (c) strip anchors

Fig. 14: Anchor capacity factors from FE and LE at different relative densities and initial stress levels

Fig. 15 : Fitting of F_{u-ps} from the FE simulations in strip anchors

Draft

Fig. 16 : Comparison between predicted and measured N_γ for plane strain uplift for (a) variation in I_R (b) variation in H/B (c) variation in R_D (d) variation in initial vertical stress

Fig. 17 : Comparison between predicted and measured N_γ for circular anchors for (a) variation in I_R (b) variation in H/D (c) variation in R_D (d) variation in initial vertical stress

Minerva Access is the Institutional Repository of The University of Melbourne

Author/s:

Roy, A;Chow, SH;O'Loughlin, CD;Randolph, MF

Title:

Towards a simple and reliable method for calculating the uplift capacity of plate anchors in sand

Date:

2021

Citation:

Roy, A., Chow, S. H., O'Loughlin, C. D. & Randolph, M. F. (2021). Towards a simple and reliable method for calculating the uplift capacity of plate anchors in sand. Canadian Geotechnical Journal, 58 (9), <https://doi.org/10.1139/cgj-2020-0280>.

Persistent Link:

<http://hdl.handle.net/11343/251839>