1   **A comparative study of flexibility in water**
2   **allocation in the context of hydrologic**
3   **variability**

4   Hang Zheng¹, Clive Lyle², Zhongjing Wang³

5   *1 Lecturer, State Key Laboratory of Hydro-Science and Engineering, Department*
6   *of Hydraulic and Hydropower Engineering, Tsinghua University, Beijing, 10084,*
7   *CHINA.*

8   E-mail: zhenghang@tsinghua.edu.cn

9   Phone: (86)13810668746

10   Fax: (86)10 67296971

11   *2 Principal Research Fellow, Australia-China Water Resource Research Center,*
12   *the University of Melbourne, Melbourne, Victoria, 3010, AUSTRALIA.*

13   E-mail: cwlyle@gmail.com

14   Phone: (61) 3 9816 3957

15   Fax: (86)10 67296971

16   *3 Professor, State Key Laboratory of Hydro-Science and Engineering,*
17   *Department of Hydraulic and Hydropower Engineering, Tsinghua University,*
18   *Beijing, 10084, CHINA.*

19   E-mail: zj.wang@tsinghua.edu.cn

20   Phone: (86)13501076319

21   Fax: (86)10 67296971

22   Abstract: River flow that is characterized by variability requires commensurate
23   flexibility in allocating water so that water users are able to plan their activities
24   and respond accordingly. An indicator-based assessment method is proposed in
25   this study to evaluate the flexibility of water allocation, based on a concept that a
26   flexible water allocation regime provides greater opportunity for users to freely
27   decide individual water use and leads to more variability and diversity for water
28   consumption among the users. This is demonstrated by using historical water-use
29   data and applying the assessment method in three river basins with different water
30   allocation regimes. These allocation regimes include the seasonal and volumetric
31   water allocation system in the Yellow River of China, duration-based water
32   allocation in Northwestern China, and capacity sharing in southern Queensland in
33   the northern Murray Darling Basin of Australia. Historical water-use variability
34   and diversity are defined and assessed. The result shows that water allocation
35   flexibility varies across the different water entitlement regimes. Duration-based

water allocation, a type of allocation that provides the highest degree of water-use autonomy, is ranked as the most flexible regime. Seasonal water allocation, which has the highest level of centralized regulation, shows the lowest flexibility. The proposed indicator based assessment method would be useful for evaluating the flexibility of policy options for water allocation. This could be helpful for improving the capability of water allocation regimes to cope with the changing environment and improving the effectiveness of water allocation systems.

Key words: water allocation; flexibility; autonomy; assessment.

1 Introduction

Overexploitation of water resources, degradation of river ecosystems, and an increasing number of social conflicts following the unsustainable use of water resources demonstrate the wide gap between the objectives of sustainability and current resource management practices. The management of water resources is a particularly challenging and difficult task, facing continual variability and uncertainty in the availability of water resources posed by climate change (Graddon et al. 2011).

Conventional water supply systems have been traditionally designed in fixed and rigid patterns (Cross 2000). Such designs have led to a supply management that could be easily and simply controlled but with less capacity to accommodate uncertainty and environmental change. A water resource system should be a hybrid dynamic system that can be subjected to continuous operations broken by discrete events when new goals can be defined in the short-term, either to guarantee an efficient use of the upstream water reserves or to enforce security (Faye et al. 2005).

Literature on issues pertaining to flexibility of water resource management has proliferated in recent years. (Grönlund and Määtä 2008; Falkenmark and Rockström 2010; Li and Chang 2011; Teh et al. 2012; Jafarzadegan et al. 2013) Widespread interest in this topic emphasizes the importance of understanding water resource management flexibility. The word “flexible” is used in the English language to describe objects “capable of responding or conforming to changing or new situations”. Flexibility is therefore the property that makes an object “flexible” (Gupta and Buzacott 1989). Water resource systems are argued to be

68 more flexible in the short run as they are able to adjust supply quantities to
69 unexpected demands or inflow changes. Flexibility adds great value to a system
70 because of the advantage of providing the supply process with the ability to
71 modify itself under uncertainty (Marreco and Carpio 2006).

72 According to Cross (2000), flexibility in water supplies enables the informed
73 farmer to choose almost any means of on-farm irrigation practice that best meets
74 the needs of the desired crop, the cost and availability of labor, and other local
75 economic or social situations.. Schlüter and Pahl-Wostl (2007) reported that the
76 diversification of resource use increases the resilience of resource management
77 under the given conditions of a regularly fluctuating inflow. These studies
78 demonstrated that water management flexibility could be enabled by increasing
79 the autonomy and diversity of choices for water users. Numerous water resource
80 management practices for establishing autonomous, self-adaptive, and thus,
81 flexible water governance systems include bottom-to-top decision making
82 systems, water users associations, and water markets (Zheng et al. 2012).

83 Nevertheless, inherent constraints against flexibility in water allocation remain
84 because of competition for water-use brought about by a conventional centralized
85 and bureaucratic management system. Substantial gaps still remain in our
86 knowledge about flexibility in a water-allocation regime, as well as identifying,
87 measuring, and improving it to cope with the changing environment. Related
88 research studies are rare, especially on quantitative methods.

89 This paper proposes a quantitative method to evaluate the flexibility of water
90 allocation regimes in the context of hydrologic variability. The method measures
91 water allocation flexibility through assessing the performance of the allocation
92 regime in promoting variable and diverse water-use among water consumers. If
93 greater variability and diversity of individual water-use are observed under a
94 water allocation regime in a river basin, it follows that there are more autonomy in
95 water use and higher flexibility in water allocation. This concept and method are
96 applied in three different water allocation regimes in China and in Australia. The
97 proposed method is helpful in providing insights on the flexibility of water
98 allocation regimes and valuable to facilitate the institutions' consideration on
99 improving the performance of allocation systems.

100   **2 Method**

101   **2.1 Concept**

102   A concept of flexible water allocation is argued in this study, which is that
103   flexible water allocation provides more water use autonomy and leads to greater
104   variability and diversity of water use among consumers. This concept is
105   established based on literature review. Several arguments for increasing the
106   flexibility of water resources management are catalogued into two groups. The
107   first argues that flexibility in water resources management can be increased by
108   providing water authorities with diversity, real time and optimal solutions as much
109   as possible to assist them in adapting to every possible condition under changing
110   conditions of water availability (Larsen and Gujer 2001; Faye et al. 2005;
111   Marreco and Carpio 2006; Milman and Short 2008; Li and Chang 2011). This can
112   be seen as the “top to bottom” method. The second argues that flexible water
113   resources management can be achieved by providing more opportunities or
114   autonomy to water users so they can choose the solutions that best meet their
115   needs (Gunderson et al. 2006; Wright et al. 2010; Assche et al. 2012; Teh et al.
116   2012). This is recognized as the “bottom to top” method.

117   Due to the inevitable uncertainty and complexity in the real world, providing
118   overall flexible solutions to cope with every possible condition is costly and
119   requires a flexible user community. Water governance authorities are increasingly
120   delegating the power to water users and gain management simplicity and low
121   administrative costs. Water allocation flexibility under the “bottom to top”
122   concept is adopted in the study.

123   **2.2 The quantitative assessment approach**

124   The entropy model which is the suggested as a tool to measure the flexibility
125   (Kumar 1987; Shuiabia et al. 2005) is adopted in this study. The model considers
126   the size of the set of choices available subsequent to any decision as a measure of
127   the inherent flexibility of the decision. A higher number of choices provide
128   greater flexibility. This concept is interestingly captured by “entropy”.

129   In water management systems, water allocation regime interventions are in the
130   form of regulations that change and regulate water users’ access to the available

131 water resource. How water users respond to regulations, such as the consumers'
 132 ability and freedom to use water is influenced by the size of the set of choices
 133 available, which reflects the flexibility of a water allocation regime. Higher
 134 variability and diversity in water consumption among different water users means
 135 more "entropy" in the water management system and reflects greater flexibility in
 136 the allocation system. The historical variability and spatial diversity data of water
 137 use in a river basin under a certain water allocation regime are adopted in this
 138 study to measure water allocation flexibility.

139 The method framework is illustrated in Fig. 1. The water availability in a river
 140 basin varies with time because of runoff variability. The runoff is allocated to
 141 water users according to certain allocation regimes. The water allotment
 142 represents the water use ration in a given hydrologic condition. The water use
 143 ration can be identified through several approaches, such as a volumetric cap for
 144 water withdrawal.

146 **Fig.1 Framework for flexibility assessment on surface water allocation**
 147 **regimes**

148 A flexibility indicator is proposed in this study according to the framework, as
 149 shown in Equation (1).

$$150 \quad F = \frac{CV[W(t)]}{CV[WA(t)]} \cdot \prod_i CV[WU_i(t)] \quad (1)$$

151 where, t is the time step, e.g., year; $CV()$ is the coefficient of variation, which is
 152 defined as the ratio of the standard deviation to the mean; $WU()$ is the surface
 153 water use in the river basin; $WA()$ represents the surface water availability in the
 154 basin; $WU_i()$ is the surface water use of water users i ; i is the order of the water
 155 users; F is the indicator of flexibility; $CV[WU(t)]/CV[WA(t)]$ represents the

variation in water use in the basin per unit change of water availability;
 $CV_i[WU_i(t)]$ reflects the water use variability of water user i ; and
 $CV_i[CV_i[WU_i(t)]]$ represents water-use diversity across all the water users.
 Multiplication is adopted to integrate the water-use variations and diversity to
 form the indicator F of water allocation flexibility. Higher variability and
 diversity of water use in the basin results in a larger indicator F , and represents
 greater flexibility.

2.3 The study areas

Three river basins in China and Australia are adopted as case study areas,
 including the Yellow River Basin (Yellow RB) in China with Seasonal Water
 Allocation (SWA), the St. George region of Queensland of the Murray–Darling
 Basin in Australia with Capacity Sharing (CS) regime, and the Taolai River Basin
 (Taolai RB) in Northwestern China with Duration-based Water Allocation
 (DWA).

Generally, a water-use ration is set for each water user in the water allocation
 process (Wang et al. 2009; Zheng et al. 2011) to ensure that total water use will
 not exceed the water availability of the basin. In SWA, water is allocated as shares
 of the total volume of water releases in a given season. The water that the regions
 have rights to use is then intended to be limited to their allocated seasonal water
 volume. CS regime proposes a system of allocating water property rights to a
 share of the total storage (and hence a share of inflows and losses) which has been
 established in Australia (Dudley and Musgrave 1988; Hughes and Goesch 2009a).
 In this system, each user is allocated a share of the total system storage capacity
 and a share of total inflows and losses (i.e., evaporation and seepage). Users
 independently manage their capacity shares, including carrying over unused water
 between years in the reservoirs according to pre-defined rules. Duration-based
 water allocation originated from a traditional Chinese water allocation system
 about 200 years ago during the Qing dynasty. In the 18th century, an
 administrative water allocation system was established in some arid rivers of
 Northwestern China, in which the water extraction times of upstream and
 downstream users were defined by the river basin authority. This system is still
 being implemented in the Taolai RB. Instead of sharing the seasonal water release
 volume or storage capacity, water is allocated based on the duration or time. Each

189 water user in the river basin is allocated a share of the total number of water
 190 release days within a year, during which they can take water from the river freely
 191 without volumetric or other controls. This type of water allocation is denoted
 192 ‘duration-based water allocation’ in this paper.

193 2.3.1 Yellow River in China and seasonal water allocation

194 Yellow River, the second largest river in China, originates from the Tibetan
 195 Plateau, wanders through the northern semi-arid region, crosses the Loess Plateau,
 196 passes through the Eastern Plain, and finally discharges into the Bohai Gulf (Fig.
 197 2). The main course of the river flows approximately 5,500 km in distance and
 198 accumulates 753,000 km² of drainage area. Approximately 100 million people
 199 live within the basin. (Shao et al. 2009).

200

201 **Fig. 2 the Yellow River basin and the riparian provinces (municipalities)**

202 Note: Data from the National Fundamental Geographic Information System,
 203 China.

204 In 1987, the “Yellow River water allocation scheme” was approved by the
 205 Chinese State Council. The scheme proposed a sharing of water use entitlement
 206 among all riparian provinces and the ecosystem. The long-term mean annual
 207 natural runoff of 58,000 million m³ was divided into two parts: 37,000 million m³
 208 as the maximum water supply capacity for human use (Table 1) and 21,000
 209 million m³ for in-stream sediment flushing (YRCC 2008).

210 Table 1 Annual mean water entitlement sharing in the Yellow River (Unit: 10⁸
 211 m³)

Province	Qinghai	Sichuan	Gansu	Ningxia	Inner Mongolia	Shaanxi	Shanxi	Henan	Shandong	Tianjin	Total
Water Entitlement	14.1	0.4	30.4	40.0	58.6	38.0	43.1	55.4	70.0	20.0	370.0

212 Note: Data from the “Yellow River water allocation scheme”, Chinese State
213 Council, 1987.

214 In the 1990s, a SAW regime was established (Yang et al. 2004). At the end of
215 1998, the Chinese State Planning Commission and the Ministry of Water
216 Resources formulated the “Administrative Measures of Yellow River Water
217 Diversion”, which stipulated the procedures of SAW in the Yellow River to
218 ensure the enforcement of the “1987 Scheme”. Considering the variations
219 between different years and within each year, the Yellow River Conservation
220 Commission (YRCC) formulates an annual water diversion plan with detailed
221 monthly water allocation quota according to different natural runoff and storage
222 rates in the reservoirs (Xia and Pahl-Wostl 2012).

223 *2.3.2 St. George region in Australia and capacity sharing*

224 CS has been in operation in the St. George region of the Murray–Darling Basin in
225 Australia since 2000 and is being adopted elsewhere in the Basin.

226 The Murray–Darling Basin is Australia’s largest and most important catchment,
227 covering one-seventh of the continent (1 million km²); it is responsible for about
228 half the nation’s food and agricultural production and supplies water to more than
229 two million people. St. George is located on the Balonne River in southern
230 Queensland and in the northern the Murray–Darling Basin (Fig. 3). The St.
231 George irrigation region covers a total area of around 190 km². The main irrigated
232 crop in the region is cotton, but some grapes and vegetables are also produced.
233 The total surface water of the region is 99.5 million m³, of which the issued water
234 entitlement is 84.4 million m³.

Fig. 3 the case location and the rivers of the St. George region

Note: Data from the Geoscience Australia, Australian Government

The main water storage in the St. George irrigation system is the Beardmore Dam, which has a storage capacity of 81.7 million m^3 . In the CS, each capacity share defines an equal and inseparable proportional share of inflows and storage. For example, a 10% capacity share includes a right to 10% of the storage capacity and a 10% share of available inflows. Approximately 80.7 million m^3 of the system's effective storage capacity is allocated to individual irrigators. Table 2 summarizes the distribution of storage capacity shares in St. George.

Table 2 Storage shares, St. George (Unit: 10^4 m^3)

Size of Storage Capacity Share	< 5	5 to 50	50 to150	>150	Total
Number of Users	18	25	29	22	94

Note: Data from the Australian Bureau of Agricultural and Resource Economics, 2009.

2.3.3 Taolai River in China and duration-based water allocation

The Taolai RB is an inland river basin located in Gansu Province of Northwestern China covering an area of 28,100 km^2 . The total runoff in the mainstream of the basin is 683 million m^3 and the water storage is 232 million m^3 . There are three main water users in the basin (Fig. 4) including the Jiuquan Iron & Steel Corporation (JQI&SC), the Taolai Irrigation District (Taolai ID), and the Yuanyang Irrigation District (Yuanyang ID). Using the DWA system, users share the annual water release days (365 days in total) of the mainstream of the Taolai

256 River: 37 days of water use for upstream JQI&SC; 153 days for Taolai ID; and
 257 175 days for downstream Yuanyang ID. These days are referred to as “allocation
 258 period” in this paper. Except for the annual water use of JQI&SC that is limited to
 259 45 million m³, Taolai ID and Yuanyang ID can store or use the entire natural
 260 stream flow during their water allocation period.

261

262 **Fig. 4 Location and river of the Taolai Basin**

263 Note: Data from the National Fundamental Geographic Information System,
 264 China.

265

266 **Fig. 5 Duration-based water allocation in the Taolai River Basin**

267 Note: Data from the Water Resources Management Bureau of Taolai River Basin,
 268 China.

269 Under the DWA system, the discharge volume within a specific allocation period
 270 provides the maximum available water for the user who is authorized to withdraw
 271 water during that period. As illustrated in Fig. 5, the shaded area under the flow

curve indicates the available water volume for Yuanyang ID in its first allocation period of the year. The annual available water can be identified by accumulating all the available water in each allocation period within the year.

The main characters of three regions are shown in Table 3. The Yellow RB is largest based on spatial area. In the Yellow RB, water is allocated to a few provinces but there are a very large number of users across a great area. There are 3 users in the Taolai RB and the reservoir storage capacity there is only 34% (=232/683) of the surface water resources. In St. George, the reservoirs can almost store all the available surface water and the capacity sharing in the St. George is carried by 94 users on a small area.

Table 3 the main characters of three basins/regions referring to the water allocation regimes

Basin/Region	Area (km ²)	Surface water availability (Million m ³ /a)	Storage capacity (Million m ³ /a)	Allocation regimes	Users
Yellow River	753,000	58,000	30,340	Seasonal water allocation	10 provinces
St. George	190	84	100	Capacity sharing	94 users
Taolai River	28,100	683	232	Duration-based allocation	3 users

3 Results

As shown in Table 4, the coefficient of variation (CV) of annual natural runoff and relevant water allotment in the Yellow RB is 0.20. The social-economic water allotment is presumed to have increased in the wet year, decreased in the dry year, and varied in the same proportion with the changes of annual natural runoff. The inter-year water that remained in the reservoirs does not contribute to the water allotment when the water allotment is continuously accounted across multiple years in this study. The CV of total water use in the basin is 0.09, representing low variability of water use in the Yellow River under the current seasonal water allocation regime. The water-use CVs of the inner-basin provinces vary from 0.07 to 0.19, across which the diversity of water use (identified as the variability of individual water users' CVs) is 0.35.

Table 4 annual water allotment and use in the Yellow River Basin (Unit: 10⁸ m³)

NO.	Year	Natural runoff	Annual water allotment	Water use									Total
		(1)	(2)	Qinghai	Gansu	Ningxia	Inner	Shaanxi	Shanxi	Henan	Shandong		
		(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	
(1)	1988	560.3	349.6	13.4	25.7	42.5	63.3	22.1	12.1	50.8	95.5	325.3	

NO.	Year	Natural runoff	Annual water allotment	Water use								Total
		(1)	(2)	Qinghai	Gansu	Ningxia	Inner	Shaanxi	Shanxi	Henan	Shandong	
		(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)
(2)	1989	688.7	337.7	9.8	23.3	34.1	60.6	19.6	14.4	37.2	134.8	333.8
(3)	1990	507.6	415.1	10.0	23.6	35.4	64.6	18.5	12.3	33.0	80.9	278.3
(4)	1991	392.0	306.0	15.9	23.9	34.6	71.6	19.7	12.5	40.0	83.2	301.3
(5)	1992	519.8	236.3	15.8	24.5	33.7	66.2	21.0	13.2	33.8	89.3	297.5
(6)	1993	529.2	313.3	9.9	21.1	31.7	67.9	17.3	10.3	35.5	86.1	279.8
(7)	1994	445.6	319.0	10.6	17.6	31.6	63.5	22.8	9.2	28.8	71.1	255.3
(8)	1995	397.5	268.6	10.7	18.4	30.4	63.5	22.0	9.0	31.2	73.3	258.5
(9)	1996	454.8	239.6	13.5	30.0	33.2	64.4	22.1	9.9	37.7	81.2	291.8
(10)	1997	346.3	274.1	12.3	25.8	39.5	61.2	25.0	12.2	36.7	87.0	299.6
(11)	1998	439.1	208.7	11.6	23.5	37.1	61.5	19.7	10.5	29.5	83.6	277.0
(12)	1999	466.4	264.7	12.1	25.8	41.5	66.5	20.9	9.6	34.6	84.5	295.3
(13)	2000	355.1	281.1	13.2	27.4	37.8	59.5	21.7	9.9	31.5	63.9	264.9
(14)	2001	326.5	214.0	11.3	26.9	37.0	61.0	21.8	10.5	29.4	63.4	261.3
(15)	2002	297.7	196.8	11.7	26.1	35.7	59.2	21.1	10.4	36.0	80.3	280.6
(16)	2003	568.1	179.4	10.9	29.2	35.6	50.5	18.7	9.6	28.3	50.6	233.3
(17)	2004	400.5	342.4	10.6	29.3	37.7	56.4	20.9	10.1	26.1	49.6	240.6
(18)	2005	554.8	241.4	10.8	29.2	42.1	62.2	23.6	11.8	29.3	57.3	266.3
(19)	2006	400.2	334.4	13.6	30.1	39.0	60.9	26.8	12.9	37.8	80.5	301.6
(20)	2007	489.5	241.2	13.3	30.4	39.4	59.7	25.0	13.6	33.6	71.6	286.7
(21)	2008	400.4	295.1	12.1	30.1	39.0	57.1	26.8	14.5	39.4	69.7	288.6
(22)	2009	479.9	241.4	11.0	29.9	38.0	61.3	25.6	15.1	43.4	73.4	297.7
(23)	2010	457.7	289.3	10.5	30.3	35.5	61.3	24.4	18.2	44.1	74.5	298.8
(24)	CV	0.20	0.20	0.14	0.14	0.09	0.07	0.12	0.19	0.17	0.22	0.09

297 Note: Sichuan province and Tianjin City are not included in the analysis because
298 the water use of Sichuan is much less than the other provinces and no water
299 consumption data are available for Tianjin in some years.

300 Data source: Yellow River Conservation Commission, China

301 The inflow and withdrawal data of St. George under the CS are shown in Table 5.

302 The CV of total inflows to storage is 0.61. The CV of water withdrawals (for
303 irrigation and urban use) is 0.34.

304 Table 5 annual water availability and use under capacity sharing in St George

305 (Unit: 10^8 m^3)

Item	NO.	2004 to 2005	2005 to 2006	2006 to 2007	2007 to 2008	CV
		(1)	(2)	(3)	(4)	(5)
Opening storage volume	(1)	0.54	0.32	0.31	0.04	/
Total inflows	(2)	0.71	1.11	0.13	1.11	0.61
Storage losses	(3)	0.36	0.41	0.13	0.36	/
Reconciliation	(4)	0.11	0.06	0.06	0.07	/
Withdrawals	(5)	0.68	0.76	0.33	0.50	0.34
Total net out flows	(6)=(5)+(3)-(4)	0.93	1.11	0.40	0.79	/
Est. ending storage volume	(7)=(1)+(2)-(6)	0.32	0.31	0.04	0.36	/

306 Note: Reconciliation reflects the error of estimation of water losses in the storage
307 and is used to ensure that the volume of water in the storage matches the recorded
308 values in the users' water accounts.

309 Data source: Australian Bureau of Agricultural and Resource Economics, 2009
 310 Table 6 shows the distribution of water-use variability from 2004 to 2008 across
 311 the 55 water users in the St. George region. Significant diversity is observed in the
 312 variability of individual water use, as proven by the consistent differences in the
 313 annual water use strategies adopted by irrigators under the CS. For example,
 314 differences between growers of different crops, such as cotton and grapes, and
 315 differences in irrigation requirements, are facilitated by CS and thus lead to
 316 variation in water-use practices. The diversity of the variability of individual
 317 water use is 0.73, equals to the CV of the data in column (1) in Table 6 across all
 318 the 55 users.

319 Table 6 Water-use diversity among users under capacity sharing

Water use variability (coefficient variation), St George 2002-03 to 2007-08	Percentage of users
0.0	0.0
0.0-0.2	6.8
0.2-0.4	28.8
0.4-0.6	27.7
0.6-0.8	8.8
0.8-1.0	4.0
1.0-1.2	6.6
1.2-1.4	6.6
1.4-1.6	4.5
1.6-1.8	2.0
1.8-2.0	0.0
2.0-2.2	4.2

320 Data source: Australian Bureau of Agricultural and Resource Economics, 2009
 321 The natural runoff and water-use data in the Taolai RB under the duration-based
 322 allocation regime are shown in Table 7. The annual water allocations among the
 323 irrigation regions are estimated by integrating the river flow across all the
 324 allocation periods of the irrigation regions. The CV of annual water allotment,
 325 which represents the variation of the water availability, is 0.18. The water use (for
 326 irrigation and urban use) CV of Taolai and Yuanyang irrigation regions are 0.07
 327 and 0.28, across which the diversity is estimated at 0.87.

328 Table 7 Annual water allotment and use in Taolai River Basin under duration-
 329 based allocation (Unit: 10^8 m^3)

No.	Year	Natural runoff	Annual water allotment			Water use		
			Taolai	Yuanyang	Total	Taolai	Yuanyang	Total
		(1)	(2)	(3)	(4)=(2)+(3)	(4)	(5)	(6)=(4)+(5)
(1)	1980	5.67	2.13	1.95	4.08	1.55	1.95	3.50
(2)	1981	7.32	3.35	3.10	6.45	1.79	4.19	5.98
(3)	1982	6.13	2.96	2.53	5.49	1.76	3.08	4.84

No.	Year	Natural runoff	Annual water allotment			Water use		
			Taolai	Yuanyang	Total	Taolai	Yuanyang	Total
		(1)	(2)	(3)	(4)=(2)+(3)	(4)	(5)	(6)=(4)+(5)
(4)	1983	7.02	3.36	3.05	6.41	1.72	3.74	5.46
(5)	1984	5.21	2.36	2.08	4.44	1.54	1.95	3.49
(6)	1985	5.14	1.98	1.81	3.79	1.65	1.80	3.45
(7)	1986	5.37	2.12	1.88	4.00	1.57	1.92	3.50
(8)	1987	5.57	2.52	1.93	4.46	1.59	1.74	3.33
(9)	1988	4.68	1.96	1.93	3.89	1.55	1.87	3.41
(10)	1989	4.69	3.15	2.66	5.81	1.80	3.48	5.28
(11)	1990	4.47	2.09	2.14	4.23	1.56	2.33	3.89
(12)	1991	5.08	2.07	1.95	4.01	1.49	1.95	3.44
(13)	1992	5.14	2.29	2.21	4.50	1.58	2.48	4.06
(14)	1993	5.29	2.63	2.47	5.11	1.65	2.86	4.51
(15)	1994	5.16	2.39	2.14	4.53	1.65	3.37	5.01
(16)	1995	5.59	2.09	1.91	4.00	1.48	2.00	3.48
(17)	1996	4.82	2.07	2.07	4.14	1.44	2.31	3.75
(18)	1997	4.41	1.79	1.72	3.51	1.48	1.66	3.14
(19)	1998	5.58	2.57	2.40	4.96	1.69	2.78	4.47
(20)	1999	6.70	2.79	2.76	5.55	1.65	3.36	5.01
(21)	2000	6.39	3.02	2.72	5.74	1.64	3.47	5.10
(22)	2001	5.86	2.43	2.24	4.66	1.59	2.51	4.10
(23)	2002	6.54	3.17	3.01	6.18	1.37	3.88	5.26
(24)	2003	5.71	2.28	2.22	4.50	1.63	2.39	4.02
(25)	2004	5.98	2.34	2.15	4.49	1.65	2.22	3.87
(26)	2005	7.08	3.08	2.87	5.95	1.75	3.41	5.16
(27)	2006	6.48	2.56	2.53	5.09	1.69	2.84	4.54
(28)	2007	7.39	3.21	2.92	6.13	1.80	3.92	5.72
(29)	2008	6.31	2.64	2.66	5.30	1.69	3.18	4.88
(30)	CV	0.15	0.18	0.18	0.18	0.07	0.28	0.19

Note: the annual water use of JQI&SC is limited to 37 days and also 45 million m³; thus, it was not considered in the assessment.

Data source: Water Resources Management Bureau of Taolai RB, China

Table 8 shows the flexibility based performance of the three water allocation regimes. DWA regime is estimated to have the highest flexibility in terms of water use. SWA in the Yellow RB has the lowest flexibility compared with the other two allocation regimes.

Table 8 Flexibility of water allocation regimes

Water allocation regime	Variability of allotment (1)	Variability of use (2)	Diversity of use (3)	Flexibility (4)=[(2)/(1)]*(3)
SWA	(1)	0.20	0.09	0.35
CS	(2)	0.61	0.34	0.73
DWA	(3)	0.18	0.19	0.87

Note: [row (1), column (1)] = [row (24), column (1)] in Table 4; [row (1), column (2)] = [row (24), column (11)] in Table 4. [row (2), column (1)] = [row (2), column (5)] in Table 5; [row (2), column (2)] = [row (5), column (5)] in Table 5. [row (3), column (1)] = [row (30), column (4)] in Table 7; [row (3), column (2)] = [row (30), column (6)] in Table 7.

342   **4 Discussion**

343   Under the SAW, users' annual mean water rights are defined by volumetrically
344   sharing the annual mean runoff of a river. The water management authority
345   announces the available percentage of the annual mean water right at the start of
346   the season to each individual user according to the forecasted stream flow and
347   current storage. Given the uncertainty over seasonal inflows, allocations are
348   announced and progressively adjusted, often at monthly intervals. Typically, the
349   initial allocation at the commencement of the season is relatively conservative,
350   and the allocation is increased or reduced as inflows arrive later in the season
351   (Hughes and Goesch 2009b) under a centralized regulation regime.

352   CS is a more decentralized process that allows individual users to exercise a
353   certain degree of individual control over storage decisions, leading to more
354   flexible management of water. As a result, water entitlements closely reflect the
355   physical realities of the water supply system, such as constrained storage capacity,
356   variable water inflows, and significant losses from storage and delivery.

357   The DWA system is simpler than the CS and allows individual water users to
358   withdraw and store the entire natural stream flow within their permitted extraction
359   period and independently manage it. Users can decide how much water to use and
360   how much to leave in the water course while taking all risks from hydrological
361   uncertainty. The water authority does not need to make volumetric allocation
362   announcements, and is only responsible for water-use planning and accounting to
363   ensure that water users do not exceed their allotted duration. The hydrological
364   risks are shouldered by the water users, but they also acquire more flexibility to
365   make their own decisions on use.

366   Our assessment results show that the water-use flexibility under DWA is higher
367   than that of CS. The reason for this finding is that users can freely withdraw water
368   from the river course during their allocation periods without reservoir regulation
369   in the DWA. As there are less reservoirs in the Taolai RB, the water users highly
370   rely on the stream inflow. People have to adjust the their water demand if there is
371   a water deficit. For example, the local farmers accept to reduce irrigation water or
372   cancel some irrigation plans to some extent if there is insufficient water in the
373   river during their allocation periods. Farmers tend to regard this water shortage as
374   "acceptable", because the deficit is caused by the natural hydrological variability

375 and they unfortunately encounter a drought during their allocation periods. This
376 behavior increase the flexibility in the basin.

377 It may be argued that the degree of water use flexibility in the St. George, where
378 the runoff is nearly thoroughly regulated by a multiyear reservoir, should be the
379 highest. This is because that the runoff regulation reservoirs play an critical role in
380 flexible water use. With enough reservoirs, users can withdraw water from storage
381 at almost any time when their need it. This increases the water supply reliability
382 and use flexibility. However, in the Taolai RB which actually is surrounded by
383 deserts and has a lot of potential farm lands, the water users are able to pump all
384 the stream water for irrigation from the river during their allocation periods and
385 can reduce the water demand when drought. The elastic demand management
386 strategy under the DWA allows the Taolai RB have higher degree of flexibility
387 even its runoff is partly regulated.

388 The disadvantage of DWA is also obvious. Considering that no volumetric caps in
389 water use or requirements of environmental flow maintenance exist, DWA system
390 often results in the drying up of surface stream and the over-extraction of ground
391 water. The surface water resources development ratio of the Taolai River has been
392 rising and is now close to 100%; the groundwater has also been over-exploited.
393 Although these problems could be remedied using a western style approach to
394 volumetric water licensing, or by allowing water abstractions only when river
395 flows are above pre-determined levels such as the regimes used in the southern
396 Murray Darling Basin in unregulated streams (Goulburn Murray Water, 2013).

397 Referring to the formula of F , the $WA(t)$ is recognized as the maximum water
398 volume that people are able to harvest and withdraw from the river in the basin.
399 This water availability cannot always fully meet the demand, especially in the arid
400 areas. In the Taolai RB and the Yellow RB, due to the development of agriculture
401 and the dry climate, there are plenty of irrigation districts which are able to
402 consume all the stream flow and dry up the river if there are no water use
403 permission systems. In this case, the water availability is limited by the quantity
404 of natural water resource and is equal to the runoff.

405 The case study areas adopted in this study obviously vary in terms of natural and
406 social backgrounds, such as the precipitation, degree of regulation, scale of
407 agriculture, aquatic environment conditions, environmental water allocation and

farmers' income influenced by market conditions (crop prices and agricultural costs) as well as the number of water users in a system, etc. These differences could influence the variation and diversity in surface water use. For example, The annual mean rainfall in St George, is about 530 mm which is higher than that in the Yellow RB, at 430 mm and in the Taolai RB, at about 80 mm. This means that water famers in the St George may less rely on the stream water for irrigation and need more autonomous water use strategy. In addition, the Australian farmers who generally have much larger land area than the Chinese ones, can make more wealth from irrigation agriculture and be richer. This may provide the Australian farmers with stronger capability to develop individual water use strategy, such as selling water to others in a high price. However, this paper focuses on proposing a method for orienting assessments about the flexibility of the basin overall management system. It gives an averaged estimation. Future research to develop a practical system to underpin policy and decision making should investigate the detail and significance of factors that might influence water use variability and diversity.

5 Conclusion

River flow is characterized by variability and research has demonstrated that flexible water allocation systems substantially improve regional welfare (Kilgour and Dinar 2001). Understanding and increasing the flexibility of water allocation systems to cope with hydrologic variability is one of the key issues in sustainable water management.

This study proposes a quantitative method to measure water allocation flexibility. Results show that water allocation flexibility is positively correlated with water use autonomy. Evidence from the comparative study among the SWA in the Yellow River in China, the CS in Australia, and the DWA in Northwestern China shows that the more choices or the higher capacity for autonomous water use allocated to distributive water users, the greater the flexibility obtained by the allocation system. The proposed method could provide a comparative reference for different water allocation regimes based on the performance of flexibility and help in quantitatively identifying key factors, such as autonomy, diversity, and variability, which can improve the flexibility level of the water allocation system.

440 The proposed method is also useful for evaluating and developing water
441 allocation regimes with more flexibility.

442

443 Acknowledgement

444 This research was supported by the National Natural Science Foundation of China
445 (91125018 and 51009076), the 2012 Chinese Ministry of Science and Technical-
446 Internet of Water Project (2013BAB05B03), the 2011 Chinese Ministry of Water
447 Resource Program-Shiyang River Project (201101046), and the Australian
448 Research Council (Project No. DP120102917).

449

450 Reference

- 451 Assche VK, Beunen R, Jacobs J, Teampau P (2012) Crossing trails in the
452 marshes: rigidity and flexibility in the governance of the Danube Delta.
453 *Journal of Environmental Planning and Management* 54(8): 997-1018.
- 454 Cross P (2000) Benefits of flexible Irrigation water supply. *Journal of Irrigation*
455 *and Drainage Engineering* 126(5): 275-278
- 456 Dudley N, Musgrave W (1988) Capacity sharing of water reservoirs. *Water*
457 *Resources Research* 24(5): 649-658
- 458 Falkenmark M, Rockström J (2010) Building Water Resilience in the Face of
459 Global Change: From a Blue-Only to a Green-Blue Water Approach to
460 Land-Water Management. *Journal of Water Resources Planning and*
461 *Management* 136(6): 606-610
- 462 Faye RM, Sawadogo S, Mora-Camino F (2005) Flexible management of water
463 resource systems. *Applied Mathematics and Computation* 167(1): 516-527
- 464 Goulburn Murray Water (2013) Unregulated Streams Local Management Rules.
465 [http://www.g-mwater.com.au/water-resources/surface-water/unregulated-](http://www.g-mwater.com.au/water-resources/surface-water/unregulated-local-management-rules)
466 [local-management-rules](http://www.g-mwater.com.au/water-resources/surface-water/unregulated-local-management-rules).
- 467 Graddon AR, Kuczera G, Hardy MJ (2011) A flexible modelling environment for
468 integrated urban water harvesting and re-use. *Water Science &*
469 *Technology* 63(10): 2268-2278
- 470 Grönlund E, Määtä T (2008) Implications of flexibility in European Community
471 environmental law: exemptions from environmental objectives in the
472 Water Framework Directive. *Hydrobiologia* 599(1): 221-226
- 473 Gunderson LH, Carpenter SR, Folke C, Olsson P, Peterson GD (2006) Water
474 RATs (resilience, adaptability, and transformability) in lake and wetland
475 social-ecological systems. *Ecology and Society* 11(1): 16
- 476 Gupta D, Buzacott JA (1989) A framework for understanding flexibility of
477 manufacturing systems. *Journal of Manufacturing Systems* 8(2): 89-97
- 478 Hughes N, Goesch T (2009a) Management of irrigation water storages: carryover
479 rights and capacity sharing. Australian Bureau of Agricultural and
480 Resource Economics, research report 09.10, Canberra, May.
- 481 Hughes N, Goesch T (2009b) Capacity sharing in the St George and MacIntyre
482 Brook irrigation schemes in southern Queensland. Australian Bureau of

483   Agricultural and Resource Economics, research report 09.12, Canberra,
484   June.

485 Jafarzadegan K, Abed-Elmdoust A, Kerachian R (2013) A fuzzy variable least
486   core game for inter-basin water resources allocation under uncertainty.
487   Water Resources Management 27(9): 3247-3260.

488 Kilgour D, Dinar A (2001) Flexible water sharing within an international river
489   basin. Environmental and Resource Economics 18(1): 43-60.

490 Kumar V (1987) Entropic measures of manufacturing flexibility. International
491   Journal of Production Research 25(7): 957-966.

492 Larsen TA, Gujer W (2001) Waste design and source control lead to flexibility in
493   wastewater management. Water Science and Technology 43(5): 309-318.

494 Li BH, Chang CT (2011) Efficient flexibility assessment procedure for water
495   network designs. Industrial & Engineering Chemistry Research 50(7):
496   3763-3774.

497 Marreco J, Carpio L (2006) Flexibility valuation in the Brazilian power system: A
498   real options approach. Energy Policy 34(8): 3749-3756.

499 Milman A, Short A (2008) Incorporating resilience into sustainability indicators:
500   An example for the urban water sector. Global Environmental Change
501   18(4): 758-767.

502 Schlüter M, Pahl-Wostl C (2007) Mechanisms of resilience in common-pool
503   resource management systems: an agent-based model of water use in a
504   river basin. Ecology and Society 12(2): 4.

505 Shao WW, Yang DW, Hu HP, Sanbongi K (2009) Water resources allocation
506   considering the water use flexible limit to water shortage - a case study in
507   the Yellow River Basin of China. Water Resource Manage 23(5): 869-880.

508 Shuiabia E, Thomsona V, Bhuiyanb N (2005) Entropy as a measure of operational
509   flexibility. European Journal of Operational Research 165(3): 696-707.

510 Teh CL, Teh SL, Meitner JM (2012) Preferred resource spaces and fisher
511   flexibility: implications for spatial management of small-scale fisheries.
512   Human Ecology 40(2): 213-226.

513 Wang ZJ, Zheng H, Wang X (2009) A harmonious water rights allocation model
514   for Shiyang River Basin, Gansu Province, China. International Journal of
515   Water Resources Development 25(2): 355-370.

516 Wright TF, Eberhard JR, Hobson EA, Avery ML, Russell MA (2010) Behavioral
517   flexibility and species invasions: the adaptive flexibility hypothesis.
518   Ethology Ecology and Evolution 22(4): 393-404.

519 Xia C, Pahl-Wostl C (2012) The development of water allocation management in
520   the Yellow River Basin. Water Resources Management 26(3): 395-3414.

521 Yang D, Li C, Hu H, Lei Z, Yang S, Kusuda T, Koike T, Musiaka K (2004)
522   Analysis of water resources variability in the Yellow River of China
523   during the last half century using historical data. Water Resources
524   Research 40:W06502.

525 YRCC (2008) Management and diversion of water resources in the Yellow River.
526   The Yellow River Publisher, Zhengzhou, China.

527 Zheng H, Wang ZJ, Hu SY, Malano H (2013) Seasonal water allocation – dealing
528   with hydrologic variability in the context of water rights system. Journal of
529   Water Resources Planning and Management, 139(1), 76-85.

530 Zheng H, Wang ZJ, Hu SY, Wei YP (2012) A comparative study of the
531   performance of public water rights allocation in China. Water Resources
532   Management 26(5): 1107-1123.

Minerva Access is the Institutional Repository of The University of Melbourne

Author/s:

Zheng, H;Lyle, C;Wang, Z

Title:

A Comparative Study of Flexibility in Water Allocation in the Context of Hydrologic Variability

Date:

2014-02-01

Citation:

Zheng, H., Lyle, C. & Wang, Z. (2014). A Comparative Study of Flexibility in Water Allocation in the Context of Hydrologic Variability. WATER RESOURCES MANAGEMENT, 28 (3), pp.785-800. <https://doi.org/10.1007/s11269-014-0515-4>.

Persistent Link:

<http://hdl.handle.net/11343/283322>