DR REBECCA MORRIS (Orcid ID : 0000-0003-0455-0811)

Article type : Commentary

Handling Editor: Melinda Coleman

The application of oyster reefs in shoreline protection: are we over-engineering for an ecosystem engineer?

Rebecca L. Morris¹, Donna M. Bilkovic², Maura K. Boswell³, David Bushek⁴, Just Cebrian^{*5,6}, Joshua Goff⁵, Kelly M. Kibler⁷, Megan K. La Peyre⁸, Giovanna McClenachan⁹, Josh Moody¹⁰, Paul Sacks⁹, Jenny P. Shinn⁴, Eric L. Sparks^{11,12}, Nigel A. Temple¹¹, Linda J. Walters⁹, Bret M. Webb¹³ and Stephen E. Swearer¹

This draft manuscript is distributed solely for purposes of scientific peer review. Its content is deliberative and predecisional, so it must not be disclosed or released by reviewers. Because the manuscript has not yet been approved for publication by the U.S. Geological Survey (USGS), it does not represent any official USGS finding or policy.

¹National Centre for Coasts and Climate, School of BioSciences, The University of Melbourne, VIC 3010, Australia; ²Virginia Institute of Marine Science, College of William & Mary, Gloucester Point, VA 23062, USA; ³Department of Civil and Environmental Engineering, Old Dominion University, Norfolk, VA 23529, USA; ⁴Haskin Shellfish Research Laboratory, Rutgers University, Port Norris, NJ 08349, USA; ⁵Dauphin Island Sea Lab, Dauphin Island, AL 36528, USA; ⁶Department of Marine Sciences, University of

This is the author manuscript accepted for publication and has undergone full peer review but has not been through the copyediting, typesetting, pagination and proofreading process, which may lead to differences between this version and the [Version of Record](#). Please cite this article as [doi: 10.1111/1365-2664.13390](https://doi.org/10.1111/1365-2664.13390)

This article is protected by copyright. All rights reserved

South Alabama, Mobile, AL 36688, USA; ⁷Department of Civil, Environmental & Construction Engineering and National Center for Integrated Coastal Research, University of Central Florida, Orlando, FL 32816, USA; ⁸U.S. Geological Survey, Louisiana Cooperative Fish and Wildlife Research Unit, School of Renewable Natural Resources, Louisiana State University Agricultural Center, Baton Rouge, LA 70803, USA; ⁹Department of Biology and National Center for Integrated Coastal Research, University of Central Florida, Orlando, FL 32816, USA; ¹⁰Partnership for Delaware Estuary, Wilmington, DE 19801, USA; ¹¹Coastal Research and Extension Center, Mississippi State University, Biloxi, MS 39532, USA; ¹²Mississippi-Alabama Sea Grant Consortium, Ocean Springs, MS 39564, USA; ¹³Department of Civil, Coastal & Environmental Engineering, University of South Alabama, Mobile, AL 36688, USA.

*Current address: Northern Gulf Institute, Mississippi State University, Stennis Space Center, MS 39529, USA.

Corresponding Author:

Rebecca Morris, Email rebecca.morris@unimelb.edu.au, Tel. +61 4 2339 2882

Running head: Oyster reefs for shoreline protection

Keywords: climate adaptation; coastal defences; coastal protection; coastal management; eco-engineering; living shorelines; oyster; urbanization

Paper type: Commentary

Abstract

1. Oyster reef living shorelines have been proposed as an effective alternative to traditional coastal defence structures (e.g., bulkheads, breakwaters), with the benefit that they may keep pace with sea-level rise and provide co-benefits, such as habitat provision. However, there remains uncertainty about the effectiveness of shoreline protection provided by oyster reefs, which limits their broader application.
2. We draw evidence from studies along the east and gulf coasts of the US, where much research and implementation of oyster reef restoration has occurred, to better define the existing gaps in our understanding of the use of restored oyster reefs for shoreline protection.
3. We find potential disconnects between ecological and engineering functions of reefs. In response, we outline how engineering and ecological principles are used in the design of oyster reef living shorelines and highlight knowledge gaps where an integration of these disciplines will lead to their more effective application.
4. *Synthesis and applications.* This work highlights the necessary steps to advance the application of oyster reef living shorelines. Importantly, future research should focus on appropriate designs and conditions needed for these structures to effectively protect our coasts from erosion, while supporting a sustainable oyster population, thereby providing actionable nature-based alternatives for coastal defence to diverse end-users.

1. Living shorelines for coastal defence

There is an emerging interest in harnessing the natural protection benefits offered by existing or restored/created (hereafter “restored”) coastal habitats, such as dunes, biogenic reefs and vegetation (Temmerman et al., 2013; Spalding, et al., 2014). These existing or restored habitats are often presented as an alternative to the use of traditional defence structures (e.g., seawalls, breakwaters and groynes, Figure 1a) in response to the potentially negative socio-economic (Hinkel, et al., 2014) and environmental (Bulleri & Chapman, 2010) effects of the latter. For example, artificial structures replace natural shorelines with a homogeneous habitat

that supports less biodiversity (Chapman, 2003) and a greater number of non-native species (Dafforn et al., 2012; see reviews by Bulleri & Chapman, 2010; Firth et al. 2016a). Recent reviews have argued that existing and restored habitats can be a cost-effective shoreline protection alternative to traditional structures under future scenarios of climate change and coastal development (Narayan et al., 2016; Reguero et al., 2018). Nevertheless, a number of knowledge gaps hinder the application of nature-based habitats for coastal defence (Feagin et al., 2010; Bouma et al., 2014), paramount among these being the dearth of field data quantifying the coastal defence value of these shoreline protection approaches, especially for restored habitats (Morris et al., 2018).

The east and gulf coasts of the United States have pioneered the introduction of “living shoreline” techniques using restored habitats, such as saltmarsh and oyster reefs (Figure 1b), sometimes in combination with hard structures (e.g., rock sills, Figure 1c), for biodiversity enhancement and erosion control in relatively low-energy estuarine settings (Bilkovic, *et al.*, 2017). Concurrent with these projects, has been the development of policy directives to promote the use of these approaches (e.g., The 2008 Living Shorelines Protection Act in Maryland). One increasingly popular approach involves the use of oyster reefs as a component of shoreline protection. In recent decades, there have been significant efforts to reverse the global decline of oysters (estimated at 85% functionally extinct; Beck et al., 2011) through oyster reef restoration (La Peyre et al., 2014a; Gillies et al., 2017). Initially, restoration focused on recovering the harvest of oysters and other fisheries associated with these reefs (Beck et al., 2011). More recently, there has been a growing focus on maximizing other services and benefits, such as water quality and shoreline protection (Grabowski et al., 2012). In addition to erosion control, another great attribute of oyster reefs (and living shorelines more generally) is that they are adaptive to environmental changes (Taylor and Bushek, 2008; Bible & Sandford, 2015). For instance, oyster reefs can recover quickly from major storm events (Livingston et al., 1999) and accrete at a rate equal to or greater than sea-level rise (Rodriguez et al., 2014) or local subsidence (Casas et al., 2015). This is in contrast to artificial structures, which have to be rebuilt, upgraded and maintained in response to a changing climate, at significant expense (Hinkel et al., 2014).

Despite recent advances in the promotion of living shorelines over traditional defence structures for shoreline protection, there remains uncertainty in the efficacy of shoreline protection provided by some living shoreline designs, including existing and restored oyster reefs. Indeed, scant data exists that evaluate the effectiveness of existing and restored oyster reefs at curbing shoreline erosion. Where data are available, the results are often highly

variable (e.g., La Peyre et al., 2013; see meta-analysis by Morris et al., 2018). Here we draw evidence from studies along the east and gulf coasts of the United States, where considerable research and implementation of oyster reef restoration has occurred, to better define the existing gaps in our understanding of the use of restored oyster reefs for shoreline protection. This information may be particularly useful to practitioners that are considering or beginning to apply living shorelines using shellfish reefs in other locations (e.g., *Saccostrea glomerata* [Sydney Rock oyster] in Australia, Coghlan et al. 2016; *Crassostrea gigas* [Pacific oyster] in the Netherlands, Walles et al. 2016; *Ostrea lurida* [Olympia oyster] on the US west coast; and *Geukensia demissa* [Ribbed mussel] along the US Atlantic coast, Moody, 2012), as well as for prospective oyster reef living shorelines along the east and gulf coasts. We use lessons learned from these regions to outline future considerations towards the effective use of restored oyster reefs for preventing shoreline loss worldwide, with the main goal of providing valuable, applicable information to scientists and managers.

2. Oyster reef living shorelines

The primary expectation of an oyster reef living shoreline is that it will protect against waves that cause erosion. To establish an oyster reef, all species, including the Eastern oyster (*Crassostrea virginica*) native to the east and gulf coasts of the US, require a hard substratum for juvenile settlement (Bayne, 2017). This has resulted in the development of many different types of units to construct artificial reefs, which have been deployed for oyster establishment in living shorelines (Table 1). These artificial reefs vary in construction materials, unit shape, reef size (i.e., height, length, and width), and placement (i.e., distance) relative to the shoreline (e.g., depth, intertidal vs. subtidal) (Table 1; Hernandez et al. 2018). Creating reefs using recycled oyster shell, which may be deployed as loose shell, or shell within netted bags or attached to mats, is common practice (Hernandez et al. 2018). The expectation is that oyster larvae will recruit to the shell and form a reef over the top of the shell mound, cementing the shell together. In comparison with loose shell, bags or mats may prolong the integrity of the shell mound while oysters attach. The attachment of oysters is contingent on there being larvae available to settle and environmental conditions that will allow for settlement (e.g., wave exposure, salinity; La Peyre et al., 2015). Where a natural supply of larvae is not available, projects may seed reefs with spat settled elsewhere (Geraldi et al. 2013), or adult oysters (Strain et al. 2018). Oyster mats purposely have a low reef profile, whereas multiple bags can be used to build reefs of different heights and shapes (Table 1).

These structures may be built on the footprint of dead natural reefs (e.g., Florida; Walters, 2014) or, alternatively, if no previous hard substrate is present the reefs are deployed onto soft sediments.

An increasing number of commercial businesses and contractors are providing reef substrates made of steel, rip-rap, limestone and crushed or pre-cast concrete. These structures include multiple designs, which vary in shape, height, width and complexity (Table 1). Among these diverse reef substrates, some used are very large, akin to traditional breakwater units (e.g., La Peyre et al. 2013; Table 1). This begs the question of whether we are over-engineering these structures, when their purpose is to provide substrate for a living, growing reef through the sustenance of an oyster population. Ideally, reefs should be carefully designed to optimise abiotic and biotic conditions using just enough substrate to allow the colonization and development of an oyster population. Thus hypothetically, shoreline protection increases as oysters grow and then provides a consistent level of protection over time (Figure 2). This will require coastal management that is forward-thinking, with an early investment in living shorelines, rather than reacting to failure. Few comparisons exist of sustainability (i.e., oyster reef development) and efficacy in shoreline protection among different reef types, and across the diversity of environmental settings that may affect shoreline protection and oyster reef development and persistence (for an example see Walles et al. 2016, Salvador de Paiva et al. 2018). This gap in knowledge that combines both engineering and ecological function is a significant challenge and there is a need to better define engineering designs to protect shorelines, keeping in mind that the engineered structure is also meant to become a living, growing oyster reef through recruitment, growth and accumulation of oysters (Walles et al., 2016). In the following sections we outline how engineering and ecological principles are currently applied in oyster reef living shorelines, and highlight how an integration of these disciplines could lead to more effective shoreline protection.

3. Evaluation of oyster reef living shorelines

3.1 Application of engineering principles

The primary engineering goal of oyster reef living shorelines is to create a structure that remains intact and can provide coastal defence through energy attenuation and shoreline stabilization. There are a number of different ways engineering principles can enhance the

design of oyster reef living shorelines for shoreline protection (Table 2). Much of the work to understand wave attenuation by oyster reef living shorelines has taken a similar approach to that used for traditional breakwaters (Chasten et al. 1993). Performance is evaluated on the basis of the ability of the structure to reduce wave height shoreward of the structure, with the relative importance of key design parameters assessed, e.g., structure porosity, reef crest height and width, water depth and freeboard (i.e., difference between structure height and still water depth) (U.S. Army Corps of Engineers, 2002). There is a focus on applying this information to develop empirical equations characterizing hydrodynamics and wave attenuation by oyster reef breakwaters, and predicting the resulting effects on sediment dynamics and coastal stability (Allen & Webb 2011; Webb & Allen 2015).

For instance, the trend that wave attenuation is greatest when the crest of the structure is at or above the still water level, with little wave attenuation during submergence (Allen & Webb 2011; Webb & Allen 2015) should also apply to oyster reef breakwaters (Servold et al., 2015; Chauvin, 2018; MacDonald, 2018; Wiberg et al. 2018). In a controlled hydrodynamic study within a newly-deployed oyster reef living shoreline, Spiering et al. (2018) found that wave attenuation was maximized ($83 \pm 5\%$) when water levels were 1 cm below the crest of the reef structure. When mean water levels were 5 cm above the reef structure, wave heights were reduced by $42 \pm 3\%$. This was similar to the attenuation observed in a shoreline vegetated by mature mangrove ($36 \pm 6\%$) and exceeded that observed in a bare shoreline ($11 \pm 7\%$). However, crest height may be compensated with crest width regarding wave attenuation; a higher, narrower crest may attenuate as much as a lower, wider crest, with the latter being akin to how naturally occurring oyster reefs attenuate waves (Allen and Webb, 2011). This information on crest height and width is important, as justification for oyster reef living shorelines comes from evidence (both anecdotal and scientific) showing that natural intact habitats provide efficient protection (e.g., Brandon et al. 2016). However, these natural oyster reefs were expansive (Woods et al., 2005) and such reefs no longer exist. Due to the logistics of restoring oyster reefs, there are few projects where restoration occurs at the scale that natural reefs would have once existed (e.g., in some areas of Chesapeake Bay reef footprints were an average of 102,508 m² in the 1870s; Woods et al., 2005, but oyster reef living shorelines are a maximum of 865 m²; Table 1). Thus, applying engineering principles to help understand the scale required for an oyster reef living shoreline to effectively protect the coast is a critical need.

In this regard, it is noteworthy that few studies have incorporated what happens to the relevant hydrodynamics once a structure becomes fully colonized by oysters (but see Manis

et al., 2015; further discussed in section “Filling in the gaps: integrating ecology and engineering” below). Empirical approaches to describe oyster reef living shorelines need to incorporate an understanding of the coupled bio-hydrodynamic interactions within newly-deployed reef structures and throughout stages of recruitment and development, using the growing scientific literature on oyster reef hydrodynamics (e.g., Whitman & Reidenbach, 2012; Manis et al., 2015; Styles, 2015). This would result in a combined ecological-engineering approach that acknowledges the heterogeneity of shorelines and dynamic nature of living organisms.

3.2 Application of ecological principles

The adaptive ability (i.e., to environmental changes, see section above “Living shorelines for coastal defence”) of oyster reefs is a key consideration for their use in lieu of traditional breakwaters. This adaptive ability depends on successful oyster colonization and growth on the reef substrate. Therefore, the objectives of ecological research on oyster reef living shorelines should focus on the factors that affect the persistence of oysters on the reef structure (Table 2). Key parameters that have been used to assess oyster reef persistence include recruitment, growth and survival, which are normally surveyed along with environmental factors such as sedimentation, salinity and elevation (e.g., Walles et al. 2016). The development of models of oyster habitat suitability can help predict the locations for successful oyster growth and oyster reef living shorelines (e.g., Fuchs and Reidenbach, 2013; La Peyre et al. 2015).

Although there has been a number of field studies assessing oyster colonization and shoreline change following reef deployment (e.g., Piazza et al., 2005, Scyphers et al., 2011), the link between the two has not been investigated. Work to date shows variable performance of oyster reef living shorelines regarding both oyster colonization and shoreline stabilization (Morris et al., 2018). For instance, La Peyre et al. (2013) showed that reefs constructed of ReefBLKSM in Louisiana promoted shoreline accretion at one site, reduced shoreline erosion in a second site, and had no effect on shoreline stabilization in a third site. Furthermore, recruitment of oysters was observed at the first two sites, but not at the third (La Peyre et al., 2013). It should be noted, however, that much longer times may be needed to observe changes in shoreline stabilization in relation to oyster colonization (La Peyre et al., 2014b). The variability in success among studies and locations highlights the gaps in our understanding about how to design a living shoreline, which supports a self-sustaining oyster

population that provides effective coastal defence. It is imperative that we learn from both successes and failures when moving forward in oyster reef living shoreline research (Firth et al. 2016b).

4. Filling in the gaps: integrating ecology and engineering

Living shorelines have been proposed as a solution to both ecological (i.e., the loss of habitats) and engineering (i.e., non-adaptive traditional structures) challenges in increasingly human-impacted coasts (Temmerman et al. 2013; Figure 2). Oyster reef living shorelines will only be successful at protecting the coast and restoring ecosystem services if both engineering and ecological principles are married in their design such that persistent and efficacious oyster reefs are constructed. However, studies to date have been focused separately on either engineering or ecological purposes, with little merging of the two. There are multiple examples where an integration of ecological and engineering research is needed to better understand and implement the use of oyster reef living shorelines for coastal protection (Table 2a).

One example is the effect of live oysters on hydrodynamic processes and sediment stabilization. For instance, *in situ* hydrodynamic measurements indicate that, given similar flow conditions, production and dissipation of turbulent energy are an order of magnitude greater on existing healthy oyster reefs than on degraded reefs with no live oysters (Kitsikoudis et al., in review). A recent study showed that sediment accumulation by Pacific oyster (*Crassostrea gigas*) reefs is dependent on oyster density as well as the length to width ratio of the reefs, where longer and narrower reefs with higher oyster density tend to trap more sediment (Salvador de Paiva et al., 2018). This link is important, as the purpose of oyster reef living shorelines is to provide sustained coastal defence over time through a growing oyster population (Figure 2).

Another example is the effect of wave and current-induced turbulence on spat settlement to the reef. In a study of living shoreline hydrodynamics, flow-structure interaction over newly-deployed reefs created with bagged oyster shell increased shoreline velocities by over an order of magnitude as compared to two nearby control shoreline sites (Spiering et al., 2018). Such differences in turbulent conditions, as well as settlement surfaces can affect oyster recruitment (Whitman and Reidenbach, 2012). Consequently, knowledge of the appropriate benthic topography to create the optimum recruitment conditions (i.e., hydrodynamics, settlement surface, protection from predators, sedimentation, etc.) and how

292 this might need to alter under changes in climate (e.g., by facilitating certain growth forms
293 that mitigate extreme temperatures while maintaining other target functions, including coastal
294 defence; McAfee et al., 2018) will increase the chances of creating a self-sustaining reef
295 (Whitman and Reidenbach, 2012; Kitsikoudis et al., in review).

296 In summary, successful oyster reef living shorelines combine engineering and
297 ecological principles to meet both types of needs. The design and placement of a reef will
298 affect the recruitment and resilience of the oyster population on the reef, and thus the reef
299 effectiveness in restoring ecosystem services and values including coastal protection.
300 Undoubtedly, targets can only be achieved with collaborative research and common
301 integrated goals involving ecologists and engineers.

5. Conclusions

The application of oyster reef living shorelines requires a change in how ecologists and engineers approach and evaluate their respective disciplines. Many oyster reef living shorelines as currently designed are neither representative of natural oyster reefs (but see oyster mats, Table 1), nor do they perform as traditional breakwaters. Thus, it is critical to better understand how and when they work through integrated studies (Table 2b). Research on reef hydrodynamics has focused on identifying the optimal characteristics (e.g., crest height, width) of the reef base for wave attenuation. This approach, however, may result in over-engineering of oyster reef living shorelines, when the original intent was to provide a base for oyster reef development. Over time oyster accretion will cause a change in reef structure, and a key unknown is how this will alter shoreline protection. In contrast, projects that are primarily concerned with ecological values of oyster reef living shorelines (habitat provision, water quality) may fail to achieve the objective of coastal defence. Although the majority of information to date has been acquired from research on *C. virginica*, the questions that need to be addressed (Table 2b) are applicable to all shellfish reef living shorelines. Projects in their infancy have the opportunity to be forward-thinking about the information required prior to broad implementation. In order to increase uptake, oyster reef living shorelines will need to be included as a standard tool in engineering guidelines for coastal defence. Developing such guidelines will require a greater understanding of how to create a sustainable oyster reef living shoreline that provides shoreline protection. Performance data that incorporate design criteria related to both ecological and engineering function is the critical next step to achieving this goal.

Authors' contributions

All authors conceived the ideas; RLM led the writing of the manuscript. All authors contributed critically to the drafts and gave final approval for publication.

Acknowledgements

We thank K. Heck and J. Toft for their comments on an earlier version of this manuscript. RLM was supported by an Early Career Researcher Global Mobility Grant from The University of Melbourne. The National Centre for Coasts and Climate is funded through the Earth Systems and Climate Change Hub by the Australian Government's National Environmental Science Program. This paper is Contribution No. 3814 of the Virginia

Institute of Marine Science, William & Mary. Any use of trade, firm, or product names is for descriptive purposes only and does not imply endorsement by the U.S. Government.

Data accessibility

Data have not been archived because this article does not use data.

References

- Allen, R. J. & Webb, B. M. (2011). Determination of wave transmission coefficients for oyster shell bag breakwaters. *Coastal Engineering Practice*: 684-697.
- Bayne, B. L. (2017). *Biology of Oysters*. Saint Louis, Elsevier Science.
- Beck, M.W., Brumbaugh, R.D., Airoidi, L., Carranza, A., Coen, L. D., Crawford, C., . . . Guo, X. M. (2011). Oyster reefs at risk and recommendations for conservation, restoration, and management. *BioScience*, 61, 107-116.
- Bible, J. & Sanford, E. (2015). Local adaptation in an estuarine foundation species: implications for restoration. *Biological Conservation*, 193, 95 -102.
- Bilkovic, D. M., Mitchell, M. M., Toft, J. D., & La Peyre, M. K. (2017). A primer to living shorelines. In: Bilkovic, D. M., Mitchell, M. M., Toft, J. D., & La Peyre, M. K. (Eds). *Living Shorelines: The Science and Management of Nature-Based Coastal Protection*. Florida, US: Taylor and Francis.
- Brandon, C. M., Woodruff, J. D., Orton, P. M. & Donnelly, J. P. (2016). Evidence for elevated coastal vulnerability following large-scale historical oyster bed harvesting. *Earth Surface Processes and Landforms*, 41, 1136-1143.
- Bouma, T. J., van Belzen, J., Balke, T., Zhu, Z. C., Airoidi, L., Blight, A. J., . . . Herman, P. M. J. (2014). Identifying knowledge gaps hampering application of intertidal habitats in coastal protection: opportunities & steps to take. *Coastal Engineering*, 87, 147-157.
- Boyer, K., Zabin, C., De La Cruz, S., Grosholz, E., Orr, M., Lowe, J., . . . Obernolte, R. (2017). San Francisco Bay living shorelines: restoring eelgrass and Olympia oysters for habitat and shore protection. In: D. M. Bilkovic, M. M. Mitchell, M. K. La Peyre & J. D. Toft (Eds.), *Living shorelines the science and management of nature-based coastal protection* (pp. 333-363). Florida: CRC Press.
- Bulleri, F. & Chapman, M. G. (2010). The introduction of coastal infrastructure as a driver of change in marine environments. *Journal of Applied Ecology*, 47, 26-35.

368 Casas, S. M., La Peyre, J. F. & La Peyre, M. K. (2015). Restoration of oyster reefs in an
 369 estuarine lake: population dynamics and shell accretion. *Marine Ecology Progress Series*,
 370 524, 171-184.

371 Chapman, M. G. (2003). Paucity of mobile species on constructed seawalls: effects of
 372 urbanization on biodiversity. *Marine Ecology Progress Series*, 264, 21-29.

373 Chasten, M. A., Rosati, J. D., McCormick, J. W. & Randall, R. E. (1993). Engineering design
 374 guidance for detached breakwaters as shoreline stabilization structures. U.S. Army Corps of
 375 Engineers: Washington, United States.

376 Chauvin, J. M. (2018). Wave attenuation by constructed oyster reef breakwaters. Baton
 377 Rouge, Louisiana, US: Louisiana State University.

378 Coghlan, I. R., Howe, D. & Glamore, W. C. (2016). Preliminary testing of oyster shell filled
 379 bags. Water Research Laboratory Technical Report 2015/20.

380 Dafforn, K. A., Glasby, T. M. & Johnston, E. L. (2012). Comparing the invasibility of
 381 experimental "reefs" with field observations of natural reefs and artificial structures. *Plos*
 382 *One*, 7, e38124.

383 Davies, J. L. (1964). A morphogenic approach to world shorelines. *Zeitschrift für*
 384 *Geomorphologie*, 8, 27-42.

385 Firth, L. B., Knights, A. M., Bridger, D., Evans, A. J., Mieszkowska, N., Moore, P. J., . . .
 386 Hawkins, S. J. (2016a). Ocean sprawl: challenges and opportunities for biodiversity
 387 management in a changing world. *Oceanography and Marine Biology: An Annual Review*,
 388 54, 189–262.

389 Firth, L. B., Browne, K. A., Knights, A. M., Hawkins, S. J. & Nash, R. (2016b). Eco-
 390 engineered rock pools: a concrete solution to biodiversity loss and urban sprawl in the marine
 391 environment. *Environmental Research Letters*, 11, 094015.

392 Fuchs, H. L. & Reidenbach, M. A. (2013). Biophysical constraints on optimal patch lengths
 393 for settlement of a reef-building bivalve. *Plos One*, 8, e71506.

394 Geraldi, N. R., Simpson, M., Fegley, S. R., Holmlund, P. & Peterson, C. H. (2013). Addition
 395 of juvenile oysters fails to enhance oyster reef development in Pamlico Sound. *Marine*
 396 *Ecology Progress Series*, 480, 119-129.

397 Gillies, C. L., Crawford, C. & Hancock, B. (2017). Restoring Angasi oyster reefs: What is the
 398 endpoint ecosystem we are aiming for and how do we get there? *Ecological Management and*
 399 *Restoration*, 18, 214-222.

Grabowski, J. H., Brumbaugh, R. D., Conrad, R. F., Keeler, A. G., Opaluch, J. J., Peterson, C. H., . . . Smyth, A. R. (2012). Economic valuation of ecosystem services provided by oyster reefs. *BioScience*, 62, 900-909.

Hernandez, A. B., Brumbaugh, R. D., Frederick, P., Grizzle, R., Luckenbach, M. W., Peterson, C. H. & Angelini, C. (2018). Restoring the eastern oyster: how much progress has been made in 53 years? *Frontiers in Ecology and the Environment*, 16, 1-9.

Piazza, B. P., Banks, P. D. & La Peyre, M. K. (2005). The potential for created oyster shell reefs as a sustainable shoreline protection strategy in Louisiana. *Restoration Ecology*, 13, 499-506.

Kitskoudis, V., Kibler, K. M. & Walters, L. J. In review. In-situ measurements of turbulent flow over intertidal natural and degraded oyster reefs in an estuarine lagoon. *Ecological Engineering*.

La Peyre, M. K., Schwarting, L., & Miller, S. (2013). Preliminary assessment of bioengineered fringing shoreline reefs in Grand Isle and Breton Sound, Louisiana. U.S. Geological Survey Open-File Report 2013–1040, 34 p.

La Peyre, M., Furlong, J., Brown, L. A., Piazza, B. P. & Brown, K. (2014a). Oyster reef restoration in the northern Gulf of Mexico: Extent, methods and outcomes. *Ocean and Coastal Management*, 89, 20-28.

La Peyre, M. K., Humphries, A. T., Casas, S. M. & La Peyre, J. F. (2014b). Temporal variation in development of ecosystem services from oyster reef restoration. *Ecological Engineering*, 63, 34-44.

La Peyre, M. K., Serra, K., Joyner, T. A. & Humphries, A. (2015). Assessing shoreline exposure and oyster habitat suitability maximizes potential success for sustainable shoreline protection using restored oyster reefs. *PeerJ* 3: e1317; DOI 10.7717/peerj.1317

Livingston, R. J., Howell, R. L., Niu, X. F., Lewis, F. G. & Woodsum, G. C. (1999). Recovery of oyster reefs (*Crassostrea virginica*) in a gulf estuary following disturbance by two hurricanes. *Bulletin of Marine Science*, 64, 465-483.

MacDonald, M. (2018). Wave monitoring and sedimentation analysis at four oyster castle breakwaters at Gandy's Beach, NJ. For: The Nature Conservancy. New Jersey, US.

Manis, J. E., Garvis, S. K., Jachec, S. M. & Walters, L. J. (2015). Wave attenuation experiments over living shorelines over time: a wave tank study to assess recreational boating pressures. *Journal of Coastal Conservation*, 19, 1-11.

McAfee, D., Bishop, M. J., Yu, T-N. & Williams, G. A. (2018). Structural traits dictate abiotic stress amelioration by intertidal oysters. *Functional Ecology*, 32, 2666-2677.

Moody, J. A. (2012). The relationship between the ribbed mussel (*Geukensia demissa*) and salt marsh shoreline erosion. MSc Thesis. Rutgers University, New Jersey, USA.

Morris, R. L., Konlechner, T. M., Ghisalberti, M. & Swearer, S. E. (2018). From grey to green: Efficacy of eco-engineering solutions for nature-based coastal defence. *Global Change Biology*, 24, 1827-1842.

Narayan, S., Beck, M. W., Reguero, B. G., Losada, I. J., van Wesenbeeck, B., Pontee, N., . . . Burks-Copes, K. A. (2016). The effectiveness costs and coastal protection benefits of natural and nature-based defences. *Plos One*, 11, e0154735.

Reguero, B. G., Beck, M. W., Bresch, D. N., Calil, J. & Meliane, I. (2018). Comparing the cost effectiveness of nature-based and coastal adaptation: A case study from the Gulf Coast of the United States. *Plos One*, 13, e0192132.

Rodriguez, A. B., Fodrie, F. J., Ridge, J. T. Lindquist, N. L., Theuerkauf, E. J., Coleman, S. E., . . . Kenworthy, M. D. (2014). Oyster reefs can outpace sea-level rise. *Nature Climate Change*, 4, 493-497.

Salvador de Paiva, J. N., Walles, B., Ysebaert, T. & Bouma, T. J. (2018). Understanding the conditionality of ecosystem services: The effect of tidal flat morphology and oyster reef characteristics on sediment stabilization by oyster reefs. *Ecological Engineering*, 112, 89-95.

Scyphers, S. B., Powers, S. P., Heck, K. & Byron, D. (2011). Oyster reefs as natural breakwaters mitigate shoreline loss and facilitate fisheries. *Plos One*, 6, e22396.

Servold, K. P., Webb, B. M. & Douglass, S. L. (2015). Effects of low-crested living shoreline breakwaters on wave setup. *Coastal Structures and Solutions to Coastal Disasters: ASCE*.

Spalding, M. D., Ruffo, S., Lacambra, C., Meliane, I., Hale, L. Z., Shepard, C. C., & Beck, M. W. (2014). The role of ecosystems in coastal protection: adapting to climate change and coastal hazards. *Ocean and Coastal Management*, 90, 50-57.

Spiering, D. W., Kibler, K. M. & Kitskoudis, V. (2018). Hydrodynamic change following living shoreline restoration based on a Before-After-Control-Impact experiment. *World Environmental and Water Resources Congress, American Society of Civil Engineers, Hydraulics and Waterways, Water Distribution Systems Analysis, and Smart Water*, 54-64.

Strain, E. M. A., Morris, R. L., Coleman, R. A., Figueira, W. F., Steinberg, P. D., Johnston, E. L. & Bishop, M. J. (2018). Increasing microhabitat complexity on seawalls can reduce fish predation on native oysters. *Ecological Engineering*, 120, 637-644.

Styles, R. (2015). Flow and turbulence over an oyster reef. *Journal of Coastal Research*, 31, 978-985.

Taylor, J. & Bushek, D. (2008). Intertidal oyster reefs can persist and function in a temperate North American Atlantic estuary. *Marine Ecology Progress Series*, 361, 301-306.

Temmerman, S., Meire, P., Bouma, T. J., Herman, P. M. J., Ysebaert, T. & De Vriend, H. J. (2013). Ecosystem-based coastal defence in the face of global change. *Nature*, 504, 79-83.

U.S. Army Corps of Engineers. (2002). Coastal Engineering Manual (Vols. 1110-2-1100). Washington D.C.: U.S. Army Corps of Engineers.

Walles, B., Troost, K., van den Ende, D., Nieuwhof, S., Smaal, A. C. & Ysebaert, T. (2016). From artificial structures to self-sustaining oyster reefs. *Journal of Sea Research*, 108, 1-9.

Walters, L. (2014). Assess oyster reef restoration & develop public outreach materials for long-term protection. Final Report to National Park Service. 63 pp.

Webb, B. M. & Allen, R. J. (2015). Wave transmission through artificial reef breakwaters. Coastal Structures and Solutions to Coastal Disasters: ASCE.

Whitman, E. R. & Reidenbach, M. A. (2012) Benthic flow environments affect recruitment of *Crassostrea virginica* larvae to an intertidal oyster reef. *Marine Ecology Progress Series* 463, 177-191.

Wiberg, P. L., Taube, S. R., Ferguson, A. E., Kremer, M. R. & Reidenbach, M. A. (2018). Wave attenuation by oyster reefs in shallow coastal bays. *Estuaries and Coasts*, 42, 331-347.

Woods, H., Hargis, W. J., Hershner, C. H. & Mason, P. A. M. (2005). Disappearance of the natural emergent 3-dimensional oyster reef system of the James River, Virginia 1871-1948. *Journal of Shellfish Research*, 24, 139-142.

Table 1. Examples of oyster reef living shorelines used throughout the United States of America. Values for reef size are presented as an estimated range of length (L) width (W) and height (H) from smallest to largest projects. WAD/WAU = Wave Attenuating Device/Unit. All examples are from microtidal locations (defined as a tidal range of 0-2 m as per Davies, 1964).

<i>State</i>	<i>Structures used</i>	<i>Size (m)</i>	<i>Tidal height</i>	<i>Example</i>
New Jersey	Bagged shell Oyster castles®	L: 1.8 – 9.1 W: 1.0 – 5.8 H: 0.5 – 1.0	Intertidal
Virginia	Bagged shell Oyster castles® Ready Reef Reefball™	L: 1.2 – 278.9 W: 0.6 – 3.1 H: 0.3 – 1.0	Intertidal Subtidal
Florida	Bagged shell Oyster mats	L: 6 – 83 W: 3 – 10 H: 0.05 – 0.13	Intertidal
Alabama	Loose shell Bagged shell Reefball™ ReefBLK SM WAU®	L: 17.0 – 250.0 W: 2.3 – 6.0 H: 0.5 – 2.0	Intertidal Subtidal

Louisiana	ShoreJAX™		
	Oysterbreak™	L: 25.0 – 9656.0	Subtidal
	Reefball™	W: 1.0 – 6.5	
	ReefBLK SM	H: 0.75 – 1.4	
	WAD®

Table 2. Examples of (a) important design criteria to be addressed from an ecological, engineering or interactive perspective for oyster reef living shorelines where the ecological goal is a self-sustaining oyster reef and the engineering goal is to provide coastal defence; and (b) key research questions that arise from the integration of ecology and engineering to

526 inform when and where oyster reef living shorelines are a viable alternative to traditional
527 structures.

(a) <i>Effect of:</i>	Ecology	Engineering	Interaction
<i>Restored reef presence</i>	Larval supply – availability and timing Habitat suitability (e.g., salinity, hydrology) Trajectory of colonization	Decrease in cross-shore sediment transport Wave attenuation	Influence of oyster metrics (e.g., density, size) on waves and sediment transport Influence of wave energy on oyster persistence (e.g., recruitment, survival, mortality) Sediment accretion and oyster settlement, survival
<i>Reef material</i>	Spat settlement Refuge from predation	Structural integrity	Wave-induced turbulence on spat settlement and how this changes with different reef complexity or rugosity
<i>Reef length (parallel to shore)</i>	Patch size and shape – impacts on reef recruitment (e.g., edge effects)	Enhancement of shore-parallel currents	Influence of oyster metrics (e.g., density, size) on currents
<i>Reef width (perpendicular to shore)</i>	Spatial configuration of patches – impacts on reef recruitment and survival (e.g., edge effects on settlement, food)	Relationship between width of the reef and incident wavelength for wave attenuation	Reef edge effects (e.g., velocity magnitude) on oyster metrics and persistence (e.g., recruitment, survival, mortality)
<i>Reef height / depth</i>	Optimum tidal range and depth for oyster settlement, growth and survival	Wave breaking Wave set-up	Change in wave breaking and set-up with oyster colonization over time

(b) *Key research questions*

What is the optimum environment and reef material required for settlement of oysters?

What is the effect of oyster colonization and growth on reef hydrodynamics?

What is the timeline for oyster reef living shorelines to provide coastal defence?

What is the scale of oyster reef needed for coastal defence?

What factors affect the resilience of oyster populations and is there any risk associated with this?

528

529 **Figure 1.** Coastal protection provided by (a) a traditional bulkhead, (b) a living shoreline
530 with an oyster sill and (c) a living shoreline with a rock sill.

531

532 **Figure 2.** Hypothesized effect on wave attenuation for oyster reef living shorelines that are
533 designed for oysters (a) or waves (b). It is expected that wave attenuation will improve over
534 time with the accretion of oysters under appropriate environmental conditions. In contrast,
535 reefs that are not designed to maximize oyster colonization will have a design life akin to
536 traditional breakwaters. Symbols are courtesy of the Integration and Application Network,
537 University of Maryland Center for Environmental Science (ian.umces.edu/symbols/).

jpe_13390_f1.jpg

jpe_13390_f1a.jpg

jpe_13390_f2.jpg

jpe_13390_f2a.jpg

jpe_13390_f3a.jpg

Minerva Access is the Institutional Repository of The University of Melbourne

Author/s:

Morris, RL;Bilkovic, DM;Boswell, MK;Bushek, D;Cebrian, J;Goff, J;Kibler, KM;La Peyre, MK;McClenachan, G;Moody, J;Sacks, P;Shinn, JP;Sparks, EL;Temple, NA;Walters, LJ;Webb, BM;Swearer, SE

Title:

The application of oyster reefs in shoreline protection: Are we over-engineering for an ecosystem engineer?

Date:

2019-07-01

Citation:

Morris, R. L., Bilkovic, D. M., Boswell, M. K., Bushek, D., Cebrian, J., Goff, J., Kibler, K. M., La Peyre, M. K., McClenachan, G., Moody, J., Sacks, P., Shinn, J. P., Sparks, E. L., Temple, N. A., Walters, L. J., Webb, B. M. & Swearer, S. E. (2019). The application of oyster reefs in shoreline protection: Are we over-engineering for an ecosystem engineer?. JOURNAL OF APPLIED ECOLOGY, 56 (7), pp.1703-1711. <https://doi.org/10.1111/1365-2664.13390>.

Persistent Link:

<http://hdl.handle.net/11343/285713>