Introduction

There has been a rapid increase in the amount of research on wood in rivers (Shields and Gippel, 1995; Abbe and Montgomery, 1996; Montgomery et al., 2003; Swanson, 2003; Brooks et al., 2006; Eaton et al., 2012; Tonkin et al., 2016), and also an increase in the range of regions being studied. Research has expanded from temperate regions (Abbe and Montgomery, 2003) to now include investigations of wood in rivers in tropical (Wohl et al., 2012), arctic (Freschet et al., 2012), and arid regions (Chalmers et al., 2012). Not only has research in different regions expanded, but research into the role of wood in different process zones has increased over the last decade, from headwater streams (Wohl and Jaeger, 2009), to lowland rivers (Brooks and Brierley, 2002), and even to coastal environments (Kennedy and Woods, 2012). Central to this burgeoning work are methods for describing the load and distribution of wood in rivers. A measure of wood load can be used to compare between rivers and along reaches of a river (Brooks et al., 2003; Gurnell, 2013); they can provide targets for restoration (Fox et al., 2003; Fox and Bolton, 2007; Kitchingman et al., 2015), and can be used to investigate the geomorphic or ecologic role of wood in different types of river systems (Nakamura and Swanson, 1994; Andreoli et al., 2007; Jones et al., 2011; Moulin et al., 2011; Collins et al., 2012; Eaton et al., 2012).

Responding to the plethora of different reported measures of wood in rivers, and the expanding environments where wood is being measured, Wohl et al. (2010) called for more consistency in reporting the characteristics of wood loads. They

This is the author manuscript accepted for publication and has undergone full peer review but has not been through the copyediting, typesetting, pagination and proofreading process, which may lead to differences between this version and the Version of Record. Please cite this article as doi: [10.1002/esp.4006](https://doi.org/10.1002/esp.4006)

recommended collecting, and reporting, a set of 35 variables to allow for the comparison of wood loads between different rivers and along the drainage network. Reporting these measures would provide critical data for comparisons between similar and different types of rivers. However, the work on wood loads in rivers has not yet progressed much beyond collecting sets of empirical data from different rivers reaches.

The majority of studies describe the central tendency of a load of wood in a reach as an average or median value, usually expressed as the volume of wood per reporting section (i.e. some sampling length of the channel (usually 100m) or area of the bed (m^2 or Ha)) (Baillie and Davies, 2002; Wohl et al., 2012). Additionally, some measure of variance (e.g. standard deviation, variance, standard error) is reported to describe the variability of wood loads in the reporting sections over the reach. While these parameters are useful, the use of parameters such as the mean and standard deviation which describes a Gaussian (normal) distribution, is only useful if the data can be assumed to fit the Gaussian distribution. However, it is well known that wood is seldom evenly distributed along river channels, and it is often clumped in log jams (Abbe and Montgomery, 2003; Webb and Erskine, 2003, 2005; Eaton et al., 2012), which can result in a non-normal distribution or skewed distribution. To circumvent this issue of non-normal distributions parameters such as the median (rather than the mean), skewness and kurtosis are reported to describe the distribution of wood across the reach. Despite these refinements, we argue that the use of mean wood loads and a standard deviation holds little description of the spatial distribution of

wood in the reach. What is required is a description of wood loads that can reflect both the central tendency and the variability of wood loads along a river or stream reach.

The frequency of naturally occurring phenomena are often described by distributions that allow data to be extrapolated and interpolated. Probability distributions are commonly used in frequency analysis to describe wind speeds, precipitation data, and flood frequency.

We predict that instream wood frequency would be well described by a Weibull distribution. Trees are naturally recruited to rivers by many different processes (see Martin and Benda (2001) and Benda et al. (2003)). Many of these delivery and removal processes are stochastic in both space and time which ultimately result in a clumped distribution of wood within the channel (Abbe and Montgomery, 2003; Webb and Erskine, 2003, 2005). The spatial frequency distribution of wood in any river is a result of the interaction between the frequency distributions of the processes that deliver and remove wood, and the frequency distribution of the size of trees along the river banks. Although never explicitly applied to the distribution of wood in a river, the Weibull distribution has been shown to model well many of the key drivers which govern the load of wood in a river (Table 1). For example, riparian tree growth rates, tree mortality, and transport of wood by floods, are all described by Weibull distributions (Table 1). Gurnell (2007) has suggested that vegetation particles including large wood, in rivers should be considered a form of bed-load, and bed material sediment transport also follows a Weibull distribution (Kondolf and

Adhikari, 2000). Because the factors that drive the distribution of wood loads in a river can be described using a Weibull distribution, we would expect the resulting distribution of wood in a river also to be well described using this distribution.

Therefore, in this paper, after describing the statistical characteristics of the Weibull distribution, we (a) test whether the Weibull distribution provides a good description of wood loads in rivers; and (b) explore the implications of using the Weibull distribution to describe and compare wood loads in rivers.

The Weibull distribution

The probability (f) and cumulative distribution (F) of the two-parameter Weibull distribution (Weibull, 1951) for a set of random variables (x) are:

$$f(x; b, c) = \frac{c}{b} \left(\frac{x}{b}\right)^{c-1} e^{-\left(\frac{x}{b}\right)^c} \quad \text{for } x \geq 0 \quad (1)$$

$$F(x; b, c) = 1 - e^{-\left(\frac{x}{b}\right)^c} \quad \text{for } x \geq 0 \quad (2)$$

where:

x = random variable

b = scale parameter

c = shape parameter

The scale parameter (b) is a function of the central tendency of the data, shifting the central tendency of the distribution along the X axis. The shape parameter (c)

controls the overall shape of the distribution and describes the variation of the data. A smaller shape value indicates a greater deviation away from the mean value, while a larger shape value represents a smaller deviation. Figure 1 illustrates how different values of the shape parameter influence the spread of values (x) and the presence of extreme values in the frequency distribution. For each curve, the scale parameter is held constant ($b = 10$) and the shape parameter is varied. As the shape parameter increases from one to ten, the variability of values decreases and the presence of extreme values decrease. Additionally, the distribution shifts from a highly left-skewed distribution ($c = 1$) to a near normal distribution ($c = 3$) to a right-skewed distribution ($c = 10$).

We hypothesize that when using the Weibull distribution to describe wood loads, the scale (b) parameter will be easily represented through the use of the arithmetic mean of wood loads, and that the shape parameter (c) is representative of the ability of the river to transport wood and therefore representative of the spatial distribution of wood loads in the reach. The spatial distribution of wood is a function of the variable delivery and removal rates of wood in the channel (Gurnell, 2013), and the ability of the river channel to transport and shift wood from one location to another (Bocchiola et al., 2006).

The ability of a river to rearrange wood in the channel is a balance between driving and resisting factors of wood transport in the channel. Previous research has indicated that the higher the stream power (Braudrick and Grant, 2001), and the smaller the ratio between the lengths of logs to the width of the river (length to width

ratio, or L^*), the higher the probability of wood being entrained during high flows (Jacobson et al., 1999b; Wohl and Goode, 2008). Merten et al. (2010) show that predicting wood transport at the individual log scale is a complex problem. Their work identified seven variables to predict wood mobilization during a flood, and that the mobilization of wood is a function of both mechanical factors (L^* , burial, shape of the tree, and shape of the channel), and the hydraulic factors (discharge, stream power, buoyancy of the wood, depth of flows). We posit that the mechanical attributes are resisting factors in transport, and that the hydraulic attributes are driving factors in wood transport. We assume here that L^* is the primary factor in resisting transport, and that stream power (Ω) is the primary factor in driving transport. Additionally, we assume that secondary factors of wood density (ρ_{log}) and channel sinuosity (K) can be used to scale the importance of the primary factors.

We can conceptually assess the effect of the primary factors and the secondary factors on the spatial distribution of wood in a river. For example, if two rivers (A and B) have the same total stream power (Ω), but the L^* for river A is 1.5 and for river B ($L^* = 0.5$) we would expect river B to be able to transport the wood much more easily than river A. Spatially, these two rivers could potentially have the same mean load of wood over the reach, but we would expect to find sections of river B with little or no wood and some sections with medium to large log jams because of the larger ability of river B to transport and rearrange wood within the channel. As a result, river B would have a lower (smaller) scale parameter (c) compared to river A, indicating that the river can easily transport delivered wood through the sections. The

secondary factors scale the importance of each primary factor. If the density of wood ($\rho_{\log}$) is less (i.e. 0.5 kg m^{-3} vs 0.9 kg m^{-3}) the logs would float higher in the column of water meaning that less stream power would be required to move the log.

Additionally, if the river was straight ($K=1$) the L^* of the wood is the primary resisting factor, however in a more sinuous stream ($K=2.5$) the L^* becomes less important as the changing position of the thalweg and cross sectional shape increases the probability that the transporting wood will come in contact with the bed or banks. We hypothesize that a ratio of the resisting factors to the driving factors will be a good predictor variable for the ability of a river to transport wood, and therefore allow the prediction of the Weibull shape parameter based on that relationship. In other words $\text{shape } (c) \propto (L^*/K) / (\Omega/\rho_{\log})$. Where L^* is scaled by the sinuosity of the channel (K) and stream power (Ω) is scaled by the dry density of the wood ($\rho_{\log}$) in transport.

Methods

To test our hypotheses and the application of the Weibull distribution to describing wood loads we use a census of wood loads from six rivers that are relatively undisturbed by humans. We then empirically determine how well the two parameter Weibull distribution describe the frequency and spatial distribution of wood loads across each of the five river reaches. We investigate whether a ratio resisting and driving forces are useful for determining of the shape parameter (c), and whether the arithmetic mean of the wood load tracks well with the scale parameter (b).

Site Descriptions

Instream wood was measured as part of a larger project investigating the role of catchment wide variables in predicting reference wood loads at a reach scale (Kitchingman et al., 2015). Wood loads at the six sites described here were measured between December 2011 and October 2012 during low flow periods. All six rivers are located in the state of Victoria, Australia (Figure 2 and Table 2). The vegetation along the river banks are predominately *Eucalyptus sp.*, *Acacia sp.*, and a few patches of *Salix fragilis* (crack willow). Three of the rivers have their catchments in the Victorian Alps. The Wonnangatta and Thurra Rivers flow to the south of the Alps, with the former passing through small floodplains with a slope of 0.0047 (sinuosity of 1.4), and the latter passing through a temperate rainforest catchment, with a slope of 0.0048 (sinuosity of 1.3). The Ovens River flows north of the Alps (slope of 0.0007 and sinuosity of 2.1), passing onto the Riverine plain where it becomes a tributary to the Murray River. The Aire River and Parker River catchments flow from the Otway Ranges in SW Victoria with slopes of 0.0027 (sinuosity of 1.4), and 0.018 (sinuosity of 1.5) respectively. The Loddon River flows (slope 0.0009 and sinuosity 1.8) north from the Great Dividing Ranges in Central Victoria crossing the Central Riverine plain where it joins the Murray River. The reaches selected for analysis in the study have average bankfull widths ranging from 13 to 65 meters and catchment areas that ranged from 30 to 7758 km². Reach lengths ranged from 1.5 km to 3.0 km, and were selected based on the fact that

these reaches were relatively unmodified, with intact mature riparian vegetation and no record of instream wood removal (see Kitchingman et al. 2015).

Wood load assessment

Instream wood was measured using the rapid assessment methods described in Kitchingman et al. (2013). All instream wood was measured that had a minimum diameter of 0.1 m and a minimum length of 1m. The location of each piece or group of wood was recorded using a Trimble GeoExplorer XT6000 series GPS, coupled with a laser range finder and a Hummingbird 998c SI side imaging sonar system to search for submerged pieces of wood. Each piece or group of wood was classified into one of 16 categories and the volume of wood was calculated following the methods describe in Kitchingman et al. (2015) by measuring diameters of the trunk and limbs in each of the 16 categories and building a regression model to estimate the volume of wood in of each piece or group of wood classified. This approach generated a volume estimate for each mass or piece of wood in the channel. Each location of a log or mass of logs was then mapped in the reach using ArcGIS. The reach was subdivided into 100m reporting sections and the volume of all wood in the section was summed to produce the estimated load of wood for each section ($\text{m}^3/100\text{m}$). Additionally, we calculated the volume of wood per hectare for each of the 100m sections (m^3/ha) as point of comparison as m^3/ha is also a widely reported unit of wood loads. Lastly the wood loads were exported as a table for analysis and distribution fitting in MATLAB.

Resisting and Driving factor ratio calculations

Stream power was calculated by using a series of gauges in the local catchments to develop an area-discharge relationship for the Mean Annual Flood discharge.

Cross-sectional stream power (Rhoads, 1987), or the stream power per unit length of a defined reach is given as $\Omega = \rho g Q_{2.33} S$, where ρ is the density of water (1,000 kg m⁻³), g is the gravitational constant, $Q_{2.33}$ is the widely accepted Mean Annual Flood discharge (Beven and Carling, 1989; Kemp, 2004) calculated from the discharge-area relationship for each catchment, and S is the slope of the reach, used as a proxy for the slope of the water surface during Mean Annual Flood. Sinuosity (K) for each river reach was calculated using ArcGIS by dividing the total reach length by the down valley length.

The length to width ratio (L^*) was calculated using the average bankfull measurements for the reach and then dividing by the average height of the dominant tree species on the bank, as these trees are the most likely source of the large pieces of wood in the reach. The average height of the large trees was extracted from the 2005 Ecological Vegetation Classes (EVC) layers for each reach location (DELWP, 2016). Large trees were determined based on the dominant tree type in the EVC layer. The dominant tree species for each river was used to estimate the dry density of wood (ρ_{log}). Dry densities were estimated using forestry look-up tables for each dominant tree species (DCNR, 1992). Finally, a ratio of the resisting factors

to the driving factors $(L^*/K) / (\Omega/\rho_{log})$ was calculated to provide an estimate of the ability of each river to transport wood through the reaches.

Estimating Weibull parameters

Histograms of the wood load in each section were developed using the Freedman-Diaconis rule to determine bin widths (Bin Size = $2IQR(x)/n^{(1/3)}$, where IQR is the inter quartile range, x is the load of wood in each reporting section, and n is the number of observations (Freedman and Diaconis, 1981). In order to estimate the two parameters of the Weibull distribution we used the maximum likelihood estimate (MLE) method. The MLE is regularly used as a procedure for estimating the Weibull distribution parameters for many different types of datasets (tree diameters, wind speeds, tensile strength, annual discharge), and has been reported to be more efficient and consistent than any other method of parameter estimation (Cohen, 1965; Myung, 2003). MATLAB was used to estimate the parameters (of both reporting units ($m^3/100m$ and m^3/ha), and then the cumulative frequency distribution was constructed using the estimated parameters and the 95 % confidence intervals. The data used to estimate the parameters were then plotted over the top of the cumulative distribution frequency (CDF) curve to visually test for fit. The fitting procedure was accomplished by calculating the cumulative frequency or Weibull plotting position, by ranking the data (X) in ascending order, and assigning rank frequencies ($Fr = R/N+1$) where R is the rank number and N is the total number of

data points. Lastly, the relationship between estimated Weibull parameters (scale and shape) were then tested by fitting lines of best fit through the data points of all the rivers. The arithmetic mean of the wood load for the entire reach was regressed against the scale parameter, and resisting and driving factors ratio was regressed against the shape parameter. The best fit relationships were then plotted on the curves with the 95% confidence interval of fit of each relationship.

Results

Wood loads

Average measured wood loads ranged between 11.4 m³/100m (19.9m³/ha) on the Wonnangatta River to 77.4 m³/100m (204.3 m³/ha) on the Aire River. The other four river resulted in a range of loads; Parker River (43.8 m³/100 and 338.4 m³/ha), Ovens River (49.9 m³/100m and 128.1 m³/ha), Thurra River (53.4 m³/100m and 296.8 m³/ha), and the Lodden River (29.9 m³/100m and 119.5 m³/ha). The total stream power (Table 3) ranged from 269 W m⁻¹ on the Lodden River to 4673 W m⁻¹ on the Wonnangatta. The Aire River and the Ovens River had similar stream powers (1780 and 1470 W m⁻¹ respectively). And the Parker River and Thurra rivers had stream powers of 3537 W m⁻¹ and 814 W m⁻¹ respectively.

L and wood density*

The length to width ratios (L^*) (Table 3) of the largest trees to the bankfull widths ranged from 0.46 on the Wonnangatta River to 2.31 on the Parker River. The Thurra River had a length to width ratio of 1.67, and the Ovens, Loddon, and Aire Rivers had ratios of 0.51, 0.6, and 0.66. The estimated density of logs in each of the rivers was a result of the dominant tree species for that river. The Ovens and Loddon was dominated by *Eucalyptus calamundenses* ($\rho_{\log} = 0.915 \text{ kg m}^{-3}$). The Aire and Parker rivers were dominated by *Eucalyptus viminalis* ($\rho_{\log} = 0.700 \text{ kg m}^{-3}$) and *Nothofagus cunninghamii* ($\rho_{\log} = 0.855 \text{ kg m}^{-3}$) respectively. The Wonnangatta and Thurra Rivers were dominated by *Eucalyptus cypellocarpa* ($\rho_{\log} = 0.715 \text{ kg m}^{-3}$) and *Acacia melanoxylon* ($\rho_{\log} = 0.800 \text{ kg m}^{-3}$) respectively.

Estimated Weibull parameters

Surprisingly, when fitting distributions to both reporting units ($\text{m}^3/100\text{m}$ and m^3/ha) the resulting fits were similar. The scale parameter (central tendency of the data) differed due to the values from each of the reporting units. However, and more importantly, the shape parameter estimated from both data sets was the same regardless if the data was reported in $\text{m}^3/100\text{m}$ or m^3/ha . Due to the fact that the fitted shape parameter did not change between the two reporting units, we only report results of the $\text{m}^3/100\text{m}$ reporting unit.

The distribution of wood loads in the 100m sections (Figure 3) show that the Aire, Loddon and Parker rivers have a near normal distribution of loads across the reach,

while the Ovens River is right skewed and the Thurra River is slightly left skewed. The Wonnangatta River is highly right skewed with many of the 100m reporting sections having a very small load of wood, and a few sections with large log jams. Using the MLE method in MATLAB, a Weibull distribution was fit to the raw data (Figure 3) and the shape and scale parameters were estimated (Table 3). The resulting parameter estimates from the MLE for each of the six wood datasets were used to construct the probability distribution functions (PDF) and cumulative distribution functions (CDF). Overall, the two parameter Weibull distribution described the wood load data very well across all six rivers as illustrated by the plotting position of data against the CDF for each river (Figure 3) as the measured load of wood per 100 m section plots within, or very near to, the 95% confidence intervals of the Weibull CDF for the entire reach.

A comparison of the PDFs of all the rivers together (Figure 4) show that even though average wood loads for the reach are similar between some of the rivers (Ovens, Thurra, and Parker), the spatial distribution of loads is different. Additionally, the comparison of all the PDFs together show the drastic differences in the frequency of loads occurring over each of the six different reaches. The Ovens River distribution has a longer thicker right tail; the Thurra has a narrow range of wood loads in all of the reporting sections; and the Parker had a normal distribution.

The relationship between the arithmetic mean of wood loads in the reach and the estimated scale parameter has a strong linear relationship ($R^2 = 0.99$), showing that the scale parameter is a good measure of central tendency for the load of wood in

the reach (Figure 5a). The relationship between the ability of the river to move and redistribute wood (ratio of resisting and driving factors) shows a logarithmic relationship ($R^2 = 0.73$) with the shape parameter of the distributions (Figure 5b), providing a measure for the uniformity or clumped nature of wood loads in the river. However it should be noted that this relationship only holds if the reporting section (100m) is the same across all rivers. Changing the reporting section length will ultimately result in a different distribution.

Discussion

The use of the two parameter Weibull distribution to describe wood loads in our six rivers appears to be an appropriate application. This method allows for an easy numerical and graphical comparison of not only the central tendency of the data, but also a description of the spatial variation in wood loads along the reach. Each of the six rivers had a different average wood load for the reach. However, in common with wood load measurements reported in the literature, the use of the average load for these six rivers provides little information about the spatial distribution of that wood along the reach. In fitting the Weibull distribution to the measured wood loads, it appears that: 1) the scale parameter provides a good estimate of the average wood load and describes the central tendency of the distribution. The linear relationship allows for a simple estimate of the scale parameter based on the average wood load for the reach. 2) The shape parameter is related to the ability of the river to transport wood and is a useful descriptor of how clumped or un-clumped the wood is.

Additionally, as the relation is logarithmic, it would seem that the spatial distribution

would eventually reach a point where the load would be considered uniform (i.e. small headwater streams).

The Weibull distribution in describing wood loads is a more practical and useful approach compared to comparing the mean value of the load for the reach. For example, the Ovens River and the Thurra River have similar average wood loads (49.9 and 53.4 m³/100m respectively). Simply comparing the means, these rivers appear to be similar. However, obviously due to the differences in the bankfull widths and channel slope the spatial distribution of wood in the two reaches is very different. The load of wood in the Ovens River is right skewed, with most sections having smaller loads than the mean, and a few of the sections having high loads most likely resulting from the presence of log jams as a result of higher transport rates. The Thurra River in contrast has less variability and the majority of wood is not in transport resulting in a fairly uniform load of wood in each section along the reach. These differences are captured by the fitted PDFs (Figure 4) and the Weibull parameter estimates (Table 3).

The use of an average load value for the Wonnangatta River as to describe the wood load would be very misleading as a description of the distribution of wood in the reach as many of the sections in the reach have very low loads due to the high stream power and low length to width ratio. Wood is most likely easily transported where it is later deposited in log jams on the sides of the channel. The Weibull parameters and PDF show that even though the overall load of wood is low, there are a few very large log jams occurring on the river. The data does not show where

the log jams are occurring, but probabilistically we know that we would expect the spatial distribution of wood in the channel to be low loadings in most sections of the reach with small number of large log jams occurring in the reach. The spatial distribution of wood along a reach is just as important as the average wood load in the reach; it drives the availability and type of habitat for aquatic fauna (Abbe and Montgomery, 1996) and the routing of sediment and flow through the channel (Shields and Gippel, 1996; Cadol and Wohl, 2011), influencing the evolution of the channel and floodplain (Collins et al., 2012; Wohl, 2013).

Given the reasonably strong relationship between the shape parameter of the Weibull distribution and the ability of a river to transport and rearrange wood in the channel (Figure 5b), we have developed a conceptual model relating the transport capability of the channel to the shape of the wood load distribution for a reach.

Figure 6 illustrates that in rivers with high transport rates we might expect to see shape parameters on the order of 1. This means that the driving factors of transport are much greater than the resisting factors and therefore wood is transported or removed from the reach easily, and that when log jams form, they are potentially very large (i.e. rafts). Rivers with a shape parameter of ~ 1 are likely to have an L^* value much smaller than one, a relatively straight planform and/or high stream power. In rivers where the driving factors are greater than the resisting factors we would expect the regular formation of large log jams. Large log jams could occur in a channel where the L^* is near one, stream power is high, and the sinuosity is moderate ($K=1.8$). Wood delivered is easily transportable but can become racked in

a log jam. Alternatively we would expect wood loads to fit a shape parameter of 3 when the driving and resisting factors are balanced. This may occur in rivers where there is minimal transport due to the density of wood (White, 1998) or an inability to transport wood (L^* is greater than one). In headwater systems where there is minimal transport and the delivery of wood is driven by catastrophic events (i.e. landslides, avalanches, fires), we would expect the shape parameter to be on the order of 6 to 10, meaning that the spatial distribution of wood is left skewed with wood loads having little variability along the reach and that the resistance factors outweigh the driving factors.

Because of the different delivery and removal mechanisms that act on wood loads in different rivers, we would not expect the relationships developed here between the shape parameter and the resisting and driving factors ratio to hold constant across all different river types and climatic zones. This is due to the fact that we have only tested this method on a single climatic region. However, if enough river reaches were measured for large wood in a range of climatic zones this would allow for the development of either a regional or global shape parameter relationship. Having a regional shape parameter will allow managers and researchers to predict the distribution of wood loads that should be expected in rivers that may have been desnagged or had the banks cleared and the source of wood removed. The Weibull distribution allows for a numerical and graphical comparison of different rivers and reaches, providing managers and researchers the ability to visualize what proportion of sections in a reach they might expect to have loads over a certain value.

Additionally, the application of the Weibull distribution not only has potential in describing wood loads, but also in describing the distribution of log sizes in the river channel. The size of logs in a channel has implications on the available surface area for macroinvertebrates (Kaller and Kelso, 2007). It is likely that this body of literature would benefit through the application of the Weibull distribution of log sizes. The use of the Weibull distribution to characterize the wood in a river would be especially useful in restoration projects, as managers could use the spatial distribution of wood (both loads and sizes) in a natural river and mimic that distribution in their restoration reach.

Conclusion

As research on wood in rivers continues to expand, we need to be able to describe the spatial distribution of wood in a reach. The case study rivers employed here illustrate that a single measurement of an average load is not adequate to describe the spatial heterogeneity of wood loads. A frequency distribution-based approach allows both means and distributions to be compared between rivers and regions, facilitating prediction, extrapolation and interpolation. Theory predicts that the processes that deliver wood to streams and move that wood through streams follow a Weibull distribution. Thus it was reasonable to expect that the wood load in rivers should also follow that distribution, and our results show that this is indeed the case. The flexibility of the two-parameter Weibull distribution means that it can describe

most wood loads in rivers, reflecting not only the average load of wood in a reach, but also spatial distribution of the load.

It appears that the scale parameter of the distribution reflects the arithmetic mean of the wood load, whilst the shape parameter is closely related to the ability of the river channel to transport wood. However, it is unclear to what extent the relationships presented here will extend across different river types and climatic zones. By presenting instream wood loads as a probability and cumulative distributions, we can gain a better understanding of the spatial distribution of wood along the length of a study reach. Additionally this provides managers and researchers with a better tool to describe wood loads from reach to reach and from one region to another.

Acknowledgements

We thank the many people who contributed to the collection of the data used in this project. In particular, Justin O'Mahony, Joanne Kearns, Graeme Hackett, Scott Raymond, Jason Lieschke and Mike Nicol assisted in the collection of field data; Paul Moloney and Nick Bond provided biometric support. Comments by two anonymous reviewers improved the manuscript greatly. This work was funded by the Natural Resources and Water Sector groups of the Department of Environment and Primary Industries, Victoria.

References:

- Abbe, T. D., and Montgomery, D. R., 1996, Large woody debris jams, channel hydraulics and habitat formation in large rivers: Regulated Rivers Research & Management, v. 12, no. 23, p. 201-221.
- Abbe, T. D., and Montgomery, D. R., 2003, Patterns and processes of wood debris accumulation in the Queets river basin, Washington: Geomorphology, v. 51, no. 1–3, p. 81-107.
- Andreoli, A., Comiti, F., and Lenzi, M. A., 2007, Characteristics, distribution and geomorphic role of large woody debris in a mountain stream of the Chilean Andes: Earth Surface Processes and Landforms, v. 32, no. 11, p. 1675-1692.
- Baillie, B. R., and Davies, T. R., 2002, Influence of large woody debris on channel morphology in native forest and pine plantation streams in the Nelson region, New Zealand: New Zealand Journal of Marine and Freshwater Research, v. 36, no. 4, p. 763-774.
- Benda, L., Miller, D., Sias, J., Martin, D., Bilby, R., Veldhuisen, C., and Dunne, T., 2003, Wood recruitment processes and wood budgeting: Ecology and Management of Wood in World Rivers, v. 37, p. 49-73.

Beven, K. J., and Carling, P., 1989, Floods: hydrological, sedimentological and geomorphological implications, John Wiley and Sons Ltd.

Bocchiola, D., Rulli, M. C., and Rosso, R., 2006, Flume experiments on wood entrainment in rivers: *Advances in Water Resources*, v. 29, no. 8, p. 1182-1195.

Braudrick, C. A., and Grant, G. E., 2001, Transport and deposition of large woody debris in streams: a flume experiment: *Geomorphology*, v. 41, no. 4, p. 263-283.

Brooks, A. P., and Brierley, G. J., 2002, Mediated equilibrium: the influence of riparian vegetation and wood on the long-term evolution and behaviour of a near-pristine river: *Earth Surface Processes and Landforms*, v. 27, no. 4, p. 343-367.

Brooks, A. P., Brierley, G. J., and Millar, R. G., 2003, The long-term control of vegetation and woody debris on channel and flood-plain evolution: insights from a paired catchment study in southeastern Australia: *Geomorphology*, v. 51, no. 1–3, p. 7-29.

Brooks, A. P., Howell, T., Abbe, T. B., and Arthington, A. H., 2006, Confronting hysteresis: Wood based river rehabilitation in highly altered riverine landscapes of south-eastern Australia: *Geomorphology*, v. 79, no. 3-4, p. 395-422.

Cadol, D., and Wohl, E., 2011, Coarse sediment movement in the vicinity of a logjam in a neotropical gravel-bed stream: *Geomorphology*, v. 128, no. 3-4, p. 191-198.

Chalmers, A. C., Erskine, W. D., Keene, A. F., and Bush, R. T., 2012, Relationship between vegetation, hydrology and fluvial landforms on an unregulated sand-bed stream in the Hunter Valley, Australia: *Austral Ecology*, v. 37, no. 2, p. 193-203.

Cohen, A. C., 1965, Maximum likelihood estimation in the Weibull distribution based on complete and on censored samples: *Technometrics*, v. 7, no. 4, p. 579-588.

- Collins, B. D., Montgomery, D. R., Fetherston, K. L., and Abbe, T. B., 2012, The floodplain large-wood cycle hypothesis: A mechanism for the physical and biotic structuring of temperate forested alluvial valleys in the North Pacific coastal ecoregion: *Geomorphology*, v. 139, p. 460-470.
- Coomes, D. A., and Allen, R. B., 2007, Mortality and Tree-Size Distributions in Natural Mixed-Age Forests: *Journal of Ecology*, v. 95, no. 1, p. 27-40.
- DCNR, 1992, Forest Management Planners' Manual: Department of Conservation & Natural Resources, Melbourne.
- DELWP, 2016, Biodiversity Interactive Map, <http://www.depi.vic.gov.au/environment-and-wildlife/biodiversity/biodiversity-interactive-map>.
- Dorvlo, A. S. S., 2002, Estimating wind speed distribution: *Energy Conversion and Management*, v. 43, no. 17, p. 2311-2318.
- Eaton, B. C., Hassan, M. A., and Davidson, S. L., 2012, Modeling wood dynamics, jam formation, and sediment storage in a gravel-bed stream: *Journal of Geophysical Research. Earth Surface*, v. 117.
- Fox, M., and Bolton, S., 2007, A Regional and Geomorphic Reference for Quantities and Volumes of Instream Wood in Unmanaged Forested Basins of Washington State: *North American Journal of Fisheries Management*, v. 27, no. 1, p. 342-359.
- Fox, M., Bolton, S., and Conquest, L., 2003, 14. Reference Conditions for Instream Wood in Western Washington: *RESTORATION PUGET SOUND RIVERS* (p), p. 861.
- Freedman, D., and Diaconis, P., 1981, On the histogram as a density estimator: L 2 theory: *Probability theory and related fields*, v. 57, no. 4, p. 453-476.
- Freschet, G. T., Weedon, J. T., Aerts, R., van Hal, J. R., and Cornelissen, J. H. C., 2012, Interspecific differences in wood decay rates: insights from a new short-term method to study long-term wood decomposition: *Journal of Ecology*, v. 100, no. 1, p. 161-170.

Gurnell, A. M., 2007, Analogies between mineral sediment and vegetative particle dynamics in fluvial systems: *Geomorphology*, v. 89, no. 1-2, p. 9-22.

Gurnell, A. M., 2013, 9.11 Wood in Fluvial Systems, *in* Editor-in-Chief: John, F. S., ed., *Treatise on Geomorphology*: San Diego, Academic Press, p. 163-188.

Jacobson, P. J., Jacobson, K. M., Angermeier, P. L., and Cherry, D. S., 1999a, Transport, retention, and ecological significance of woody debris within a large ephemeral river: *Journal of the North American Benthological Society*, p. 429-444.

Jacobson, P. J., Jacobson, K. M., Angermeier, P. L., and Cherry, D. S., 1999b, Transport, retention, and ecological significance of woody debris within a large ephemeral river: *Journal of the North American Benthological Society*, v. 18, no. 4, p. 429-444.

Jones, T. A., Daniels, L. D., and Powell, S. R., 2011, Abundance and Function of Large Woody Debris in Small, Headwater Streams in the Rocky Mountain Foothills of Alberta, Canada: *River Research and Applications*, v. 27, no. 3, p. 297-311.

Kaller, M. D., and Kelso, W. E., 2007, Association of macroinvertebrate assemblages with dissolved oxygen concentration and wood surface area in selected subtropical streams of the southeastern USA: *Aquatic Ecology*, v. 41, no. 1, p. 95-110.

Kemp, I., 2004, Flood channel morphology of a quiet river, the Lachlan downstream from Cowra, southeastern Australia: *Geomorphology*, v. 60, no. 1-2, p. 171-190.

Kennedy, D. M., and Woods, J. L. D., 2012, The influence of coarse woody debris on gravel beach geomorphology: *Geomorphology*, v. 159, p. 106-115.

Kitchingman, A., Tonkin, Z., Ayres, R. M., Lyon, J., Stout, J. C., Rutherford, I. D., and Wilson, P., 2015, Predicting natural instream woody-habitat loads across large river networks: *Marine and Freshwater Research*, p. -.

- Kitchingman, A., Tonkin, Z., and Lyon, J., 2013, A novel approach to spatially assessing instream woody habitat densities across large areas: *Journal of Environmental Management*, v. 128, p. 555-560.
- Kondolf, G. M., and Adhikari, A., 2000, Weibull vs. Lognormal Distributions for Fluvial Gravels: *Journal of sedimentary research*, v. 70, no. 3, p. 456-460.
- Martin, D. J., and Benda, L. E., 2001, Patterns of instream wood recruitment and transport at the watershed scale: *Transactions of the American Fisheries Society*, v. 130, no. 5, p. 940-958.
- Merten, E., Finlay, J., Johnson, L., Newman, R., Stefan, H., and Vondracek, B., 2010, Factors influencing wood mobilization in streams: *Water Resources Research*, v. 46.
- Mishnaevsky Jr, L., and Qing, H., 2008, Micromechanical modelling of mechanical behaviour and strength of wood: State-of-the-art review: *Computational Materials Science*, v. 44, no. 2, p. 363-370.
- Montgomery, D. R., Collins, B. D., Buffington, J. M., and Abbe, T. B., 2003, Geomorphic effects of wood in rivers: *Ecology and Management of Wood in World Rivers*, v. 37, p. 21-47.
- Moulton, B., Schenk, E. R., and Hupp, C. R., 2011, Distribution and characterization of in-channel large wood in relation to geomorphic patterns on a low-gradient river: *Earth Surface Processes and Landforms*, v. 36, no. 9, p. 1137-1151.
- Myung, I. J., 2003, Tutorial on maximum likelihood estimation: *Journal of Mathematical Psychology*, v. 47, no. 1, p. 90-100.
- Nakamura, F., and Swanson, F. J., 1994, Distribution of Coarse Woody Debris in a Mountain Stream, Western Cascade Range, Oregon: *Canadian Journal of Forest Research-Revue Canadienne De Recherche Forestiere*, v. 24, no. 12, p. 2395-2403.
- Rhoads, B. L., 1987, Stream Power Terminology: *Professional Geographer*, v. 39, no. 2, p. 189-195.

Schreuder, H. T., and Swank, W. T., 1974, Coniferous Stands Characterized with The Weibull Distribution: Canadian Journal of Forest Research, v. 4, no. 4, p. 518-523.

Shields, F. D., and Gippel, C. J., 1995, Prediction of Effects of Woody Debris Removal on Flow Resistance: Journal of Hydraulic Engineering-Asce, v. 121, no. 4, p. 341-354.

Shields, F. D., and Gippel, C. J., 1996, Prediction of effects of woody debris removal on flow resistance - Closure: Journal of Hydraulic Engineering-Asce, v. 122, no. 8, p. 471-472.

Someels, G. L., Oderwald, R. G., Harms, W. R., and Langdon, O. G., 1980, Predicting Mortality with a Weibull Distribution: Forest Science, v. 26, no. 2, p. 291-300.

Swanson, F. J., 2003, Wood in rivers: A landscape perspective, *in* Gregory, S. V., Boyer, K. L., and Gurnell, A. M., eds., Ecology and Management of Wood in World Rivers, Volume 37, p. 299-313.

Taylor, S. E., Bender, D. A., Kline, D. E., and Kline, K. S., 1992, COMPARING LENGTH EFFECT MODELS FOR LUMBER TENSILE-STRENGTH: Forest products journal, v. 42, no. 2, p. 23-30.

Tonkin, Z., Kitchingman, A., Ayres, R. M., Lyon, J., Rutherford, I. D., Stout, J. C., and Wilson, P., 2016, Assessing the Distribution and Changes of Instream Woody Habitat in South-Eastern Australian Rivers: River Research and Applications, p. n/a-n/a.

Webb, A. A., and Erskine, W. D., 2003, Distribution, recruitment, and geomorphic significance of large woody debris in an alluvial forest stream: Tonghi Creek, southeastern Australia: Geomorphology, v. 51, no. 1-3, p. 109-126.

Webb, A. A., and Erskine, W. D., 2005, Natural variability in the distribution, loading and induced scour of large wood in sand-bed forest streams: River Research and Applications, v. 21, no. 2-3, p. 169-185.

Weibull, W., 1951, A STATISTICAL DISTRIBUTION FUNCTION OF WIDE APPLICABILITY: Journal of applied mechanics, v. 18, no. 3, p. 293-297.

White, K., 1998, Stability of instream large woody debris [Honours: The University of Melbourne.

Wohl, E., 2013, Floodplains and wood: Earth-Science Reviews, v. 123, no. 0, p. 194-212.

Wohl, E., Bolton, S., Cadol, D., Comiti, F., Goode, J. R., and Mao, L., 2012, A two end-member model of wood dynamics in headwater neotropical rivers: Journal of Hydrology, v. 462, p. 67-76.

Wohl, E., Genderelli, D. A., Dwire, K. A., Ryan-Burkett, S. E., Young, M. K., and Fausch, K. D., 2010, Large in-stream wood studies: a call for common metrics: Earth Surface Processes and Landforms, v. 35, no. 5, p. 618-625.

Wohl, E., and Goode, J. R., 2008, Wood dynamics in headwater streams of the Colorado Rocky Mountains: Water Resources Research, v. 44, no. 9.

Wohl, E., and Jaeger, K., 2009, A conceptual model for the longitudinal distribution of wood in mountain streams: Earth Surface Processes and Landforms, v. 34, no. 3, p. 329-344.

Tables

Table 1: List of mechanisms that can be modelled by Weibull distributions and the delivery and removal mechanisms of wood to rivers that are affected by these mechanisms

Mechanism modelled by Weibull distribution	Delivery/Removal Process	References
<ul style="list-style-type: none"> Flood frequency 	Bank erosion, transport of wood in/out of reach	(Jacobson et al., 1999a; Braudrick and Grant, 2001)
<ul style="list-style-type: none"> Tree stem diameter in stands 	Affects the volume of standing stock available for delivery to the river	(Cohen, 1965; Schreuder and Swank, 1974; Coomes and Allen, 2007)
<ul style="list-style-type: none"> Tree mortality 	Chronic/acute mortality rates of trees	(Somers et al., 1980; Coomes and Allen, 2007)
<ul style="list-style-type: none"> Wind speeds 	wind throw of trees and limbs	(Dorvlo, 2002)
<ul style="list-style-type: none"> Breakage of wood materials 	Mechanical breakdown and removal of wood from reach (i.e. shear strength of wood)	(Taylor et al., 1992; Mishnaevsky Jr and Qing, 2008)
<ul style="list-style-type: none"> Sediment size distributions 	Transport and breakage of vegetation in river	(Kondolf and Adhikari, 2000; Gurnell, 2007)

Table 2: Geomorphic variables for each site, Average large tree height was used to calculate the length to width ratio for large trees in the channel.

River	Catchment Area (km ²)	Valley Slope (m/m)	BFW (SD) (m)	Reach length (m)	Average Large Tree height (m)
Aire	94	0.0027	38 (7.3)	2000	25

Parker	30	0.018	13 (6.9)	1500	30
Ovens	3258	0.0007	39 (7.4)	2000	20
Wonnangatta	968	0.0047	65 (13.6)	3000	30
Thurra	121	0.0048	18 (4.6)	1500	30
Loddon	7758	0.0009	25 (25.2)	2000	25

Table 3: Wood load results including Mean load (both m³/100m and m³/ha, Stream power, L* Sinuosity, and wood density, Estimated Weibull distribution parameters Scale, Shape and 95% confidence intervals for each parameter. The Weibull parameter shape estimates were the same for both types of reporting units of wood loads (m³/100m and m³/ha)

River	Ave. Wood load m ³ /100m	Ave. Wood load (m ³ /ha)	Ω (Wm ⁻¹)	L*	K	$\rho_{\log}$	Weibull Parameter estimates (m ³ /100m)			
							Scale (b)	Shape (c)	95 percent conf. int. for Scale (high/low)	95 percent conf. int. for Shape (high/low)
Aire	77.4	204.3	1781	0.66	1.4	0.700	86.9	3.0	(101.3 / 74.5)	(4.2 / 2.2)

Parker	43.8	338.4	3537	2.31	1.5	0.855	49.2	3.1	(58.3 / 41.5)	(4.7 / 2.1)
Ovens	49.9	128.1	1471	0.51	2.1	0.915	56.4	2.2	(69.3 / 45.9)	(3.0 / 1.6)
Wonnangatta	11.4	19.9	4673	0.46	1.4	0.750	8.3	0.6	(15.7 / 4.3)	(0.8 / 0.4)
Thurra	53.4	296.8	814	1.67	1.3	0.900	56.3	9.6	(59.5 / 53.2)	(14.4 / 6.4)
Loddon	29.9	119.5	269	0.60	1.8	0.915	33.1	3.8	(37.3 / 29.3)	(5.3 / 2.7)

Author Manuscript

$$(\Omega/\rho_{\log}) \gg (L^*/K)$$

$$(\Omega/\rho_{\log}) \succsim (L^*/K)$$

$$(\Omega/\rho_{\log}) \approx (L^*/K)$$

$$(\Omega/\rho_{\log}) < (L^*/K)$$

$$(\Omega/\rho_{\log}) \ll (L^*/K)$$

High rate of removal
from each 100 m section

Low rate of removal
from each 100 m section

Minerva Access is the Institutional Repository of The University of Melbourne

Author/s:

Stout, JC;Rutherford, I;Grove, J;Webb, JA;Kitchingman, A;Tonkin, Z

Title:

Using the Weibull distribution to improve the description of riverine wood loads

Date:

2017-03-30

Citation:

Stout, J. C., Rutherford, I., Grove, J., Webb, J. A., Kitchingman, A. & Tonkin, Z. (2017). Using the Weibull distribution to improve the description of riverine wood loads. EARTH SURFACE PROCESSES AND LANDFORMS, 42 (4), pp.647-656. <https://doi.org/10.1002/esp.4006>.

Persistent Link:

<http://hdl.handle.net/11343/291636>