



Minerva Access is the Institutional Repository of The University of Melbourne

Author/s:

Quevedo, DE;Nesic, D

Title:

Robust stability of packetized predictive control of nonlinear systems with disturbances and Markovian packet losses

Date:

2012-08-01

Citation:

Quevedo, D. E. & Nesic, D. (2012). Robust stability of packetized predictive control of nonlinear systems with disturbances and Markovian packet losses. *AUTOMATICA*, 48 (8), pp.1803-1811. <https://doi.org/10.1016/j.automatica.2012.05.046>.

Persistent Link:

<https://hdl.handle.net/11343/299565>

# Robust Stability of Packetized Predictive Control of Nonlinear Systems with Disturbances and Markovian Packet Losses <sup>★</sup>

Daniel E. Quevedo <sup>a</sup>, Dragan Nešić <sup>b</sup>

<sup>a</sup>*School of Electrical Engineering & Computer Science, The University of Newcastle, NSW 2308, Australia*

<sup>b</sup>*Department of Electrical and Electronic Engineering, The University of Melbourne, Parkville, VIC 3052*

---

## Abstract

We study a predictive control formulation for uncertain discrete-time non-linear uniformly continuous plant models where controller output data is transmitted over an unreliable communication channel. The channel introduces Markovian data-loss and does not provide acknowledgments of receipt. To achieve robustness with respect to dropouts, at every sampling instant the controller transmits packets of data. These contain possible control inputs for a finite number of future time instants, and minimize a finite horizon cost function. At the actuator side, received packets are buffered, providing the plant inputs. Within this context, we adopt a stochastic Lyapunov function approach to establish stability results of the networked control system. A distinguishing aspect of this work is that it considers situations where the maximum number of consecutive packet dropouts has unbounded support.

*Key words:* Control over networks, predictive control, packet dropouts, non-linear systems, stochastic stability.

---

## 1 Introduction

Motivated by both practical and also theoretical aspects, significant research has concentrated on Networked Control Systems (NCSs), as documented, e.g., in [1]. In a NCS, plant and controller communicate via a network which may be shared with other applications. This simplifies the cabling (especially if the network is wireless) and, thus, increases overall system reliability. However, since general purpose network platforms were not originally designed for applications with critical timing requirements, their use for closed-loop control presents some serious challenges. The network itself is a dynamical system that exhibits characteristics which traditionally have not been taken into account in control system design. In addition to being quantized, transmitted data may be affected by time delays and data-dropouts. Thus, in a NCS links are not transparent, often constituting a significant performance bottleneck. Various models have been utilized to describe time-delays and packet dropouts

in NCSs. For example, suitable deterministic boundedness assumptions can be used to derive sufficient conditions for deterministic stability [2–8]. A simple stochastic approach considers network effects as independent and identically distributed (i.i.d.) random variables [9–22]. However, fading communication channel gains and network congestion levels are, in general, correlated [23–25]. This motivates the adoption of, more general, (finite) Markov chain models [26–33].

An important feature of many communication protocols is that data is sent in large time-stamped packets. This opens the possibility to conceive NCS architectures in which *packets of data* containing finite sequences are sent through the network. Through buffering and appropriate selection logic at the receiver node, time delays and packet dropouts can to some extent be compensated for [34–36]. Here, model predictive control (MPC) [37] becomes a natural choice for tackling controller to actuator links, since potential plant input values over a finite horizon are readily available [38]. Deterministic stability results of such *packetized predictive control* (PPC) schemes have been obtained in [39–41] for cases where the maximum number of consecutive packets dropouts is bounded, and in [42] for networks with bounded time-delays. Despite the widespread use of stochastic models in the communications community, to date only our own papers [43, 44] have studied stochastic stability of PPC. Whilst [43] focuses on quantized control of perturbed LTI systems with i.i.d. dropouts, [44] considers nonlinear sys-

---

<sup>★</sup> This research was supported under Australian Research Council's Discovery Projects funding scheme (project number DP 0988601). The second author was supported by the ARC Discovery Project (DP 1094326) and Future Fellowship (FT 0990727). A preliminary version of parts of this paper was presented at the 8th IFAC Symposium on Nonlinear Control Systems. Corresponding author D. E. Quevedo. Tel. +61-2-49217072. Fax +61-2-49601712.

*Email addresses:* dquevedo@ieee.org (Daniel E. Quevedo), d.nesic@unimelb.edu.au (Dragan Nešić).




Fig. 1. NCS Architecture with Packet Dropouts and Buffering

tems without disturbances in the presence of i.i.d. dropouts.

In the present work we study a PPC formulation for discrete-time non-linear plant models with disturbances, where optimizing sequences are transmitted over an unreliable communication channel, see Fig. 1. The controller is designed without knowledge of the packet dropout distribution and does not require acknowledgments of receipt. We combine elements of the PPC model of [40] with stochastic stability analysis [45, 46] to establish sufficient conditions for the optimal MPC value function to constitute a stochastic Lyapunov function of the NCS *at the successful transmission instants*. We then show how this property ensures stochastic stability of the NCS. Our stability results apply to NCSs with Markovian packet dropouts and nonlinear plant models with disturbances. Disturbances and times between successful transmissions are allowed to have unbounded support.

**Notation** We write  $\mathbb{R}$  for the real numbers,  $\mathbb{R}_{>0}$  for  $(0, \infty)$ ,  $\mathbb{N}$  for  $\{1, 2, \dots\}$ , and  $\mathbb{N}_0$  for  $\mathbb{N} \cup \{0\}$ . The  $p \times p$  identity matrix is denoted via  $I_p$ ;  $0_p \triangleq 0 \cdot I_p$ ;  $\{y\}_{\mathbb{K}} = \{y(\ell) : \ell \in \mathbb{K}\}$ , and

$$\{y\}_{\ell_1}^{\ell_2} = \begin{cases} \{y(\ell_1), \dots, y(\ell_2)\} & \text{if } \ell_1 \leq \ell_2, \\ \{\} & \text{if } \ell_1 > \ell_2. \end{cases}$$

We adopt the convention  $\sum_{k=\ell_1}^{\ell_2} a_k = 0$ , if  $\ell_1 > \ell_2$  and irrespective of  $a_k$ . The norm of a vector  $x$  is denoted  $|x|$ . To denote the probability of an event  $\Omega$ , we write  $\Pr\{\Omega\}$ . The conditional probability of  $\Omega$  given  $\Gamma$  is denoted via  $\Pr\{\Omega | \Gamma\}$ . The expected value of a random variable  $\nu$  given  $\Gamma$ , is denoted by  $\mathbf{E}\{\nu | \Gamma\}$ , whereas for the unconditional expectation we will write  $\mathbf{E}\{\nu\}$ . We use the same notation for random variables and their realizations.

## 2 NCS Architecture

We consider (possibly unstable) systems with state  $x \in \mathbb{R}^n$  and constrained input  $u \in \mathbb{U} \subseteq \mathbb{R}^p$ ,  $0 \in \mathbb{U}$ , described via:

$$x(k+1) = f(x(k), u(k), w(k)), \quad k \in \mathbb{N}_0, \quad (1)$$

where  $f(0, 0, 0) = 0$ . The initial state  $x(0)$  is arbitrarily distributed (with possibly unbounded support) and the disturbance  $\{w\}_{\mathbb{N}_0}$  is i.i.d., but otherwise arbitrarily distributed.<sup>1</sup>

<sup>1</sup> Note that our disturbance model serves to describe a class of NCSs with quantized inputs [43]. Our results in Section 5 require




Fig. 2. Markov Packet Dropout Model

**Network effects** Our interest lies in clock-driven networks situated between controller output and plant input. All data to be transmitted is sent in large time-stamped packets. The network is affected by transmission errors (for example, due to channel fading and congestion), which are in general correlated in time and introduce packet-dropouts [23–25]. This motivates us to model the network as an erasure channel and to characterize transmission effects via the following time-homogeneous binary Markov process  $\{d\}_{\mathbb{N}_0}$ :

$$d(k) \triangleq \begin{cases} 1 & \text{if packet-dropout occurs at instant } k, \\ 0 & \text{if packet-dropout does not occur at instant } k, \end{cases} \quad (2)$$

where the transition probabilities are given by, see Fig. 2:

$$\begin{aligned} \Pr\{d(k+1) = 0 | d(k) = 0\} &= q \\ \Pr\{d(k+1) = 1 | d(k) = 0\} &= 1 - q \\ \Pr\{d(k+1) = 1 | d(k) = 1\} &= p \\ \Pr\{d(k+1) = 0 | d(k) = 1\} &= 1 - p. \end{aligned} \quad (3)$$

The associated *failure rate* is  $1 - q \in (0, 1)$ , whereas the *recovery rate* is given by  $1 - p \in (0, 1)$ . The values  $q \approx 1$  and  $p \approx 0$ , thus, describe a more reliable network;  $q \approx 0$  and  $p \approx 1$  refer to a network more prone to dropouts. The model (3) incorporates temporal correlations of network conditions. It is therefore more general and realistic than i.i.d. Bernoulli models. In fact, the i.i.d. dropout model corresponds to the special case where  $q = 1 - p$ , in which case:

$$\Pr\{d(k) = 1\} = p, \quad \Pr\{d(k) = 0\} = 1 - p, \quad (4)$$

where  $p$  is the *dropout-rate*. In practice,  $p$  and  $q$  are not known exactly. Accordingly, in the present work our focus is on situations where the controller does not have knowledge about  $p$  and  $q$ . (Of course, closed loop stability will depend upon these parameters, see Sections 5 and 6.)

As foreshadowed in the introduction, at each time instant  $k$  and for plant state  $x(k)$ , the packetized predictive controller sends a control packet, say  $\tilde{u}(x(k))$ , to the plant input node. To achieve good performance despite unreliable communication,  $\tilde{u}(x(k))$  contains constrained tentative control inputs

that  $\mathbf{E}\{|x(0)|^s\}$  and  $\mathbf{E}\{|w(k)|^s\}$  be bounded for some  $s > 0$ .

for a finite number of  $N$  future time instants, i.e., we have

$$\vec{u}(x(k)) = \begin{bmatrix} u_0(x(k)) \\ u_1(x(k)) \\ \vdots \\ u_{N-1}(x(k)) \end{bmatrix} \in \mathbb{U}^N \subseteq \mathbb{R}^{pN}. \quad (5)$$

At the actuator side, the received packets are buffered, providing the plant inputs, see Fig. 1.

**Buffering** The buffering mechanism amounts to a parallel-in serial-out shift register, which acts as a safeguard against dropouts. The buffer state,  $b(k) \in \mathbb{U}^N$ , is overwritten whenever a valid (i.e., error-free and undelayed) control packet arrives. Actuator values are sequentially passed on to the plant until the next valid control packet is received. Thus,

$$\begin{aligned} b(k) &= d(k)Sb(k-1) + (1-d(k))\vec{u}(k), \\ u(k) &= e_1^T b(k) \end{aligned} \quad (6)$$

where  $b(0) = 0$  and where  $S$  and  $e_1$  are defined via:

$$S \triangleq \begin{bmatrix} 0_p & I_p & 0_p & \dots & 0_p \\ \vdots & \ddots & \ddots & \ddots & \vdots \\ 0_p & \dots & 0_p & I_p & 0_p \\ 0_p & \dots & \dots & 0_p & I_p \\ 0_p & \dots & \dots & \dots & 0_p \end{bmatrix}, \quad e_1 \triangleq \begin{bmatrix} I_p \\ 0_p \\ \vdots \\ 0_p \end{bmatrix}. \quad (7)$$

**Remark 1 (Holding the control input)** *The choice of the matrix  $S$  in (7) corresponds to setting the buffer state to zero if no data is received over  $N$  consecutive instants. Alternatively, if one wished to hold the latest value, one could set the “last” element of  $S$  equal to  $I_p$ ; see also [27, 47].*  $\square$

**Remark 2 (Dropouts of State Measurements)** *Our ideas can be readily extended to also encompass dropouts of the state measurements. In fact, if the controller only calculates control packets whenever state measurements are successfully received, then our subsequent analysis still holds. The only modification needed is that the dropout process  $\{d\}_{\mathbb{N}_0}$  include both links, i.e., we set  $d(k) = 0$  if and only if both  $x(k)$  and  $\vec{u}(k)$  are successfully transmitted; c.f., (2).*  $\square$

### 3 Packetized Predictive Control

Plant inputs are designed without knowledge on the dropout distributions and on whether previous packets were successfully transmitted. The control packets  $\vec{u}(x(k))$  in (5) are formed by adapting the ideas underpinning MPC. More precisely, at each time instant  $k$ , the following cost function is

minimized:

$$J(\vec{u}', x(k)) \triangleq F(x'(N)) + \sum_{\ell=0}^{N-1} L(x'(\ell), u'(\ell)). \quad (8)$$

The cost function in (8) examines predictions of the plant model (1) over a finite horizon of length  $N$ , which is taken equal to the buffer size. To provide a method with manageable computational complexity, the predicted state trajectories do not take into account packet-losses or disturbances and are, thus, generated by the nominal model

$$x'(\ell+1) = f(x'(\ell), u'(\ell), 0), \quad \ell \in \{0, 1, \dots, N-1\}$$

starting from  $x'(0) = x(k)$  and where the constrained entries in  $\vec{u}' = [(u'(0))^T \dots (u'(N-1))^T]^T \in \mathbb{U}^N$  are the associated tentative plant inputs. Predicted quantities are penalized via the per-stage weighting function  $L(\cdot, \cdot)$  and the terminal weighting  $F(\cdot)$ . These design variables allow one to trade-off control performance versus control effort. As in control loops without dropouts [37], the choices made for  $L(\cdot, \cdot)$ ,  $F(\cdot)$  and  $N$  influence closed loop stability. This issue will be further examined in Sections 5 and 6.

The control packet  $\vec{u}(x(k))$  is set equal to the optimizer

$$\vec{u}(x(k)) \triangleq \arg \min_{\vec{u}' \in \mathbb{U}^N} J(\vec{u}', x(k)) \quad (9)$$

and is sent through the network to the buffer, see Fig. 1. Following the receding horizon optimization idea, at the next sampling step and given  $x(k+1)$ , the horizon is shifted by one and another optimization is carried out, providing

$$\vec{u}(x(k+1)) = \arg \min_{\vec{u}' \in \mathbb{U}^N} J(\vec{u}', x(k+1)),$$

sequence, which is transmitted to the buffer. This procedure is repeated *ad infinitum*. Note that  $\vec{u}(x(k))$  in (9) contains constrained tentative plant input values for instants  $\{k, \dots, k+N-1\}$ . If  $\vec{u}(x(k))$  is received at time  $k$ , then these values are written into the buffer and implemented sequentially until some future (valid) control packet arrives. Whilst  $\vec{u}(x(k))$  is found by evaluating open-loop predictions (and not closed-loop policies), the resultant control policy is a closed-loop one. Indeed, the loop is closed at all successful transmission instants, i.e., where  $d(k) = 0$ .

### 4 NCS Model at successful transmission instants

Our subsequent analysis extends the approach of [40] to a stochastic setting.<sup>2</sup> We denote the time instants where there are no packet-dropouts (i.e., where  $d(k) = 0$ ) via

$$\mathbb{K} = \{k_i\}_{i \in \mathbb{N}_0} \subseteq \mathbb{N}_0, \quad k_{i+1} > k_i, \quad \forall i \in \mathbb{N}_0 \quad (10)$$

<sup>2</sup> Our ideas are also related to methods used to study randomly sampled systems [32, 48], and to the averaging technique of [7, 8].

and define  $\Delta(i) \triangleq k_{i+1} - k_i$ , where  $i \in \mathbb{N}_0$ . For ease of exposition, we will assume that the first successful transmission instant occurs at  $k = 0$ , thus,  $k_0 = 0$  and  $\Delta(0) = k_1$ . Consequently,  $\{\Delta\}_{\mathbb{N}_0}$  is i.i.d. with distribution

$$\Pr\{\Delta(i) = j\} = \begin{cases} q & \text{if } j = 1, \\ (1-q)(1-p)p^{j-2} & \text{if } j \geq 2, \end{cases} \quad (11)$$

see also [32]. As a particular case of (11), if the dropout process is i.i.d. Bernoulli distributed as in (4), then we have:

$$\Pr\{\Delta(i) = j\} = (1-p)p^{j-1}, \quad \forall j \in \mathbb{N}. \quad (12)$$

It is convenient to introduce the iterated *open-loop* mapping:

$$f_{ol}^j(x, \{\varpi\}_0^{j-1}) \triangleq f(f_{ol}^{j-1}(x, \{\varpi\}_0^{j-2}), 0, \varpi(j-1))$$

for  $j \in \mathbb{N}$ , and where  $f_{ol}^0(x, \{\varpi\}_0^{-1}) \triangleq x$ . We also define the iterated mappings with inputs<sup>3</sup>  $\{\varpi\}_0^{j-1}$ :

$$f^j(x, \{\varpi\}_0^{j-1}) \triangleq f(f^{j-1}(x, \{\varpi\}_0^{j-2}), u_{j-1}(x), \varpi(j-1)), \quad (13)$$

for  $j \in \{1, \dots, N\}$ , and where we set  $f^0(x, \{\varpi\}_0^{-1}) \triangleq x$ .

Given the buffering mechanism, see (6), (9) and (5), it is easy to see that the plant state at  $k_i \in \mathbb{K}$  is characterized via:

$$x(k_{i+1}) = \begin{cases} f^{\Delta(i)}(x(k_i), \{w\}_{k_i}^{k_{i+1}-1}) & \text{if } \Delta(i) \leq N, \\ f_{ol}^{\Delta(i)-N}(x(k_i + N), \{w\}_{k_i+N}^{k_{i+1}-1}) & \text{if } \Delta(i) \geq N. \end{cases} \quad (14)$$

where  $x(k_i + N) = f^N(x(k_i), \{w\}_{k_i}^{k_i+N-1})$ .

It is important to emphasize that, since  $\{w\}_{\mathbb{N}_0}$  and  $\{\Delta\}_{\mathbb{N}_0}$  are i.i.d., the system state sequence, at the instants of successful transmission  $\{x\}_{\mathbb{K}}$ , is Markovian. ( $\{x\}_{\mathbb{N}_0}$  is in general not Markovian.) This observation is fundamental for the stability analysis of Section 5.

**Remark 3 (Relationship to previous works)** *A key difference between the current situation and that studied in articles such as [20, 21, 28, 36, 39, 40] is that the results in the latter works require that  $\Delta(i)$  be bounded, for all  $i \in \mathbb{N}_0$ . In the present work, we remove this assumption by allowing the maximum number of consecutive packet dropouts to have unbounded support, see (12). For that purpose, we extend our recent work documented in [43] to encompass non-linear plant models and Markovian dropouts.*  $\square$

<sup>3</sup> For example, we have  $f^1(x, \varpi(0)) = f(x, u_0(x), \varpi(0))$  and  $f^2(x, \{\varpi\}_0^1) = f(f(x, u_0(x), \varpi(0)), u_1(x), \varpi(1))$ .

## 5 Stochastic Stability of the NCS

Due to disturbances and packet dropouts, the system state  $\{x\}_{\mathbb{N}_0}$  becomes a random process. To establish closed loop stability results, we will adopt the stochastic Lyapunov approach, as described in [45], and study the optimal costs  $V(x) \triangleq J(\bar{u}(x), x)$ . These are based upon predictions which use the nominal plant model (1) without disturbances and with inputs taken from  $\bar{u}(x)$ , see (9). In fact, we have:

$$V(x) = F(\bar{f}^N(x)) + \sum_{\ell=0}^{N-1} L(\bar{f}^\ell(x), u_\ell(x)), \quad (15)$$

where, see (13),

$$\bar{f}^\ell(x) \triangleq f^\ell(x, \{0, \dots, 0\}), \quad \forall \ell \in \{0, 1, \dots, N\}. \quad (16)$$

To derive our results, we will make some assumptions on the cost function and on the class of plant models considered.

**Assumption 1** *There exist  $\alpha_F, \alpha_L, b, c \in \mathbb{R}_{>0}$ , such that, for all  $(x, u) \in \mathbb{R}^n \times \mathbb{U}$ ,*

$$\alpha_F |x|^b \leq F(x), \quad F(0) = 0, \quad (17a)$$

$$\alpha_L |x|^c \leq L(x, u), \quad L(0, 0) = 0. \quad (17b)$$

**Assumption 2** *The plant model and weighting functions are uniformly continuous, i.e.,  $\exists \lambda_x, \lambda_w, \lambda_L, \lambda_F, s \in \mathbb{R}_{>0}$ :*

$$|f(x, u, w) - f(z, u, 0)|^s \leq \lambda_x |x - z|^s + \lambda_w |w|^s, \quad (18a)$$

$$|L(x, u) - L(z, u)| \leq \lambda_L |x - z|^s, \quad (18b)$$

$$|F(x) - F(z)| \leq \lambda_F |x - z|^s. \quad (18c)$$

for all  $(x, z, u, w) \in \mathbb{R}^n \times \mathbb{R}^n \times \mathbb{U} \times \mathbb{R}^m$ .  $\square$

**Assumption 3** *There exists a constrained control law  $\kappa_f: \mathbb{R}^n \rightarrow \mathbb{U}$  such that for the nominal plant model:*

$$F(f(x, \kappa_f(x), 0)) - F(x) + L(x, \kappa_f(x)) \leq 0, \quad (19)$$

for all  $x \in \mathbb{R}^n$ .  $\square$

Assumptions 1 to 3 (and variations thereof) have been extensively used for establishing stability of predictive control loops (without dropouts); see, e.g., [37]. The policy  $\kappa_f(\cdot)$  in (19) can be regarded as a stabilizing law for the nominal plant model, which is not necessarily implemented. Assumption 4, stated below, is specific to the NCS architecture studied. It amounts to an upper bound of  $p$ , see (3), for a given plant model, or, conversely, to an upper bound on the rate of growth of  $x$  when left in open loop, for a given  $p$ .

**Assumption 4** *There exist  $\gamma \in [1, 1/p)$  and  $\eta, v \in \mathbb{R}_{>0}$  such that*

$$F(f(x, 0, w)) \leq \gamma F(x) + \eta |w|^v, \quad (20)$$

for all  $(x, w) \in \mathbb{R}^n \times \mathbb{R}^m$ .  $\square$

Before proceeding, we make the following observations:

**Lemma 4** *Suppose that Assumption 3 holds. Then:*

$$L(x, u_0(x)) \leq V(x) \leq F(x), \quad \forall x \in \mathbb{R}^n. \quad (21)$$

**PROOF.** Lemma 2.15 in [37] establishes  $V(x) \leq F(x)$ . The other inequality in (21) follows directly from (15).  $\square$

**Lemma 5** *Suppose that Assumptions 1 and 2 hold with  $b = s$  and that*

$$p < \frac{\alpha_F}{\lambda_F \lambda_x}. \quad (22)$$

*Then Assumption 4 is satisfied with  $\gamma = \lambda_F \lambda_x / \alpha_F$ ,  $\eta = \lambda_F \lambda_w$  and  $v = s$ .*

**PROOF.** Since  $f(0, 0, 0) = 0$ , we can use (18) to obtain  $F(f(x, 0, w)) = |F(f(x, 0, w))| \leq \lambda_F |f(x, 0, w)|^s = \lambda_F |f(x, 0, w) - f(0, 0, 0)|^s \leq \lambda_F \lambda_x |x|^s + \lambda_F \lambda_w |w|^s$ . The result follows from using (17a) and (21).  $\square$

A particular case of (22) results when the plant model is scalar LTI with system pole  $a$  and  $F(x) = |x|$ , the absolute value. Here, one can choose  $\lambda_F = \alpha_F = s = b = 1$ , and  $\lambda_x = |a|$ . Thus, (22) becomes  $|a|p < 1$ , which is necessary and sufficient for mean-square stabilizability in the case where dropouts are i.i.d. as in (4); see, e.g., [15, 33, 49].

Our first results, stated as Proposition 6 and Corollary 7, establish sufficient conditions for exponential convergence of  $\{\mathbf{E}\{|x(k_i)|^c\}\}$  for  $k_i \in \mathbb{K}$ . This property is then used, in Theorem 8, for establishing asymptotic convergence of  $\{\mathbf{E}\{|x(k)|^c\}\}$  at all time instants  $k \in \mathbb{N}_0$ . In both cases, convergence is to a bounded set containing the origin, whose size is proportional to the moment  $\mathbf{E}\{|w(k)|^s\}$ . To formulate our results, we define the following quantities:

$$\psi_\ell \triangleq \frac{1 - p\gamma}{p^{\ell-1}(1-q)(\gamma-1)}, \quad \ell \in \mathbb{N} \quad (23)$$

$$\phi(x) \triangleq L(x, u_0(x)) - \psi_N^{-1} F(\bar{f}^N(x)), \quad x \in \mathbb{R}^n.$$

**Proposition 6** *Suppose that Assumptions 2 to 4 hold with  $v = s$ . Then there exists  $\sigma \in \mathbb{R}_{>0}$  such that, at  $k_1 \in \mathbb{K}$ ,*

$$\mathbf{E}\{V(x(k_1)) \mid x(0)\} - V(x(0)) \leq \sigma \mathbf{E}\{|w(k)|^s\} - \phi(x(0)). \quad (24)$$

**PROOF.** See Section 7.  $\square$

**Corollary 7** *Suppose that (17b) and Assumptions 2 to 4 hold with  $v = s$ , that*

$$\mathbf{E}\{|x(0)|^s\} < \infty, \quad \mathbf{E}\{|w(k)|^s\} < \infty$$

*and that there exists  $\rho \in (0, 1]$  such that*

$$L(x, u_0(x)) - \psi_N^{-1} F(\bar{f}^N(x)) \geq \rho F(x), \quad \forall x \in \mathbb{R}^n. \quad (25)$$

*Then the expectation of  $|x(k_i)|^c$ ,  $k_i \in \mathbb{K}$  converges exponentially to a bounded set, i.e., for all  $k_i \in \mathbb{K}$ ,*

$$\mathbf{E}\{|x(k_i)|^c\} \leq \frac{\lambda_F(1-\rho)^i}{\alpha_L} \mathbf{E}\{|x(0)|^s\} + \frac{\sigma}{\rho\alpha_L} \mathbf{E}\{|w(k)|^s\},$$

*with  $\sigma \in \mathbb{R}$ . Here,  $\alpha_L$  is given in (17b) and  $\lambda_F$ , in (18c).*

**PROOF.** Proposition 6 establishes that  $V(x(k_i))$  is a stochastic Lyapunov-like function for the closed loop at the time instants  $k_i \in \mathbb{K}$ . In fact, if (25) holds, then Lemma 4 gives that  $\phi(x(k_i)) \geq \rho V(x(k_i))$ ,  $\forall k_i \in \mathbb{K}$ , so that, by (24),

$$\mathbf{E}\{V(x(k_1)) \mid x(0)\} - V(x(0)) \leq \sigma \mathbf{E}\{|w(k)|^s\} - \rho V(x(0)).$$

Given (17) and since  $\{x\}_{\mathbb{K}}$  is Markovian, we can use [46, Prop. 3.2] to conclude that:

$$\mathbf{E}\{V(x(k_i)) \mid x(0)\} \leq (1-\rho)^i V(x(0)) + \sigma \mathbf{E}\{|w(k)|^s\} \sum_{\ell=0}^{i-1} (1-\rho)^\ell, \quad \forall i \geq 1. \quad (26)$$

The result now follows from using (17b), (18c), Lemma 4 and taking expectation; see, e.g., [50, p.341].  $\square$

Whilst Corollary 7 examines only  $\{x\}_{\mathbb{K}}$ , i.e., the plant state at the instants of successful transmission, the following theorem establishes boundedness of  $\mathbf{E}\{|x(k)|^s\}$  for all  $k \in \mathbb{N}_0$ .

**Theorem 8** *Suppose that (25) and Assumptions 1 to 4 hold with  $b = c = v = s$ . Then there exist  $C_1, C_2 \in \mathbb{R}_{>0}$  such that, for all  $i \in \mathbb{N}_0$ ,*

$$\max_{k \in \{k_i, k_i+1, \dots, k_i+\Delta(i)-1\}} \mathbf{E}\{|x(k)|^s\} \leq C_1(1-\rho)^i \mathbf{E}\{|x(0)|^s\} + C_2 \mathbf{E}\{|w(k)|^s\}. \quad (27)$$

**PROOF.** See Section 8.  $\square$

Theorem 8 constitutes the main result of the present work. It gives a sufficient condition for stochastic stability of the NCS in the presence of disturbances and Markovian dropouts. Our result establishes that, if the conditions of the theorem

are met, then  $\mathbf{E}\{|x(k)|^s\}$  is bounded for all  $k \in \mathbb{N}_0$ . Furthermore, by taking  $i \rightarrow \infty$ , the bound in (27) provides:

$$\lim_{k \rightarrow \infty} \mathbf{E}\{|x(k)|^s\} \leq C_2 \mathbf{E}\{|w(k)|^s\}. \quad (28)$$

Thus, if  $\mathbf{E}\{|w(k)|^s\} = 0$ , then one obtains that<sup>4</sup>

$$\lim_{k \rightarrow \infty} \mathbf{E}\{|x(k)|^s\} = 0. \quad (29)$$

The condition (25) involves the upper bound of the plant growth rate,  $\gamma$ , the dropout distribution parameters  $p$  and  $q$ , and the cost function parameters  $N$ ,  $F(\cdot)$  and  $L(\cdot, \cdot)$ . The result confirms that, it is desirable that  $q \approx 1$ ,  $p \approx 0$ ,  $\gamma \approx 1$  and  $N$  be large. More details on how to choose the design parameters are given in the following section.

**Remark 9** Since (19) is a global condition (see also [8]), Assumption 3 will, in general, not be satisfied if (1) is open-loop unstable outside a bounded region and  $\mathbb{U}$  is bounded; cf., [22]. To examine such situations and also to incorporate state constraints, it would be desirable to replace (19) by a local condition, which needs to hold only in some bounded set, say  $\mathbb{X}_f \subset \mathbb{R}^n$ ; see, e.g., [51] and also [39, 40], which use similar ideas for NCSs where  $\Delta(i)$  and the disturbances are uniformly bounded. In the present case, where disturbances and consecutive dropouts are unbounded, the situation is significantly more difficult to handle. In fact, to prove boundedness of  $\mathbf{E}\{|x(k)|^s\}$  following along the lines adopted in the present work, one would require that  $\mathbb{X}_f$  be a robust invariant set of  $\{x\}_{\mathbb{K}}$ , see (14). Since the maximum number of consecutive dropouts is unbounded, for plants which are open-loop unstable outside a bounded region, this will in general not hold. We conclude that the issue of formulating local conditions deserves further study.  $\square$

## 6 Choice of Design Parameters

The stability result in Theorem 8 suggests that one may incorporate (25) as an additional constraint on  $\bar{f}^N(x)$  in the minimization of the cost function. The following corollary shows how to design the cost function parameters in (8) such that stochastic stability can be guaranteed without requiring additional constraints in the optimization. Our result also sheds some light into closed loop performance by quantifying the convergence factor  $1 - \rho$  in (27).

**Corollary 10** *If the assumptions of Theorem 8 hold and*

$$F(x) < (1 + \psi_N)L(x, u_0(x)), \quad \forall x \in \mathbb{R}^n, \quad (30)$$

then  $\{x\}_{\mathbb{N}_0}$  satisfies (27) for all  $\rho \in (0, \rho_N^*)$ , where

$$\rho_N^* \triangleq \frac{L(x, u_0(x))}{F(x)} + \psi_N^{-1} \left( \frac{L(x, u_0(x))}{F(x)} - 1 \right) > 0. \quad (31)$$

<sup>4</sup> As shown in [44], if there are no disturbances, then Assumption 2 is not needed to establish (29).

**PROOF.** If (30) is satisfied, and since  $\psi_N > 0$ , for all  $\rho \in (0, \rho_N^*)$  and all  $x \in \mathbb{R}^n$ , we have  $F(x) \leq (1 + \psi_N)L(x, u_0(x))/(1 + \rho\psi_N)$ , which is equivalent to

$$\rho F(x) \leq \psi_N^{-1}(L(x, u_0(x)) - F(x)) + L(x, u_0(x)). \quad (32)$$

On the other hand, (21) and (15) provide the bound  $F(\bar{f}^N(x)) \leq F(x) - L(x, u_0(x)) - \sum_{\ell=1}^{N-1} L(\bar{f}^\ell(x), u_\ell(x)) \leq F(x) - L(x, u_0(x))$ , which upon substitution into (32) implies (25). The result follows from Theorem 8.  $\square$

Corollary 10 allows us to conclude that the NCS will be stable if the weighting functions  $F(\cdot)$  and  $L(\cdot, \cdot)$  are chosen to be compatible with Assumptions 1 to 4 and the bound in (30). To further elucidate this result, we observe that  $\psi_{\ell+1} \geq \psi_\ell$ ,  $\forall \ell \in \mathbb{N}$ , and  $\lim_{\ell \rightarrow \infty} \psi_\ell = \infty$ . Thus, choosing larger horizon lengths  $N$  is beneficial for fulfilling (30) and hence guaranteeing stability, in the sense of (27). Moreover, for any design which satisfies Assumptions 1 to 4, stability can be ensured if a sufficiently large horizon length is used. In fact,  $\{x\}_{\mathbb{N}_0}$  satisfies (27) if  $N \in \mathbb{N}$  is chosen such that

$$N > 1 + \log \left( \frac{\tau(1 - p\gamma)L(x, u_0(x))}{F(x) - L(x, u_0(x))} \right) / \log(p), \quad \forall x \in \mathbb{R}^n,$$

where  $\tau^{-1} \triangleq (1 - q)(\gamma - 1)$ . Note that (23) gives that

$$1 - \rho_N^* = \left( 1 - \frac{L(x, u_0(x))}{F(x)} \right) \left( 1 + \frac{p^N}{\tau p(1 - p\gamma)} \right). \quad (33)$$

Thus, the bound on the convergence factor  $1 - \rho_N^*$  in (31) is exponentially decreasing in  $N$  with limiting value

$$\lim_{N \rightarrow \infty} 1 - \rho_N^* = 1 - L(x, u_0(x))/F(x).$$

**Example 1 (Adapted from [52, Example 2.3])** Consider an open-loop unstable plant model of the form (1), where

$$f(x, u, w) = \begin{bmatrix} x_2 + u_1 \\ -\text{sat}(x_1 + x_2) + u_2 \end{bmatrix} + \begin{bmatrix} \sqrt{w^2 + 5} - \sqrt{5} \\ 0 \end{bmatrix}, \quad (34)$$

with

$$x = \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}, \quad u = \begin{bmatrix} u_1 \\ u_2 \end{bmatrix}, \quad \text{sat}(v) = \begin{cases} -1, & \text{if } v < -1, \\ v & \text{if } v \in [-1, 1], \\ 1, & \text{if } v > 1. \end{cases}$$

We fix  $|\cdot|$  as the Euclidean norm. The second component of the plant input is constrained via

$$|u_2(k)| \leq 0.8, \quad \forall k \in \mathbb{N}_0.$$

The network introduces Markovian packet dropouts with failure rate  $1 - q = 0.4$  and recovery rate  $1 - p = 0.45$ .

To control this NCS, we wish to use the PPC formulation of Section 3. The weighting functions are chosen as  $F(x) = 2|x|$ ,  $L(x, u) = |x|$ , which satisfy (17) and (18) with  $\alpha_F = \lambda_F = 2$ , and  $\alpha_L = \lambda_L = b = c = s = 1$ . Since

$$\left| \frac{d\sqrt{w^2 + 5}}{dw} \right| \leq 1, \quad \forall w \in \mathbb{R}$$

and by proceeding as in [52, p.73], we obtain that (34) satisfies (18a) with  $s = 1$ ,  $\lambda_x = 1.618$  and  $\lambda_w = 1$  uniformly. Since  $p = 0.55 < 1/\lambda_x \approx 0.618$ , Lemma 5 gives that Assumption 4 holds with  $\eta = 2$ ,  $v = 1$  and open-loop rate of growth bounded by  $\gamma = 1.618$ . Assumption 3 is also satisfied, since for  $\kappa_f: \mathbb{R}^2 \rightarrow \mathbb{R} \times [-0.8, 0.8]$  chosen as  $\kappa_f(x) = [-x_2 \ 0.8\text{sat}(x_1 + x_2)]^T$ , we have

$$\begin{aligned} F(f(x, \kappa_f(x), 0)) - F(x) + L(x, \kappa_f(x)) \\ = 0.4|\text{sat}(x_1 + x_2)| - |x| \leq 0.4|x_1 + x_2| - |x| \\ \leq 0.8 \max\{|x_1|, |x_2|\} - \max\{|x_1|, |x_2|\} \leq 0. \end{aligned}$$

Given that Assumptions 1 to 4 hold with  $b = c = v = s$ , the results established in the present work can be readily applied. In fact, direct calculations give that  $\psi_\ell = 0.245/p^\ell$ , see (23), and condition (30) becomes

$$2|x| < (1 + 0.245/p^N)|x|, \quad \forall x \in \mathbb{R}^2 \iff p^N < 0.245.$$

Thus, if the horizon and buffer length satisfy  $N \geq 3$ , then Corollary 10 establishes that the NCS is stable in the sense of (27). For example, if one chooses  $N = 3$ , then the convergence factor provided by (33) is given by  $1 - \rho_3^* \approx 0.84$ .  $\square$

## 7 Proof of Proposition 6

Throughout this section, we will write  $x$  instead of  $x(0)$ ,  $\Delta$  for  $\Delta(0)$ , and  $u_\ell$  for  $u_\ell(x(0))$ , see (5). To prove Proposition 6, we will first state, and prove, some technical lemmas.

**Lemma 11** If (18a) holds, then:

$$\mathbf{E}\{|x(\ell) - \bar{f}^\ell(x)|^s \mid x\} \leq \lambda_w \sum_{j=0}^{\ell-1} \lambda_x^j \mathbf{E}\{|w(k)|^s\} \quad (35)$$

for all  $\ell \in \{1, 2, \dots, \Delta\}$ , with  $\Delta \leq N$ .

**PROOF.** Since  $x(\ell) = f^\ell(x, \{w\}_0^{\ell-1})$ , (18a) gives that

$$\begin{aligned} & |f^\ell(x, \{w\}_0^{\ell-1}) - \bar{f}^\ell(x)|^s \\ &= |f(f^{\ell-1}(x, \{w\}_0^{\ell-2}), u_{\ell-1}(x), w(\ell-1)) \\ &\quad - f(\bar{f}^{\ell-1}(x), u_{\ell-1}(x), 0)|^s \\ &\leq \lambda_x |f^{\ell-1}(x, \{w\}_0^{\ell-2}) - \bar{f}^{\ell-1}(x)|^s + \lambda_w |w(\ell-1)|^s. \end{aligned}$$

The result follows from noting that  $\{w\}_{\mathbb{N}_0}$  is i.i.d.  $\square$

**Lemma 12** Define

$$\beta_{\Delta, \ell} \triangleq \lambda_w \lambda_x^{\ell-\Delta} \sum_{j=0}^{\Delta-1} \lambda_x^j, \quad \tilde{\lambda}_{\Delta, N} \triangleq \lambda_F \beta_{\Delta, N} + \lambda_L \sum_{\ell=\Delta}^{N-1} \beta_{\Delta, \ell}. \quad (36)$$

If  $\Delta \leq N$ , and Assumptions 2 and 3 hold, then:

$$\begin{aligned} & \mathbf{E}\{V(x(k_1)) \mid x\} - V(x) \\ & \leq \tilde{\lambda}_{\Delta, N} \mathbf{E}\{|w(k)|^s\} - \sum_{\ell=0}^{\Delta-1} L(\bar{f}^\ell(x), u_\ell(x)). \end{aligned} \quad (37)$$

**PROOF.** We adapt the approach of [40, Lemma 1]. We focus on time instant  $k_1 = \Delta$  and introduce the sequence

$$\{x^\#\}_\Delta^{N+\Delta} \triangleq \{x_\Delta^\#, x_{\Delta+1}^\#, \dots, x_N^\#, x_{N+1}^\#, \dots, x_{N+\Delta}^\#\}. \quad (38)$$

Its first  $N - \Delta + 1$  elements are defined recursively via:

$$x_{j+1}^\# = f(x_j^\#, u_j(x), 0), \quad j \in \{\Delta, \dots, N-1\}, \quad (39)$$

with  $x_\Delta^\# = x(k_1)$ ; the remaining  $\Delta$  elements are given by

$$\begin{aligned} x_{j+1}^\# &= f(x_j^\#, u_j^\#, 0), \\ u_j^\# &= \kappa_f(x_j^\#), \quad j \in \{N, \dots, N+\Delta-1\}, \end{aligned} \quad (40)$$

where  $\kappa_f(\cdot)$  is chosen such that (19) holds. We next consider

$$\begin{aligned} \bar{u}^\# &= \{u_\Delta(x), u_{\Delta+1}(x), \dots, u_{N-1}(x), \\ &\quad u_N^\#, u_{N+1}^\#, \dots, u_{N+\Delta-1}^\#\}, \end{aligned}$$

whose first  $N - \Delta$  elements are taken from  $\bar{u}(x)$ , whereas the remaining  $\Delta$  elements are provided by (40). It follows from (8) that the associated cost satisfies:

$$\begin{aligned} J(\bar{u}^\#, x(k_1)) &= F(x_{N+\Delta}^\#) + \sum_{\ell=\Delta}^{N-1} L(x_\ell^\#, u_\ell(x)) \\ &\quad + \sum_{\ell=N}^{N+\Delta-1} L(x_\ell^\#, u_\ell^\#). \end{aligned} \quad (41)$$

Since  $V(x(k_1)) \leq J(\bar{u}^\#, x(k_1))$ , for  $\Delta < N$  we can bound

$$\begin{aligned} & \mathbf{E}\{V(x(k_1)) \mid x\} - V(x) \leq \mathbf{E}\{J(\bar{u}^\#, x(k_1)) \mid x\} - V(x) \\ &= \sum_{\ell=\Delta}^{N-1} \left( \mathbf{E}\{L(x_\ell^\#, u_\ell(x)) \mid x\} - L(\bar{f}^\ell(x), u_\ell(x)) \right) \\ &\quad - F(\bar{f}^N(x)) - \sum_{\ell=0}^{\Delta-1} L(\bar{f}^\ell(x), u_\ell(x)) \\ &\quad + \mathbf{E}\{F(x_{N+\Delta}^\#) \mid x\} + \sum_{\ell=N}^{N+\Delta-1} \mathbf{E}\{L(x_\ell^\#, u_\ell^\#) \mid x\}, \end{aligned} \quad (42)$$

where we have used (15). On the other hand, (18a), (39) and Lemma 11 provide that, for  $\ell \in \{\Delta, \Delta + 1, \dots, N\}$ ,

$$\mathbf{E}\{|x_\ell^\# - \bar{f}^\ell(x)|^s | x\} \leq \beta_{\Delta, \ell} \mathbf{E}\{|w(k)|^s\}, \quad (43)$$

where  $\beta_{\Delta, \ell}$  are defined in (36). By rearranging terms and using (18b), (42) can be rewritten as:

$$\begin{aligned} \mathbf{E}\{V(x(k_1)) | x\} - V(x) &\leq \lambda_L \sum_{\ell=\Delta}^{N-1} \beta_{\Delta, \ell} \mathbf{E}\{|w(k)|^s\} \\ &- \sum_{\ell=0}^{\Delta-1} L(\bar{f}^\ell(x), u_\ell(x)) + \mathbf{E}\{F(x_N^\#) | x\} - F(\bar{f}^N(x)) \\ &+ \sum_{\ell=N}^{N+\Delta-1} \mathbf{E}\{L(x_\ell^\#, u_\ell^\#) + F(x_{\ell+1}^\#) - F(x_\ell^\#) | x\}. \end{aligned}$$

Use of (40), (19) and (18c) provides (37).

For  $\Delta = N$ , we consider

$$\bar{u}^\# = \{u_N^\#, u_{N+1}^\# \dots, u_{2N-1}^\#\},$$

where all  $N$  elements of  $\bar{u}^\#$  are calculated via (40), but with initial value  $x_N^\# = x(k_1)$ . The bound in (37) then follows as in the case  $\Delta < N$  studied above.  $\square$

**Lemma 13** Suppose that  $\Delta > N$ , that (18a), (18c) and Assumptions 3 and 4 hold with  $v = s$ . Furthermore, define

$$\Gamma_{\ell, N} \triangleq \eta \sum_{j=0}^{\ell-N-1} \gamma^j, \quad \tilde{\eta}_{\Delta, N} \triangleq \Gamma_{\Delta, N} + \gamma^{\Delta-N} \lambda_F \beta_{N, N}, \quad (44)$$

where  $\beta_{N, N}$  is as in (36) with  $\Delta = \ell = N$ . Then:

$$\mathbf{E}\{F(x(\ell)) | x\} \leq \gamma^{\ell-N} \mathbf{E}\{F(x(N)) | x\} + \Gamma_{\ell, N} \mathbf{E}\{|w(k)|^s\}, \quad (45)$$

for all  $\ell \in \{N + 1, \dots, \Delta\}$ , and

$$\begin{aligned} \mathbf{E}\{V(x(k_1)) | x\} - V(x) &\leq \tilde{\eta}_{\Delta, N} \mathbf{E}\{|w(k)|^s\} \\ &+ (\gamma^{\Delta-N} - 1)F(\bar{f}^N(x)) - \sum_{\ell=0}^{N-1} L(\bar{f}^\ell(x), u_\ell(x)). \end{aligned} \quad (46)$$

**PROOF.** With  $\ell \in \{N + 1, \dots, \Delta\}$ , (20) gives:

$$\begin{aligned} \mathbf{E}\{F(f(x(\ell-1), 0, w(\ell-1))) | x(\ell-1)\} \\ \leq \gamma F(x(\ell-1)) + \eta \mathbf{E}\{|w(\ell)|^s\}. \end{aligned} \quad (47)$$

Since  $\Delta > N$ , by (14),  $\{x\}_N^{k_1}$  is Markovian. We thus have:

$$\begin{aligned} \mathbf{E}\{F(x(\ell)) | x(\ell-1)\} &= \mathbf{E}\{F(x(\ell)) | \{x\}_N^{\ell-1}\} \\ &\leq \gamma F(x(\ell-1)) + \eta \mathbf{E}\{|w(\ell)|^s\}, \end{aligned}$$

where we have used (47). By taking conditional expectation in the above and using the Markov property, we obtain:

$$\begin{aligned} \mathbf{E}\{\mathbf{E}\{F(x(\ell)) | \{x\}_N^{\ell-1}\} | x(N)\} &= \mathbf{E}\{F(x(\ell)) | x(N)\} \\ &\leq \gamma \mathbf{E}\{F(x(\ell-1)) | x(N)\} + \eta \mathbf{E}\{|w(\ell)|^s\}. \end{aligned}$$

The above recursion can be applied  $\ell - N$  times to give  $\Gamma_{\ell, N} \mathbf{E}\{|w(\ell)|^s\} + \gamma^{\ell-N} F(x(N)) \geq \mathbf{E}\{F(x(\ell)) | x(N)\} = \mathbf{E}\{F(x(\ell)) | x(N), x\}$ ; thus, [45, Eq. 1.28], establishes (45).

To prove (46), we set  $\ell = \Delta$  in (45) and use Lemma 4:

$$\begin{aligned} \mathbf{E}\{V(x(k_1)) | x\} - V(x) &\leq \gamma^{\Delta-N} \mathbf{E}\{F(x(N)) | x\} + \Gamma_{\Delta, N} \mathbf{E}\{|w(k)|^s\} - V(x) \\ &= \Gamma_{\Delta, N} \mathbf{E}\{|w(k)|^s\} + \gamma^{\Delta-N} \mathbf{E}\{F(x(N)) | x\} \\ &\quad - F(\bar{f}^N(x)) - \sum_{\ell=0}^{N-1} L(\bar{f}^\ell(x), u_\ell(x)) \\ &\leq \Gamma_{\Delta, N} \mathbf{E}\{|w(k)|^s\} + (\gamma^{\Delta-N} - 1)F(\bar{f}^N(x)) \\ &\quad + \gamma^{\Delta-N} (\mathbf{E}\{F(x(N)) | x\} - F(\bar{f}^N(x))) \\ &\quad - \sum_{\ell=0}^{N-1} L(\bar{f}^\ell(x), u_\ell(x)). \end{aligned}$$

Lemma 11 and Equation (18c) now provide (46).  $\square$

Having established the above results, Proposition 6 can now be proven by using (11) and conditioning upon  $\Delta$  as follows:

$$\begin{aligned} \mathbf{E}\{V(x(k_1)) | x\} &= \mathbf{E}\{\mathbf{E}\{V(x(k_1)) | x, \Delta\}\} \\ &= q \mathbf{E}\{V(x(k_1)) | x, \Delta = 1\} \\ &\quad + (1-q)(1-p) \sum_{i=2}^{\infty} p^{i-2} \mathbf{E}\{V(x(k_1)) | x, \Delta = i\} \\ &= q \mathbf{E}\{V(x(k_1)) | x, \Delta = 1\} \\ &\quad + (1-q)(1-p) \sum_{i=2}^N p^{i-2} \mathbf{E}\{V(x(k_1)) | x, \Delta = i\} \\ &\quad + (1-q)(1-p) \sum_{i=N+1}^{\infty} p^{i-2} \mathbf{E}\{V(x(k_1)) | x, \Delta = i\}. \end{aligned}$$

If we now utilize (37) and (46), then:

$$\begin{aligned}
 & \mathbf{E}\{V(x(k_1)) \mid x\} - V(x) \\
 & \leq q(\tilde{\lambda}_{1,N} \mathbf{E}\{|w(k)|^s\} - L(x, u_0(x))) \\
 & \quad + (1-q)(1-p) \sum_{i=2}^N p^{i-2} \left( \tilde{\lambda}_{i,N} \mathbf{E}\{|w(k)|^s\} \right. \\
 & \quad \quad \left. - \sum_{\ell=0}^{i-1} L(\bar{f}^\ell(x), u_\ell(x)) \right) \\
 & \quad + (1-q)(1-p) \sum_{i=N+1}^{\infty} p^{i-2} \left( \tilde{\eta}_{i,N} \mathbf{E}\{|w(k)|^s\} \right. \\
 & \quad \quad \left. + (\gamma^{i-N} - 1)F(\bar{f}^N(x)) - \sum_{\ell=0}^{N-1} L(\bar{f}^\ell(x), u_\ell(x)) \right).
 \end{aligned}$$

We next define

$$\begin{aligned}
 \sigma \triangleq & q\tilde{\lambda}_{1,N} + (1-q)(1-p) \sum_{i=2}^N p^{i-2} \tilde{\lambda}_{i,N} \\
 & + (1-q)(1-p) \sum_{j=N+1}^{\infty} p^{i-2} \tilde{\eta}_{j,N}, \quad (48)
 \end{aligned}$$

which is finite, since, by Assumption 4,  $p\gamma < 1$ . Therefore,

$$\begin{aligned}
 & \mathbf{E}\{V(x(k_1)) \mid x\} - V(x) \\
 & \leq \sigma \mathbf{E}\{|w(k)|^s\} - qL(x, u_0(x)) \\
 & \quad - (1-q)(1-p) \sum_{i=2}^N p^{i-2} \sum_{\ell=0}^{i-1} L(\bar{f}^\ell(x), u_\ell(x)) \\
 & \quad + (1-q)(1-p) \sum_{i=N+1}^{\infty} p^{i-2} (\gamma^{i-N} - 1)F(\bar{f}^N(x)) \\
 & \quad - (1-q)(1-p) \sum_{i=N+1}^{\infty} p^{i-2} \sum_{\ell=0}^{N-1} L(\bar{f}^\ell(x), u_\ell(x)),
 \end{aligned}$$

which gives:

$$\begin{aligned}
 & \mathbf{E}\{V(x(k_1)) \mid x\} - V(x) \leq \sigma \mathbf{E}\{|w(k)|^s\} \\
 & \quad - \left( q + (1-q)(1-p) \sum_{i=2}^{\infty} p^{i-2} \right) L(x, u_0(x)) \\
 & \quad + (1-q)(1-p) \sum_{i=N+1}^{\infty} p^{i-2} (\gamma^{i-N} - 1)F(\bar{f}^N(x)) \\
 & \quad - (1-q)(1-p) \sum_{i=N+1}^{\infty} p^{i-2} \sum_{\ell=1}^{N-1} L(\bar{f}^\ell(x), u_\ell(x)) \\
 & = \sigma \mathbf{E}\{|w(k)|^s\} - (1-q)p^{N-1} \sum_{\ell=1}^{N-1} L(\bar{f}^\ell(x), u_\ell(x)) \\
 & \quad - L(x, u_0(x)) + (1-q)p^{N-1} \left( \frac{\gamma-1}{1-p\gamma} \right) F(\bar{f}^N(x)),
 \end{aligned}$$

since  $p\gamma < 1$ . This completes the proof of Proposition 6.  $\square$

## 8 Proof of Theorem 8

We will denote  $x(0)$  by  $x$ , and  $\Delta(0)$  by  $\Delta$ . By Corollary 7, (26) holds for all  $k_i \in \mathbb{K}$ . We next examine instants  $k \notin \mathbb{K}$ . For that purpose, we condition upon  $\Delta$  to obtain:

$$\begin{aligned}
 & \sum_{j=0}^{k_1-1} \mathbf{E}\{|x(j)|^s \mid x\} = \sum_{\ell=0}^{\Delta-1} \mathbf{E}\{|x(\ell)|^s \mid x\} \\
 & = q \mathbf{E}\{|x|^s \mid x, \Delta = 1\} \\
 & \quad + (1-q)(1-p) \sum_{i=2}^{\infty} p^{i-2} \sum_{\ell=0}^{i-1} \mathbf{E}\{|x(\ell)|^s \mid x, \Delta = i\} \\
 & = q \mathbf{E}\{|x|^s \mid x, \Delta = N\} \\
 & \quad + (1-q)(1-p) \sum_{i=2}^N p^{i-2} \sum_{\ell=0}^{i-1} \mathbf{E}\{|x(\ell)|^s \mid x, \Delta = N\} \\
 & \quad + (1-q)(1-p) \sum_{i=N+1}^{\infty} p^{i-2} \sum_{\ell=0}^{i-1} \mathbf{E}\{|x(\ell)|^s \mid x, \Delta = i\} \\
 & \leq q \sum_{\ell=0}^{N-1} \mathbf{E}\{|x(\ell)|^s \mid x, \Delta = N\} \\
 & \quad + (1-q)(1-p) \sum_{i=2}^{\infty} p^{i-2} \sum_{\ell=0}^{N-1} \mathbf{E}\{|x(\ell)|^s \mid x, \Delta = N\} \\
 & \quad + (1-q)(1-p) \sum_{i=N+1}^{\infty} p^{i-2} \sum_{\ell=N}^{i-1} \mathbf{E}\{|x(\ell)|^s \mid x, \Delta = i\} \\
 & = \sum_{\ell=0}^{N-1} \mathbf{E}\{|x(\ell)|^s \mid x, \Delta = N\} \\
 & \quad + (1-q)(1-p) \sum_{i=N+1}^{\infty} p^{i-2} \sum_{\ell=N}^{i-1} \mathbf{E}\{|x(\ell)|^s \mid x, \Delta = i\}.
 \end{aligned}$$

Expression (17a), then provides the bound:

$$\begin{aligned}
 & \sum_{j=0}^{k_1-1} \mathbf{E}\{|x(j)|^s \mid x\} \\
 & \leq \sum_{\ell=0}^{N-1} \mathbf{E}\{|x(\ell) - \bar{f}^\ell(x) + \bar{f}^\ell(x)|^s \mid x, \Delta = N\} \\
 & \quad + \frac{(1-p)}{\alpha_F/(1-q)} \sum_{i=N+1}^{\infty} p^{i-2} \sum_{\ell=N}^{i-1} \mathbf{E}\{F(x(\ell)) \mid x, \Delta = i\}.
 \end{aligned}$$

On the other hand, for all  $y, z \in \mathbb{R}^n$  and all  $s \in \mathbb{R}_{>0}$ ,

$$\begin{aligned}
 |y+z|^s & \leq 2 \max(|y|, |z|)^s + 2 \min(|y|, |z|)^s \\
 & = 2^s (|y|^s + |z|^s)
 \end{aligned}$$

Lemmas 11 and 13 then give that

$$\begin{aligned}
 \sum_{j=0}^{k_1-1} \mathbf{E}\{|x(j)|^s | x\} &\leq 2^s \lambda_w \sum_{\ell=0}^{N-1} \sum_{j=0}^{\ell-1} \lambda_x^j \mathbf{E}\{|w(k)|^s\} \\
 &+ 2^s \sum_{\ell=0}^{N-1} \mathbf{E}\{|\bar{f}^\ell(x)|^s | x, \Delta = N\} \\
 &+ \frac{1-p}{\alpha_F/(1-q)} \sum_{i=N+1}^{\infty} p^{i-2} \sum_{\ell=N}^{i-1} \gamma^{\ell-N} \mathbf{E}\{F(x(N)) | x\} \\
 &+ \frac{1-p}{\alpha_F/(1-q)} \sum_{i=N+1}^{\infty} p^{i-2} \sum_{\ell=N}^{i-1} \Gamma_{\ell,N} \mathbf{E}\{|w(k)|^s\}.
 \end{aligned}$$

By Assumption 4,  $p\gamma < 1$ . Therefore, it is easy to see that all sums above are convergent. Furthermore, (18c) provides

$$F(x(N)) \leq \lambda_F |x(N) - \bar{f}^N(x)|^s + F(\bar{f}^N(x)).$$

Having established the above, we can use Lemma 11 to conclude that there exist finite constants  $C'_1$  and  $C_3$ , which are independent of  $x$  and provide the bound  $\sum_{j=0}^{k_1-1} \mathbf{E}\{|x(j)|^s | x\} \leq C'_1 V(x) + C_3 \mathbf{E}\{|w(k)|^s\}$ . In a similar manner, it can be shown that  $\exists C'_1, C_3 \in \mathbb{R}$  such that

$$\sum_{j=k_i}^{k_{i+1}-1} \mathbf{E}\{|x(j)|^s | x(k_i)\} \leq C'_1 V(x(k_i)) + C_3 \mathbf{E}\{|w(k)|^s\},$$

for all  $k_i \in \mathbb{K}$ . Since  $\{x\}_{\mathbb{K}}$  is Markovian, by taking conditional expectation and using (26), we have

$$\sum_{j=k_i}^{k_{i+1}-1} \mathbf{E}\{|x(j)|^s | x\} \leq C'_1 (1-\rho)^i V(x) + C_2 \mathbf{E}\{|w(k)|^s\},$$

for all  $k_i \in \mathbb{K}$ , and where

$$C_2 \triangleq \sigma C'_1 \sum_{\ell=0}^{i-1} (1-\rho)^\ell + C_3 \leq \frac{\sigma C'_1}{\rho} + C_3 < \infty.$$

As a consequence, it holds that

$$\begin{aligned}
 \max_{j \in \{k_i, k_i+1, \dots, k_i+\Delta(i)-1\}} \mathbf{E}\{|x(j)|^s | x\} \\
 \leq C'_1 (1-\rho)^i V(x) + C_3 \mathbf{E}\{|w(k)|^s\},
 \end{aligned}$$

which gives

$$\begin{aligned}
 \max_{j \in \{k_i, k_i+1, \dots, k_i+\Delta(i)-1\}} \mathbf{E}\{|x(j)|^s\} \\
 \leq C'_1 (1-\rho)^i \mathbf{E}\{V(x)\} + C_2 \mathbf{E}\{|w(k)|^s\} \\
 \leq C'_1 (1-\rho)^i \lambda_F \mathbf{E}\{|x|^s\} + C_2 \mathbf{E}\{|w(k)|^s\},
 \end{aligned}$$

where we have used (18c) and (21). Setting  $C_1 = C'_1 \lambda_F$ , establishes (27).

## 9 Conclusions

This work has studied a NCS architecture where a packetized predictive controller uses an unreliable network affected by Markovian packet-dropouts to control a nonlinear plant with unbounded disturbances. It has been shown that, provided that the plant and network satisfy suitable conditions, stochastic stability of the closed loop can be ensured by appropriate choice of tuning parameters. Future research could include the study of more general NCSs, including where the controller does not have access to the plant state.

## References

- [1] J. Baillieul and P. Antsaklis. Control and communication challenges in networked real-time systems. *Proc. IEEE*, 95(1):9–27, January 2007.
- [2] G. C. Walsh, H. Ye, and L. G. Bushnell. Stability analysis of networked control systems. *IEEE Trans. Automat. Contr.*, 10(3):438–446, 2002.
- [3] D. Nešić and A. R. Teel. Input-to-state stability of networked control systems. *Automatica*, 40:2121–2128, 2004.
- [4] J. Xiong and J. Lam. Stabilization of networked control systems with a logic ZOH. *IEEE Trans. Automat. Contr.*, 54(2):358–363, February 2009.
- [5] M. Tabbara, D. Nešić, and A. R. Teel. Stability of wireless and wireline networked control systems. *IEEE Trans. Automat. Contr.*, 52(9):1615–1630, September 2007.
- [6] M. B. G. Cloosterman, N. van de Wouw, W. P. M. H. Heemels, and H. Nijmeijer. Stability of networked control systems with uncertain time-varying delays. *IEEE Trans. Automat. Contr.*, 54(7):1575–1580, July 2009.
- [7] A. Hassibi, S. P. Boyd, and J. P. How. Control of asynchronous dynamical systems with rate constraints on events. In *Proc. IEEE Conf. Decis. Contr.*, pages 1345–1351, Phoenix, AZ, 1999.
- [8] D. Muñoz de la Peña and P. D. Christofides. Stability of nonlinear asynchronous systems. *Syst. & Contr. Lett.*, 57:465–473, 2008.
- [9] A. S. Matveev and A. V. Savkin. Comments on "control over noisy channels" and relevant negative results. *IEEE Trans. Automat. Contr.*, 50(12):2105–2110, December 2005.
- [10] O. C. Imer, S. Yüksel, and T. Başar. Optimal control of LTI systems over unreliable communication links. *Automatica*, 42(9):1429–1439, September 2006.
- [11] H. Gao, X. Meng, and T. Chen. Stabilization of networked control systems with a new delay characterization. *IEEE Trans. Automat. Contr.*, 53(9):2142–2148, October 2008.
- [12] L. Schenato, B. Sinopoli, M. Franceschetti, K. Poolla, and S. S. Sastry. Foundations of control and estimation over lossy networks. *Proc. IEEE*, 95(1):163–187, January 2007.
- [13] M. Tabbara and D. Nešić. Input-output stability of networked control systems with stochastic protocols and channels. *IEEE Trans. Automat. Contr.*, 53(5):1160–1175, June 2008.
- [14] Y. Zhao, H. Gao, and T. Chen. Fuzzy constrained predictive control of non-linear systems with packet dropouts. *IET Control Theory Appl.*, 4(9):1665–1677, September 2009.
- [15] H. Ishii. Limitations in remote stabilization over unreliable channels without acknowledgements. *Automatica*, 45:2278–2285, 2009.
- [16] L. Shi, L. Xie, and R. M. Murray. Kalman filtering over a packet-delaying network: A probabilistic approach. *Automatica*, 45(9):2134–2140, September 2009.

- [17] K. Tsumura, H. Ishii, and H. Hoshina. Tradeoffs between quantization and packet loss in networked control of linear systems. *Automatica*, 45:2963–2970, 2009.
- [18] D. Bernardini, M. C. F. Donkers, A. Bemporad, and W. P. M. H. Heemels. A model predictive control approach for stochastic networked control systems. In *Proc. 2nd IFAC Workshop on Distributed Estimation and Control in Networked Systems*, Anney, France, 2010.
- [19] Y. Liang, T. Chen, and Q. Pan. Optimal linear state estimator with multiple packet dropouts. *IEEE Trans. Automat. Contr.*, 55(6):1428–1433, June 2010.
- [20] D. Antunes, J. P. Hespanha, and C. Silvestre. Control of impulsive renewal systems: Application to direct design in networked control. In *Proc. IEEE Conf. Decis. Contr.*, pages 6882–6887, Shanghai, China, 2009.
- [21] D. Antunes, J. P. Hespanha, and C. Silvestre. Stochastic hybrid systems with renewal transitions. In *Proc. Amer. Contr. Conf.*, pages 3124–3129, Baltimore, MD, 2010.
- [22] D. Chatterjee, A. Amin, P. Hokayem, J. Lygeros, and S. S. Sastry. Mean-square boundedness of stochastic networked control systems with bounded control inputs. In *Proc. IEEE Conf. Decis. Contr.*, pages 4759–4764, Atlanta, GA, December 2010.
- [23] E. N. Gilbert. Capacity of a burst-noise channel. *The Bell Syst. Tech. J.*, 39:1253–1265, September 1960.
- [24] E. O. Elliot. Estimates of error rates for codes on burst-noise channels. *The Bell Syst. Tech. J.*, 42:1977–1997, September 1963.
- [25] L. Lindbom, A. Ahlén, M. Sternad, and M. Falkenström. Tracking of time-varying mobile radio channels—part II: A case study. *IEEE Trans. Commun.*, 50(1):156–167, January 2002.
- [26] Y. Shi and B. Yu. Output feedback stabilization of networked control systems with random delays modeled by Markov chains. *IEEE Trans. Automat. Contr.*, 54(7):1668–1674, July 2009.
- [27] J. Wu and T. Chen. Design of networked control systems with packet dropouts. *IEEE Trans. Automat. Contr.*, 52(7):1314–1319, July 2007.
- [28] J. Xiong and J. Lam. Stabilization of linear systems over networks with bounded packet loss. *Automatica*, 43:80–87, 2007.
- [29] M. Huang and S. Dey. Stability of Kalman filtering with Markovian packet losses. *Automatica*, 43(4):598–607, April 2007.
- [30] S. C. Smith and P. Seiler. Estimation with lossy measurements: Jump estimators for jump systems. *IEEE Trans. Automat. Contr.*, 48(12):2163–2171, December 2003.
- [31] P. Seiler and R. Sengupta. An  $\mathcal{H}_\infty$  approach to networked control. *IEEE Trans. Automat. Contr.*, 50(3):356–364, March 2005.
- [32] L. Xie and L. Xie. Stability analysis of networked sampled-data linear systems with Markovian packet losses. *IEEE Trans. Automat. Contr.*, 54(6):1375–1381, June 2009.
- [33] K. You and L. Xie. Minimum data rate for mean square stabilizability of linear systems with Markovian packet losses. *IEEE Trans. Automat. Contr.*, 56(4):772–785, April 2011.
- [34] L. A. Montestruque and P. Antsaklis. Stability of model-based networked control systems with time-varying transmission times. *IEEE Trans. Automat. Contr.*, 49(9):1562–1572, September 2004.
- [35] W. Hu, G. Liu, and D. Rees. Event-driven networked predictive control. *IEEE Trans. Ind. Electron.*, 54(3):1603–1613, June 2007.
- [36] D. E. Quevedo, E. I. Silva, and G. C. Goodwin. Control over unreliable networks affected by packet erasures and variable transmission delays. *IEEE J. Select. Areas Commun.*, 26(4):672–685, May 2008.
- [37] J. B. Rawlings and D. Q. Mayne. *Model Predictive Control: Theory and Design*. Nob Hill Publishing, Madison, WI, 2009.
- [38] A. Casavola, E. Mosca, and M. Papini. Predictive teleoperation of constrained dynamic systems via internet-like channels. *IEEE Trans. Contr. Syst. Technol.*, 14(4):681–694, July 2006.
- [39] D. Muñoz de la Peña and P. D. Christofides. Lyapunov-based model predictive control of nonlinear systems subject to data losses. *IEEE Trans. Automat. Contr.*, 53(9):2076–2089, September 2008.
- [40] D. E. Quevedo and D. Nešić. Input-to-state stability of packetized predictive control over unreliable networks affected by packet-dropouts. *IEEE Trans. Automat. Contr.*, 56(2):370–375, February 2011.
- [41] Y. Ishido, K. Takaba, and D. E. Quevedo. Stability analysis of networked control systems subject to packet-dropouts and finite-level quantization. *Syst. & Contr. Lett.*, 60(5):325–332, May 2011.
- [42] G. Pin and T. Parisini. Networked predictive control of uncertain constrained nonlinear systems: Recursive feasibility and input-to-state stability analysis. *IEEE Trans. Automat. Contr.*, 56(1):72–87, January 2011.
- [43] D. E. Quevedo, J. Østergaard, and D. Nešić. Packetized predictive control of stochastic systems over bit-rate limited channels with packet loss. *IEEE Trans. Automat. Contr.*, 56(12):2854–2868, December 2011.
- [44] D. E. Quevedo and D. Nešić. On stochastic stability of packetized predictive control of non-linear systems over erasure channels. In *8th IFAC Symposium on Nonlinear Control Systems*, September 2010.
- [45] H. Kushner. *Introduction to Stochastic Control*. Holt, Rinehart and Winston, Inc., New York, N.Y., 1971.
- [46] S. P. Meyn. Ergodic theorems for discrete time stochastic systems using a stochastic Lyapunov function. *SIAM Journal on Control and Optimization*, 27(6):1409–1439, November 1989.
- [47] L. Schenato. To zero or to hold control inputs with lossy links? *IEEE Trans. Automat. Contr.*, 54(5):1093–1099, May 2009.
- [48] H. J. Kushner and L. Tobias. On the stability of randomly sampled systems. *IEEE Trans. Automat. Contr.*, AC-14(4):319–324, August 1969.
- [49] V. Gupta and N. C. Martins. On stability in the presence of analog erasure channels between controller and actuator. *IEEE Trans. Automat. Contr.*, 55(1):175–179, January 2010.
- [50] M. Loève. *Probability Theory*. D. Van Nostrand Company, Inc, 3rd edition, 1963.
- [51] M. Cannon, V. Deshmukh, and B. Kouvaritakis. Nonlinear model predictive control with polytopic invariant sets. *Automatica*, 39(8):1487–1494, August 2003.
- [52] H. K. Khalil. *Nonlinear Systems*. Prentice Hall, 2nd edition, 1996.